

**LFCS**

---

**Laboratory for Foundations of Computer Science**  
Department of Computer Science - University of Edinburgh

**The Definition of Standard ML  
Version 2**

by

Robert Harper  
Robin Milner  
Mads Tofte

The Definition of Standard ML  
Version 2

**LFCS Report Series**

**LFCS**  
Department of Computer Science  
University of Edinburgh  
The King's Buildings  
Edinburgh EH9 3JZ

**ECS-LFCS-88-62**

(also published as CSR-274-88)

**August 1988**

**Copyright © 1988, LFCS**

# The Definition of Standard ML

## Version 2

Robert Harper      Robin Milner

Mads Tofte

Laboratory for Foundations of Computer Science

Department of Computer Science

University of Edinburgh

Edinburgh EH9 3JZ, Scotland

1 August 1988

Edinburgh, 23 September 1988

## ERRATA

Most of the following mistakes were spotted by David Berry, Kevin Mitchell and David Matthews.

Notation:  $p5, L7$  refers to line 7 on page 5, whereas  $L - 7$  refers to line 7 from the bottom.

- $p v, L8$  for “declarationstype” read “declarations type”
- $p v, L19$  for “demanding than” read “demanding that”
- $p v, L - 11$  for “understand that” read “understand than”
- $p6, L - 11$  for “effect” read “affect”
- $p7, L - 4$  for “more tightly that” read “more tightly than”
- $p16, L8$  for “conponent” read “component”
- $p16, L - 1$  for “domain)from” read “domain) from”
- $p18, L - 10$  should be “ $((T \text{ of } C) \cup T, (U \text{ of } C), (E \text{ of } C) + VE)$ ”
- $p34, L - 6$  for “exists a realisation” read “exists precisely one realisation”
- $p50, L - 4$  for “packet then rule 115” read “packet then rule 115 or rule 116”
- $p57$  rule 157, for “ $\Rightarrow E$ ” read “ $\Rightarrow E'$ ”, both in the premise and in the conclusion (to avoid confusion with the  $E$  of  $B$ ).
  
- $p62, L2$  for “yield” read “yields”
- $p62, L2$  for “(either because” read “(for instance because”
- $p62, L3$  delete “because of”
- $p62$  rule 189, in the second premise, for  $\vdash$  read  $\vdash_{\text{DYN}}$
- $p76, L11$  for “returns exception packet” read “returns the exception packet”
- $p78, L4$  for “I am” read “We are”
- $p79, L19$  for “function argument structure” read “functor argument structure”
  
- $p80, L20$  for “was supported” read “supported”
- $p81, L8$  after “Rutherford-Appleton Laboratory” insert “, by Aaron Slo-  
man’s group at the University of Sussex (POPLOG)”
- $p87, L4$  (first column) add the entry:  $\langle \prime \rangle$  (on variables), 38

## Preface to Version 2

This second Version of the definition of Standard ML incorporates some corrections to Version 1 [16], and also some extensions. As far as the Core language is concerned, it is consistent with the informal description [15] as modified by [23] and [1].

Great care was taken to make Version 1 clear, accurate and complete, and great care has been taken to revise it in the same spirit. The language may undergo changes in the future, but we have adopted a very conservative policy keeping changes to a bare minimum. Any future Version of this document will indicate precisely how it differs from its predecessor.

We shall first list the the changes from Version 1 and then list the few parts of the language which are considered somewhat experimental. Readers not familiar with Version 1 may skip the following list of changes.

### CHANGES

Unless otherwise stated, references refer to Version 2.

1. The title of the document has been changed from “The Semantics of Standard ML” to “The Definition of Standard ML” since the document defines the language, syntax as well as semantics.
2. Appendix E describing how ML evolved has been added, see page 77.
3. An Index and a list of references have been added, see pages 86 and 83.
4. As envisaged in the preface to Version 1, a uniform treatment of exceptions and constructors has been adopted. The idea is explained in [1]. The changes to the semantics are consistent with the changes detailed in [1].
5. A new section, Section 8, pages 61–62, defining the syntax and semantics of Programs has been added. In particular, the interactive nature of the language has been made explicit.
6. The “applied” functor forms (Version 1, Section 3.4) have been given the status of derived forms and moved to Appendix A, page 65, while the “pure” forms (Version 1, Section 3.6) have been moved to the grammar itself (Section 3.4, pages 12 and 14). This entails that functors can be applied to structure expressions as well as to declarations.
7. The Closure Restrictions on signature expressions and functors (Version 1, Section 3.7) have been relaxed, see Section 3.6 page 14.

8. A new section “Signature Matching” has been inserted in the static semantics for Modules, see page 34. In this, it is clarified that matching a structure against a signature is a combination of instantiation and enrichment. In addition, the definition of functor signature matching has been simplified using the notion of matching, see page 43.
9. A type discipline for polymorphic references and exceptions has been provided. To this end, a distinction between *imperative* and *applicative* type variables has been introduced (page 16), together with the notions of *imperative types* (page 19) and *non-expansive expressions* (page 20). The definition of instantiation of type schemes is modified so that imperative type variables are instantiated with imperative types only, and the definition of the closure operation is modified to distinguish between expansive and non-expansive expressions (page 21). The modified inference rules are: the rule for value declarations (rule 16, page 25); the rules for exception bindings (rules 30 and 31, page 27); and the rule for declarations as structure-level declarations (rule 55, page 37).
10. Rule 85 in Version 1 concerning type sharing was wrong. It did not allow sharing between a type and a datatype. The corrected rule (rule 85, page 41) allows such sharing. For two type structures to satisfy a sharing equation, their type names (or more generally, their type functions), must be the same; however, the rule now allows the one type structure to have an empty constructor environment and the other to have a non-empty constructor environment, in accordance with the general principle that different consistent “views” can coexist.
11. The treatment of explicit type variables has been changed so that the scope of explicit type variables can be given by syntactic rules, see Section 4.6 page 19. These rules replace the rules given in [15]. The latter depended on traversing the program text in a particular order and one could give examples where, for instance, the textual ordering of the components of a pair would be significant for the scoping. The new rules do not have this defect.
12. The treatment of *abstype* has been corrected. Let  $dec'$  be a declaration of the form *abstype datbind with dec end* and let *tycon* be a type constructor declared by *datbind*. If the elaboration of *datbind* makes *tycon* an equality type, then the equality on *tycon* can be used in the body, *dec*, but the equality is not exported outside  $dec'$ . In Version 1, the equality was “exported” unintentionally. Thus the definition of *Abs* is revised (page 22) and the inference rule for *abstype* has been changed (page 25).
13. The symbol *#* is introduced as a reserved word (page 3). Moreover, it is admitted in symbolic identifiers (page 4).

14. We use the term “constructor binding” instead of “datatype construction”. The syntactic classes are renamed accordingly. For instance, a declaration of a single datatype now takes the form

*datatype tyvarseq tycon = conbind*

15. It has been clarified that the equality attributes of bound type variables in type functions are not significant (page 19), and that the equality attributes of bound type variables in type schemes are significant (page 19). For instance, the type declaration `type 'a t = 'a list` and `type ''a t = ''a list` are equivalent, but the value specifications `val x: 'a -> 'a` and `val x: ''a -> ''a` are not.
16. The rule for functor signature expressions has been corrected, see rule 91, page 42. The result part of a functor signature resulting from the elaboration of a functor signature expression must be principal.

This concludes the list of changes from Version 1. We now list the few parts of the language that are considered somewhat experimental and where feed-back from users is needed and encouraged.

- The derived forms of functors (Appendix A) are somewhat experimental. It is sometimes convenient to be able to apply a functor to, say, a single value or a single type, rather than demanding that functors be applied to structures only; on the other hand, having both forms in the language may result in programming mistakes.
- The type discipline for polymorphic references and exceptions in the present version is built on the system developed and proved sound by Tofte [29]. As Damas' system [8], it is built on the idea of a boolean attribute of type variables. David MacQueen has suggested a more refined discipline, currently implemented in the New Jersey compiler, where the binary attribute is replaced by a weakness level, which is a natural number. While the present type discipline is simpler to use and understand than the more refined scheme, experience may show that the simple scheme admits too few programs. Since programs that are admitted under the simple scheme are also admitted under the more refined scheme, it seems sensible to start out with the simple scheme. The New Jersey compiler is currently being modified to support both schemes.
- No syntax has yet been added to the language which dictates exactly where functor specifications may be used. However, it is envisaged that if a compiler is asked to separately compile a functor  $g$  which makes reference to a functor identifier  $f$ , then the compiler will demand a specification for  $f$ . Moreover, it is envisaged that the compiled  $g$  should only be imported into a

basis if that basis contains a functor  $f$  which matches the given specification according to the definition given in Section 5.14, page 43 .

Edinburgh, 1 August 1988

## Preface to Version 1

Great care has been taken to make this document clear, accurate and complete. Despite this we have called it "Version 1", since we expect to amend it for various reasons.

First, neither the greatest clarity nor the greatest accuracy is possible in a document of this complexity without feedback from readers. We therefore encourage readers to send us suspected errors, and to indicate points which are not clear to them. Although we do not intend to turn this document a pedagogic exposition, we shall willingly add short illuminating comments.

Second, the design of ML Modules – particularly the grammar – is still somewhat experimental, even though it is considerably refined from its original form. As a result of experimental use it may be changed or extended, and these changes or extensions will be defined in later versions of the present document.

Third, though the ML Core Language is more stable – simply because it has been subjected to more experiment – changes here may also occur. Wherever possible they will be "upwards compatible" – that is, the validity and semantics of existing programs will be preserved. One change is at present under discussion, and (for reasons of human resource) we are not delaying the issue of this document to include it. The proposed change is to the *exception* facility; it will not only add power but will also simplify the language – in particular, it will unite the notions of *handler* and *match*. This simplification is so significant that it deserves consideration even though it slightly violates the principle of upwards compatible change. But if it is adopted it will be possible to automate the necessary small modifications to existing programs.

Version 1 treats the ML Core Language and its Input/Output facilities as defined in **Standard ML** by Robert Harper, David MacQueen and Robin Milner (Report ECS-LFCS-86-2, Edinburgh University, Computer Science Department), but incorporating the changes defined in **Changes to the Standard ML Core Language** by Robin Milner (Report ECS-LFCS-87-33). As explained above, the Modules part of the language described here is considerably refined from that presented by MacQueen in ECS-LFCS-86-2.

Any future Version of this document will indicate precisely how it differs from its predecessor.

Edinburgh, 13 August 1987



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Syntax of the Core</b>	<b>3</b>
2.1	Reserved Words . . . . .	3
2.2	Special constants . . . . .	3
2.3	Comments . . . . .	4
2.4	Identifiers . . . . .	4
2.5	Lexical analysis . . . . .	5
2.6	Infix operators . . . . .	5
2.7	Derived Forms . . . . .	6
2.8	Grammar . . . . .	6
2.9	Syntactic Restrictions . . . . .	9
<b>3</b>	<b>Syntax of Modules</b>	<b>10</b>
3.1	Reserved Words . . . . .	10
3.2	Identifiers . . . . .	10
3.3	Infix operators . . . . .	10
3.4	Grammar for Modules . . . . .	10
3.5	Syntactic Restrictions . . . . .	12
3.6	Closure Restrictions . . . . .	14
<b>4</b>	<b>Static Semantics for the Core</b>	<b>16</b>
4.1	Simple Objects . . . . .	16
4.2	Compound Objects . . . . .	16
4.3	Projection, Injection and Modification . . . . .	18
4.4	Types and Type functions . . . . .	18
4.5	Type Schemes . . . . .	19
4.6	Scope of Explicit Type Variables . . . . .	19
4.7	Non-expansive Expressions . . . . .	20
4.8	Closure . . . . .	20
4.9	Type Environments and Well-formedness . . . . .	21
4.10	Inference Rules . . . . .	23
4.11	Further Restrictions . . . . .	30
4.12	Principal Environments . . . . .	30
<b>5</b>	<b>Static Semantics for Modules</b>	<b>31</b>
5.1	Semantic Objects . . . . .	31
5.2	Consistency . . . . .	32
5.3	Well-formedness . . . . .	32
5.4	Cycle-freedom . . . . .	32
5.5	Admissibility . . . . .	33
5.6	Type Realisation . . . . .	33

5.7	Realisation . . . . .	33
5.8	Signature Instantiation . . . . .	33
5.9	Functor Signature Instantiation . . . . .	33
5.10	Enrichment . . . . .	34
5.11	Signature Matching . . . . .	34
5.12	Principal Signatures . . . . .	35
5.13	Inference Rules . . . . .	36
5.14	Functor Signature Matching . . . . .	43
<b>6</b>	<b>Dynamic Semantics for the Core</b>	<b>44</b>
6.1	Reduced Syntax . . . . .	44
6.2	Simple Objects . . . . .	44
6.3	Compound Objects . . . . .	45
6.4	Basic Values . . . . .	46
6.5	Basic Exceptions . . . . .	46
6.6	Closures . . . . .	47
6.7	Inference Rules . . . . .	47
<b>7</b>	<b>Dynamic Semantics for Modules</b>	<b>55</b>
7.1	Reduced Syntax . . . . .	55
7.2	Compound Objects . . . . .	55
7.3	Inference Rules . . . . .	56
<b>8</b>	<b>Programs</b>	<b>61</b>
<b>A</b>	<b>Appendix: Derived Forms</b>	<b>63</b>
<b>B</b>	<b>Appendix: Full Grammar of the Core</b>	<b>66</b>
<b>C</b>	<b>Appendix: The Initial Static Basis</b>	<b>70</b>
<b>D</b>	<b>Appendix: The Initial Dynamic Basis</b>	<b>73</b>
<b>E</b>	<b>Appendix: The Development of ML</b>	<b>77</b>
	<b>References</b>	<b>83</b>
	<b>Index</b>	<b>86</b>



# 1 Introduction

This document provides a complete formal description of Standard ML.

To understand the method of description, at least in broad terms, it helps to consider how an implementation of ML is naturally organised. ML is an interactive language, and a *program* consists of a sequence of *top-level declarations*; the execution of each declaration modifies the top-level environment, which we call a *basis*, and reports the modification to the user.

In the execution of a declaration there are three phases: *parsing*, *elaboration*, and *evaluation*. Parsing determines the grammatical form of a declaration. Elaboration, the *static* phase, determines whether it is well-typed and well-formed in other ways, and records relevant type or form information in the basis. Finally evaluation, the *dynamic* phase, determines the value of the declaration and records relevant value information in the basis. Corresponding to these phases, our formal description divides into three parts: grammatical rules, elaboration rules, and evaluation rules. Furthermore, the basis is divided into the *static* basis and the *dynamic* basis; for example, a variable which has been declared is associated with a type in the static basis and with a value in the dynamic basis.

In an implementation, the basis need not be so divided. But for the purpose of formal description, it eases presentation and understanding to keep the static and dynamic parts of the basis separate. This is further justified by programming experience. A large proportion of errors in ML programs are discovered during elaboration, and identified as errors of type or form, so it follows that it is useful to perform the elaboration phase separately. In fact, elaboration without evaluation is just what is normally called *compilation*; once a declaration (or larger entity) is compiled one wishes to evaluate it – repeatedly – without re-elaboration, from which it follows that it is useful to perform the evaluation phase separately.

A further factoring of the formal description is possible, because of the structure of the language. ML consists of a lower level, called the *Core language* (or *Core*, for short) a middle level concerned with programming-in-the-large, called *Modules* and a very small upper level called *Programs*. With the three phases described above, there is therefore a possibility of nine components in the complete language definition. We have allotted one section to each of these components, except that we have combined the parsing, elaboration and evaluation of *Programs* in one section. The scheme for the ensuing seven sections is therefore as follows:

	<i>Core</i>	<i>Modules</i>	<i>Programs</i>
<i>Syntax</i>	Section 2	Section 3	Section 8
<i>Static Semantics</i>	Section 4	Section 5	
<i>Dynamic Semantics</i>	Section 6	Section 7	

The *Core* provides many phrase classes, for programming convenience. But about half of these classes are derived forms, whose meaning can be given by translation into the other half which we call the *Bare* language. Thus each of

the three parts for the Core treats only the bare language; the derived forms are treated in Appendix A. This appendix also contains a few derived forms for Modules. A full grammar for the Core including derived forms is presented in Appendix B.

In Appendices C and D the *initial basis* is detailed. This basis, divided into its static and dynamic parts, contains the static and dynamic meanings of all predefined identifiers.

The semantics is presented in a form known as Natural Semantics. It consists of a set of rules allowing *sentences* of the form

$$A \vdash \textit{phrase} \Rightarrow A'$$

to be inferred, where  $A$  is often a basis (static or dynamic) and  $A'$  a semantic object – often a type in the static semantics and a value in the dynamic semantics. One should read such a sentence as follows: “in the basis  $A$ , the phrase *phrase* elaborates – or evaluates – to the object  $A'$ ”. Although the rules themselves are formal the semantic objects, particularly the static ones, are the subject of a mathematical theory which is presented in a succinct form in the relevant sections. This theory, particularly the theory of types and signatures, will benefit from a more pedagogic treatment in other publications; the treatment here is probably the minimum required to understand the meaning of the rules.

The robustness of the semantics depends upon theorems. Some of these are stated but not proved; others are presented as “claims” rather than theorems – often they have been proved for a skeletal language, and although we are confident of their truth their proofs in the context of the full language will present an interesting challenge to a computer-assisted proof methodology, to attain complete certainty.

## 2 Syntax of the Core

### 2.1 Reserved Words

The following are the reserved words used in the Core. They may not (except =) be used as identifiers. In this document the alphabetic reserved words are always shown in typewriter font.

```

abstype  and  andalso  as  case  do  datatype  else
end      exception  fn  fun  handle  if  in  infix
infixr  let      local  nonfix  of  op  open  orelse
raise   rec  then  type  val  with  withtype  while
( )    [ ]  { }  ,  :  ;  ...  _  |  =  =>  ->  #

```

### 2.2 Special constants

An integer constant is any non-empty sequence of digits, possibly preceded by a negation symbol (~).

A real constant is an integer constant, possibly followed by a point (.) and one or more digits, possibly followed by an exponent symbol E and an integer constant; at least one of the optional parts must occur, hence no integer constant is a real constant. Examples: 0.7 +3.32E5 3E~7 . Non-examples: 23 .3 4.E5 1E2.0 .

A string constant is a sequence, between quotes ("), of zero or more printable characters, spaces or escape sequences. Each escape sequence is introduced by the escape character \, and stands for a character sequence. The allowed escape sequences are as follows (all other uses of \ being incorrect):

<code>\n</code>	A single character interpreted by the system as end-of-line.
<code>\t</code>	Tab.
<code>\^c</code>	The control character <i>c</i> , for any appropriate <i>c</i> .
<code>\ddd</code>	The single character with ASCII code <i>ddd</i> (3 decimal digits).
<code>\"</code>	"
<code>\\</code>	\
<code>\f···f\</code>	This sequence is ignored, where <i>f···f</i> stands for a sequence of one or more formatting characters.

The *formatting characters* are a subset of the non-printable characters including at least space, tab, newline, formfeed. The last form allows long strings to be written on more than one line, by writing \ at the end of one line and at the start of the next.

Var	(value variables )	long
Con	(value constructors )	long
ExCon	(exception constructors)	long
TyVar	(type variables )	
TyCon	(type constructors )	long
Lab	(record labels )	
StrId	(structure identifiers )	long

Figure 1: Identifiers

### 2.3 Comments

A comment is any character sequence within comment brackets (`* *`) in which comment brackets are properly nested. An unmatched comment bracket should be detected by the compiler.

### 2.4 Identifiers

The classes of identifiers for the Core are shown in Figure 1. We use *var*, *tyvar* to range over Var, TyVar etc. For each class X marked “long” there is also a class

$$\text{LongX} = \text{StrId}^* \times X$$

If  $x$  ranges over X, then *longx*, or *strid<sub>1</sub>...strid<sub>k</sub>.x*,  $k \geq 0$ , ranges over LongX. These long identifiers constitute the only link between the Core and the language constructs for Modules; by omitting them, and the open declaration, we obtain the Core as a complete programming language in its own right. (The corresponding adjustment to the Core static and dynamic semantics is simply to omit structure environments *SE*.)

An identifier is either *alphanumeric*: any sequence of letters, digits, primes (') and underbars (-) starting with a letter or prime, or *symbolic*: any sequence of the following *symbols*

! % & \$ # + - / : < = > ? @ \ ~ ' ^ | \*

In either case, however, reserved words are excluded. This means that for example # and | are not identifiers, but ## and |=| are identifiers. The only exception to this rule is that the symbol =, which is a reserved word, is also allowed as an identifier to stand for the equality predicate. The identifier = may not be re-bound; this precludes any syntactic ambiguity.

A type variable *tyvar* may be any alphanumeric identifier starting with a prime; the subclass *EtyVar* of TyVar, the *equality* type variables, consists of those which start with two or more primes. The subclass *ImpTyVar* of TyVar, the *imperative* type variables, consists of those which start with one or two primes followed by

an underbar. The complement  $\text{AppTyVar} = \text{TyVar} \setminus \text{ImpTyVar}$  consists of the *applicative* type variables. The other six classes (Var, Con, ExCon, TyCon, Lab and StrId) are represented by identifiers not starting with a prime; the class Lab is also extended to include the *numeric* labels 1 2 3 ...

TyVar is therefore disjoint from the other six classes. Otherwise, the syntax class of an occurrence of identifier *id* in a Core phrase (ignoring derived forms, Section 2.7) is determined thus:

1. Immediately before “.” – i.e. in a long identifier – or in an open declaration, *id* is a structure identifier. The following rules assume that all occurrences of structure identifiers have been removed.
2. At the start of a component in a record type, record pattern or record expression, *id* is a record label.
3. Elsewhere in types *id* is a type constructor, and must be within the scope of the type binding or datatype binding which introduced it.
4. Elsewhere, *id* is an exception constructor if it occurs in the scope of an exception binding which introduces it as such, or a value constructor if it occurs in the scope of a datatype binding which introduced it as such; otherwise it is a value variable.

It follows from the last rule that no value declaration can make a “hole” in the scope of a value or exception constructor by introducing the same identifier as a variable; this is because, in the scope of the declaration which introduces *id* as a value or exception constructor, any occurrence of *id* in a pattern is interpreted as the constructor and not as the binding occurrence of a new variable.

By means of the above rules a parser can determine the class to which each identifier class belongs; for the remainder of this document we shall therefore assume that the classes are all disjoint.

## 2.5 Lexical analysis

Each item of lexical analysis is either a reserved word, a numeric label, a special constant or an identifier. Comments and formatting characters separate items (except within string constants; see Section 2.2) and are otherwise ignored. At each stage the longest next item is taken.

## 2.6 Infix operators

An identifier may be given *infix status* by the `infix` or `infixr` directive, which may occur as a declaration; this status only pertains to its use as a *var*, a *con* or an *excon* within the scope (see below) of the directive. If *id* has infix status, then “*exp*<sub>1</sub> *id* *exp*<sub>2</sub>” (resp. “*pat*<sub>1</sub> *id* *pat*<sub>2</sub>”) may occur – in parentheses



if necessary – wherever the application “ $id\{1=exp_1, 2=exp_2\}$ ” or its derived form “ $id(exp_1, exp_2)$ ” (resp “ $id(pat_1, pat_2)$ ”) would otherwise occur. On the other hand, non-infix occurrences of *id* must be prefixed by the keyword `op`. Infix status is cancelled by the `nonfix` directive. We refer to the three directives collectively as *fixity directives*.

The form of the fixity directives is as follows ( $n \geq 1$ ):

$$\text{infix } \langle d \rangle id_1 \cdots id_n$$

$$\text{infixr } \langle d \rangle id_1 \cdots id_n$$

$$\text{nonfix } id_1 \cdots id_n$$

where  $\langle d \rangle$  is an optional decimal digit  $d$  indicating binding precedence. A higher value of  $d$  indicates tighter binding; the default is 0. `infix` and `infixr` dictate left and right associativity respectively; association is always to the left for different operators of the same precedence. The precedence of infix operators relative to other expression and pattern constructions is given in Appendix B.

The *scope* of a fixity directive *dir* is the ensuing program text, except that if *dir* occurs in a declaration *dec* in either of the phrases

$$\text{let } dec \text{ in } \cdots \text{end}$$

$$\text{local } dec \text{ in } \cdots \text{end}$$

then the scope of *dir* does not extend beyond the phrase. Further scope limitations are imposed for Modules.

These directives and `op` are omitted from the semantic rules, since they effect only parsing.

## 2.7 Derived Forms

There are many standard syntactic forms in ML whose meaning can be expressed in terms of a smaller number of syntactic forms, called the *bare language*. These derived forms, and their equivalent forms in the bare language, are given in Appendix A.

## 2.8 Grammar

The phrase classes for the Core are shown in Figure 2. We use the variable *atexp* to range over `AtExp`, etc.

The grammatical rules for the Core are shown in Figures 3 and 4.

AtExp	atomic expressions
ExpRow	expression rows
Exp	expressions
Match	matches
Mrule	match rules
Dec	declarations
ValBind	value bindings
TypBind	type bindings
DatBind	datatype bindings
ConBind	constructor bindings
ExBind	exception bindings
AtPat	atomic patterns
PatRow	pattern rows
Pat	patterns
Ty	type expressions
TyRow	type-expression rows

Figure 2: Core Phrase Classes

The following conventions are adopted in presenting the grammatical rules, and in their interpretation:

- The brackets  $\langle \rangle$  enclose optional phrases.
- For any syntax class  $X$  (over which  $x$  ranges) we define the syntax class  $Xseq$  (over which  $xseq$  ranges) as follows:

$$\begin{array}{ll}
 xseq ::= x & \text{(singleton sequence)} \\
 & \text{(empty sequence)} \\
 (x_1, \dots, x_n) & \text{(sequence, } n \geq 1)
 \end{array}$$

(Note that the “...” used here, meaning syntactic iteration, must not be confused with “...” which is a reserved word of the language.)

- Alternative forms for each phrase class are in order of decreasing precedence.
- L (resp. R) means left (resp. right) association.
- The syntax of types binds more tightly than that of expressions.
- Each iterated construct (e.g. *match*, ...) extends as far right as possible; thus, parentheses may be needed around an expression which terminates with a match, e.g. “fn *match*”, if this occurs within a larger match.

<i>atexp</i>	::=	<i>&lt;op&gt;longvar</i> <i>&lt;op&gt;longcon</i> <i>&lt;op&gt;longexcon</i> <i>{ &lt;exprow &gt; }</i> <i>let dec in exp end</i> <i>( exp )</i>	value variable value constructor exception constructor record local declaration
<i>exprow</i>	::=	<i>lab = exp &lt; , exprow &gt;</i>	expression row
<i>exp</i>	::=	<i>atexp</i> <i>exp atexp</i> <i>exp<sub>1</sub> id exp<sub>2</sub></i> <i>exp : ty</i> <i>exp handle match</i> <i>raise exp</i> <i>fn match</i>	atomic application (L) infix application typed (L) handle exception raise exception function
<i>match</i>	::=	<i>mrule &lt;   match &gt;</i>	
<i>mrule</i>	::=	<i>pat =&gt; exp</i>	
<i>dec</i>	::=	<i>val valbind</i> <i>type tybind</i> <i>datatype datbind</i> <i>abstype datbind with dec end</i> <i>exception exbind</i> <i>local dec<sub>1</sub> in dec<sub>2</sub> end</i> <i>open longstrid<sub>1</sub> ... longstrid<sub>n</sub></i>  <i>dec<sub>1</sub> &lt;;&gt; dec<sub>2</sub></i> <i>infix &lt;d&gt; id<sub>1</sub> ... id<sub>n</sub></i> <i>infixr &lt;d&gt; id<sub>1</sub> ... id<sub>n</sub></i> <i>nonfix id<sub>1</sub> ... id<sub>n</sub></i>	value declaration type declaration datatype declaration abstype declaration exception declaration local declaration open declaration ( $n \geq 1$ ) empty declaration sequential declaration infix (L) directive infix (R) directive nonfix directive
<i>valbind</i>	::=	<i>pat = exp &lt;and valbind &gt;</i> <i>rec valbind</i>	
<i>tybind</i>	::=	<i>tyvarseq tycon = ty &lt;and tybind &gt;</i>	
<i>datbind</i>	::=	<i>tyvarseq tycon = conbind &lt;and datbind &gt;</i>	
<i>conbind</i>	::=	<i>&lt;op&gt;con &lt;of ty &gt; &lt;   conbind &gt;</i>	
<i>exbind</i>	::=	<i>excon &lt;of ty &gt; &lt;and exbind &gt;</i> <i>excon = longexcon &lt;and exbind &gt;</i>	

Figure 3: Grammar: Expressions, Matches, Declarations and Bindings

<i>atpat</i>	$::=$	-	wildcard
		$\langle \text{op} \rangle \text{var}$	variable
		<i>longcon</i>	constant
		<i>longexcon</i>	exception constant
		{ $\langle \text{patrow} \rangle$ }	record
		( <i>pat</i> )	
<i>patrow</i>	$::=$	...	wildcard
		<i>lab</i> = <i>pat</i> ( , <i>patrow</i> )	pattern row
<i>pat</i>		<i>atpat</i>	atomic
		$\langle \text{op} \rangle \text{longcon } \text{atpat}$	value construction
		$\langle \text{op} \rangle \text{longexcon } \text{atpat}$	exception construction
		<i>pat</i> <sub>1</sub> <i>con</i> <i>pat</i> <sub>2</sub>	infix value construction
		<i>pat</i> <sub>1</sub> <i>excon</i> <i>pat</i> <sub>2</sub>	infix exception construction
		<i>pat</i> : <i>ty</i>	typed
		$\langle \text{op} \rangle \text{var} \langle : \text{ty} \rangle \text{ as } \text{pat}$	layered
<i>ty</i>	$::=$	<i>tyvar</i>	type variable
		{ $\langle \text{tyrow} \rangle$ }	record type expression
		<i>tyseq longtycon</i>	type construction
		<i>ty</i> -> <i>ty'</i>	function type expression (R)
		( <i>ty</i> )	
<i>tyrow</i>	$::=$	<i>lab</i> : <i>ty</i> ( , <i>tyrow</i> )	type-expression row

Figure 4: Grammar: Patterns and Type expressions

## 2.9 Syntactic Restrictions

- No pattern may contain the same *var* twice. No expression row, pattern row or type row may bind the same *lab* twice.
- No binding *valbind*, *typbind*, *datbind* or *exbind* may bind the same identifier twice; this applies also to value constructors within a *datbind*.
- In the left side *tyvarseq tycon* of any *typbind* or *datbind*, *tyvarseq* must not contain the same *tyvar* twice. Any *tyvar* occurring within the right side must occur in *tyvarseq*.
- For each value binding *pat* = *exp* within *rec*, *exp* must be of the form *fn match*. The derived form of function-value binding given in Appendix A, page 65, necessarily obeys this restriction.

### 3 Syntax of Modules

For Modules there are further keywords, identifier classes and derived forms. There are no further special constants; comments and lexical analysis are as for the Core. The derived forms for modules concern functors and appear in Appendix A.

#### 3.1 Reserved Words

The following are the additional reserved words used in Modules.

```

    eqtype  functor  include  sharing
    sig     signature struct  structure
  
```

#### 3.2 Identifiers

The additional syntax classes for Modules are SigId (signature identifiers) and FunId (functor identifiers); they may be either alphanumeric – not starting with a prime – or symbolic. The class of each identifier occurrence is determined by the grammatical rules which follow. Henceforth, therefore, we consider all identifier classes to be disjoint.

#### 3.3 Infix operators

In addition to the scope rules for fixity directives given for the Core syntax, there is a further scope limitation: if *dir* occurs in a structure-level declaration *strdec* in any of the phrases

```

    let strdec in ... end
    local strdec in ... end
    struct strdec end
  
```

then the scope of *dir* does not extend beyond the phrase.

One effect of this limitation is that fixity is local to a generative structure expression – in particular, to such an expression occurring as a functor body. A more liberal scheme (which is under consideration) would allow fixity directives to appear also as specifications, so that fixity may be dictated by a signature expression; furthermore, it would allow an *open* or *include* construction to restore the fixity which prevailed in the structures being opened, or in the signatures being included. This scheme is not adopted at present.

#### 3.4 Grammar for Modules

The phrase classes for Modules are shown in Figure 5. We use the variable *strexp* to range over StrExp, etc. The conventions adopted in presenting the grammatical rules for Modules are the same as for the Core. The grammatical rules are shown

StrExp	structure expressions
StrDec	structure-level declarations
StrBind	structure bindings
SigExp	signature expressions
SigDec	signature declarations
SigBind	signature bindings
Spec	specifications
ValDesc	value descriptions
TypDesc	type descriptions
DatDesc	datatype descriptions
ExDesc	exception descriptions
StrDesc	structure descriptions
SharEq	sharing equations
FunDec	functor declarations
FunBind	functor bindings
FunSigExp	functor signature expressions
FunSpec	functor specifications
FunDesc	functor descriptions
TopDec	top-level declarations

Figure 5: Modules Phrase Classes

in Figures 6, 7 and 8.

It should be noted that functor specifications (FunSpec) cannot occur in top-level declarations; neither can the associated functor descriptions (FunDesc) and functor signature expressions (FunSigExp). The purpose of a *funspec* is to specify the static attributes (i.e. functor signature) of one or more functors. This will be useful, in fact essential, for separate compilation of functors. If, for example, a functor  $g$  refers to another functor  $f$  then — in order to compile  $g$  in the absence of the declaration of  $f$  — at least the specification of  $f$  (i.e. its functor signature) must be available. At present there is no special grammatical form for a separately compilable “chunk” of text — which we may like to call a *module* — containing a *fundec* together with a *funspec* specifying its global references. However, below in the semantics for Modules it is defined when a declared functor matches a functor signature specified for it. This determines exactly those functor environments (containing declared functors such as  $f$ ) into which the separately compiled “chunk” containing the declaration of  $g$  may be loaded.

<i>strexp</i>	::=	<b>struct</b> <i>strdec</i> <b>end</b> <i>longstrid</i> <i>funid</i> ( <i>strexp</i> ) <b>let</b> <i>strdec</i> <b>in</b> <i>strexp</i> <b>end</b>	generative structure identifier functor application local declaration
<i>strdec</i>	::=	<i>dec</i> <b>structure</b> <i>strbind</i> <b>local</b> <i>strdec</i> <sub>1</sub> <b>in</b> <i>strdec</i> <sub>2</sub> <b>end</b>  <i>strdec</i> <sub>1</sub> {;} <i>strdec</i> <sub>2</sub>	declaration structure local empty sequential
<i>strbind</i>	::=	<i>strid</i> {: <i>sigexp</i> } = <i>strexp</i> { <b>and</b> <i>strbind</i> }	
<i>sigexp</i>	::=	<b>sig</b> <i>spec</i> <b>end</b> <i>sigid</i>	generative signature identifier
<i>sigdec</i>	::=	<b>signature</b> <i>sigbind</i>  <i>sigdec</i> <sub>1</sub> {;} <i>sigdec</i> <sub>2</sub>	single empty sequential
<i>sigbind</i>	::=	<i>sigid</i> = <i>sigexp</i> { <b>and</b> <i>sigbind</i> }	

Figure 6: Grammar: Structure and Signature Expressions

### 3.5 Syntactic Restrictions

- No binding *strbind*, *sigbind*, or *funbind* may bind the same identifier twice.
- No description *valdesc*, *typdesc*, *datdesc*, *exdesc*, *strdesc* or *fundesc* may describe the same identifier twice.

<i>spec</i>	::= val <i>valdesc</i> type <i>typdesc</i> eqtype <i>typdesc</i> datatype <i>datdesc</i> exception <i>exdesc</i> structure <i>strdesc</i> sharing <i>shareq</i> local <i>spec</i> <sub>1</sub> in <i>spec</i> <sub>2</sub> end open <i>longstrid</i> <sub>1</sub> ... <i>longstrid</i> <sub><i>n</i></sub> include <i>sigid</i> <sub>1</sub> ... <i>sigid</i> <sub><i>n</i></sub>  <i>spec</i> <sub>1</sub> {;} <i>spec</i> <sub>2</sub>	value type eqtype datatype exception structure sharing local open ( <i>n</i> ≥ 1) include ( <i>n</i> ≥ 1) empty sequential
<i>valdesc</i>	::= var : <i>ty</i> {and <i>valdesc</i> }	
<i>typdesc</i>	::= <i>tyvarseq tycon</i> {and <i>typdesc</i> }	
<i>datdesc</i>	::= <i>tyvarseq tycon = conbind</i> {and <i>datdesc</i> }	
<i>exdesc</i>	::= <i>excon</i> {of <i>ty</i> } {and <i>exdesc</i> }	
<i>strdesc</i>	::= <i>strid</i> : <i>sigexp</i> {and <i>strdesc</i> }	
<i>shareq</i>	::= <i>longstrid</i> <sub>1</sub> = ... = <i>longstrid</i> <sub><i>n</i></sub>  type <i>longtycon</i> <sub>1</sub> = ... = <i>longtycon</i> <sub><i>n</i></sub>  <i>shareq</i> <sub>1</sub> and <i>shareq</i> <sub>2</sub>	structure sharing ( <i>n</i> ≥ 2) type sharing ( <i>n</i> ≥ 2) multiple

Figure 7: Grammar: Specifications



$fundec$	$::=$	$functor\ funbind$	single
		$fundec_1 \langle ; \rangle fundec_2$	empty sequence
$funbind$	$::=$	$funid ( strid : sigexp ) \langle : sigexp' \rangle = strexp$ $\langle and\ funbind \rangle$	functor binding
$funsigexp$	$::=$	$( strid : sigexp ) : sigexp'$	functor signature expression
$funspec$	$::=$	$functor\ fundesc$	functor specification
		$funspec_1 \langle ; \rangle funspec_2$	empty sequence
$fundesc$	$::=$	$funid\ funsigexp \langle and\ fundesc \rangle$	
$topdec$	$::=$	$strdec$	structure-level declaration
		$sigdec$	signature declaration
		$fundec$	functor declaration

Note: No *topdec* may contain, as an initial segment, a shorter top-level declaration followed by a semicolon.

Figure 8: Grammar: Functors and Top-level Declarations

### 3.6 Closure Restrictions

The semantics presented in later sections requires no restriction on reference to non-local identifiers. For example, it allows a signature expression to refer to external signature identifiers and (via `sharing` or `open`) to external structure identifiers; it also allows a functor to refer to external identifiers of any kind.

However, implementors who want to provide a simple facility for separate compilation may want to impose the following restrictions (ignoring references to identifiers bound in the initial basis  $B_0$ , which may occur anywhere):

1. In any signature binding  $sigid = sigexp$ , the only non-local references in  $sigexp$  are to signature identifiers.
2. In any functor description  $funid ( strid : sigexp ) : sigexp'$ , the only non-local references in  $sigexp$  and  $sigexp'$  are to signature identifiers, except that  $sigexp'$  may refer to  $strid$  and its components.
3. In any functor binding  $funid ( strid : sigexp ) \langle : sigexp' \rangle = strexp$ , the only non-local references in  $sigexp$ ,  $sigexp'$  and  $strex$  are to functor and signature identifiers, except that both  $sigexp'$  and  $strex$  may refer to  $strid$  and its components.

In the last two cases the final qualification allows, for example, sharing constraints to be specified between functor argument and result. (For a completely precise

definition of these closure restrictions, see the comments to rules 63 (page 38), 87 (page 41) and 92 (page 42) in the static semantics of modules, Section 5.)

The significance of these restrictions is that they may ease separate compilation; this may be seen as follows. If one takes a *module* to be a sequence of signature declarations, functor specifications and functor declarations satisfying the above restrictions then the elaboration of a module can be made to depend on the initial static basis alone (in particular, it will not rely on structures outside the module). Moreover, the elaboration of a module cannot create new free structure or type names, so name consistency (as defined in Section 5.2, page 32) is automatically preserved across separately compiled modules. On the other hand, imposing these restrictions may force the programmer to write many more sharing equations than is needed if functors and signature expressions can refer to free structures.

## 4 Static Semantics for the Core

Our first task in presenting the semantics – whether for Core or Modules, static or dynamic – is to define the objects concerned. In addition to the class of *syntactic* objects, which we have already defined, there are classes of so-called *semantic* objects used to describe the meaning of the syntactic objects. Some classes contain *simple* semantic objects; such objects are usually identifiers or names of some kind. Other classes contain *compound* semantic objects, such as types or environments, which are constructed from component objects.

### 4.1 Simple Objects

All semantic objects in the static semantics of the entire language are built from identifiers and two further kinds of simple objects: type constructor names and structure names. Type constructor names are the values taken by type constructors; we shall usually refer to them briefly as type names, but they are to be clearly distinguished from type variables and type constructors. Structure names play an active role only in the Modules semantics; they enter the Core semantics only because they appear in structure environments, which (in turn) are needed in the Core semantics only to determine the values of long identifiers. The simple object classes, and the variables ranging over them, are shown in Figure 9. We have included TyVar in the table to make visible the use of  $\alpha$  in the semantics to range over TyVar.

$\alpha$ or <i>tyvar</i>	$\in$ TyVar	type variables
	$t \in$ TyName	type names
	$m \in$ StrName	structure names

Figure 9: Simple Semantic Objects

Each  $\alpha \in$  TyVar possesses a boolean *equality* attribute, which determines whether or not it *admits equality*, i.e. whether it is a member of EtyVar (defined on page 4). Independently hereof, each  $\alpha$  possesses a boolean attribute, the *imperative* attribute, which determines whether it is imperative, i.e. whether it is a member of ImpTyVar (defined on page 4) or not.

Each  $t \in$  TyName has an arity  $k \geq 0$ , and also possesses an equality attribute. We denote the class of type names with arity  $k$  by  $\text{TyName}^{(k)}$ .

### 4.2 Compound Objects

When  $A$  and  $B$  are sets  $\text{Fin } A$  denotes the set of finite subsets of  $A$ , and  $A \xrightarrow{\text{fin}} B$  denotes the set of *finite maps* (partial functions with finite domain) from  $A$  to  $B$ .

The domain and range of a finite map,  $f$ , are denoted  $\text{Dom } f$  and  $\text{Ran } f$ . A finite map will often be written explicitly in the form  $\{a_1 \mapsto b_1, \dots, a_k \mapsto b_k\}$ ,  $k \geq 0$ ; in particular the empty map is  $\{\}$ . We shall use the form  $\{x \mapsto e ; \phi\}$  – a form of set comprehension – to stand for the finite map  $f$  whose domain is the set of values  $x$  which satisfy the condition  $\phi$ , and whose value on this domain is given by  $f(x) = e$ .

When  $f$  and  $g$  are finite maps the map  $f + g$ , called  $f$  modified by  $g$ , is the finite map with domain  $\text{Dom } f \cup \text{Dom } g$  and values

$$(f + g)(a) = \text{if } a \in \text{Dom } g \text{ then } g(a) \text{ else } f(a).$$

The compound objects for the static semantics of the Core Language are shown in Figure 10.

$$\begin{array}{l}
\tau \in \text{Type} = \text{TyVar} \cup \text{RecType} \cup \text{FunType} \cup \text{ConsType} \\
(\tau_1, \dots, \tau_k) \text{ or } \tau^{(k)} \in \text{Type}^k \\
(\alpha_1, \dots, \alpha_k) \text{ or } \alpha^{(k)} \in \text{TyVar}^k \\
\rho \in \text{RecType} = \text{Lab} \xrightarrow{\text{fin}} \text{Type} \\
\tau \rightarrow \tau' \in \text{FunType} = \text{Type} \times \text{Type} \\
\text{ConsType} = \bigcup_{k \geq 0} \text{ConsType}^{(k)} \\
\tau^{(k)} t \in \text{ConsType}^{(k)} = \text{Type}^k \times \text{TyName}^{(k)} \\
\theta \text{ or } \Lambda \alpha^{(k)}. \tau \in \text{TypeFcn} = \bigcup_{k \geq 0} \text{TyVar}^k \times \text{Type} \\
\sigma \text{ or } \forall \alpha^{(k)}. \tau \in \text{TypeScheme} = \bigcup_{k \geq 0} \text{TyVar}^k \times \text{Type} \\
S \text{ or } (m, E) \in \text{Str} = \text{StrName} \times \text{Env} \\
(\theta, CE) \in \text{TyStr} = \text{TypeFcn} \times \text{ConEnv} \\
SE \in \text{StrEnv} = \text{StrId} \xrightarrow{\text{fin}} \text{Str} \\
TE \in \text{TyEnv} = \text{TyCon} \xrightarrow{\text{fin}} \text{TyStr} \\
CE \in \text{ConEnv} = \text{Con} \xrightarrow{\text{fin}} \text{TypeScheme} \\
VE \in \text{VarEnv} = (\text{Var} \cup \text{Con} \cup \text{ExCon}) \xrightarrow{\text{fin}} \text{TypeScheme} \\
EE \in \text{ExConEnv} = \text{ExCon} \xrightarrow{\text{fin}} \text{Type} \\
E \text{ or } (SE, TE, VE, EE) \in \text{Env} = \text{StrEnv} \times \text{TyEnv} \times \text{VarEnv} \times \text{ExConEnv} \\
T \in \text{TyNameSet} = \text{Fin}(\text{TyName}) \\
U \in \text{TyVarSet} = \text{Fin}(\text{TyVar}) \\
C \text{ or } T, U, E \in \text{Context} = \text{TyNameSet} \times \text{TyVarSet} \times \text{Env}
\end{array}$$

Figure 10: Compound Semantic Objects

Note that  $\Lambda$  and  $\forall$  bind type variables. For any semantic object  $A$ ,  $\text{tynames } A$  and  $\text{tyvars } A$  denote respectively the set of type names and the set of type variables occurring free in  $A$ . Moreover,  $\text{imptyvars } A$  and  $\text{apptyvars } A$  denote respectively the set of imperative type variables and the set of applicative type variables occurring free in  $A$ .

### 4.3 Projection, Injection and Modification

**Projection:** We often need to select components of tuples – for example, the variable-environment component of a context. In such cases we rely on variable names to indicate which component is selected. For instance “ $VE$  of  $E$ ” means “the variable-environment component of  $E$ ” and “ $m$  of  $S$ ” means “the structure name of  $S$ ”.

Moreover, when a tuple contains a finite map we shall “apply” the tuple to an argument, relying on the syntactic class of the argument to determine the relevant function. For instance  $C(\text{tycon})$  means  $(TE \text{ of } C)\text{tycon}$ .

A particular case needs mention:  $C(\text{con})$  is taken to stand for  $(VE \text{ of } C)\text{con}$ ; similarly,  $C(\text{excon})$  is taken to stand for  $(VE \text{ of } C)\text{excon}$ . The type scheme of a value constructor is held in  $VE$  as well as in  $TE$  (where it will be recorded within a  $CE$ ); similarly, the type of an exception constructor is held in  $VE$  as well as in  $EE$ . Thus the re-binding of a constructor of either kind is given proper effect by accessing it in  $VE$ , rather than in  $TE$  or in  $EE$ .

Finally, environments may be applied to long identifiers. For instance if  $\text{longcon} = \text{strid}_1 \dots \text{strid}_k.\text{con}$  then  $E(\text{longcon})$  means

$$(VE \text{ of } (SE \text{ of } \dots (SE \text{ of } (SE \text{ of } E)\text{strid}_1)\text{strid}_2 \dots)\text{strid}_k)\text{con}.$$

**Injection:** Components may be injected into tuple classes; for example, “ $VE$  in Env” means the environment  $(\{\}, \{\}, VE, \{\})$ .

**Modification:** The modification of one map  $f$  by another map  $g$ , written  $f+g$ , has already been mentioned. It is commonly used for environment modification, for example  $E + E'$ . Often, empty components will be left implicit in a modification; for example  $E + VE$  means  $E + (\{\}, \{\}, VE, \{\})$ . For set components, modification means union, so that  $C + (T, VE)$  means

$$((T \text{ of } C) \cup T, (E \text{ of } C) + VE)$$

Finally, we frequently need to modify a context  $C$  by an environment  $E$  (or a type environment  $TE$  say), at the same time extending  $T$  of  $C$  to include the type names of  $E$  (or of  $TE$  say). We therefore define  $C \oplus TE$ , for example, to mean  $C + (\text{tynames } TE, TE)$ .

### 4.4 Types and Type functions

A type  $\tau$  is an *equality type*, or *admits equality*, if it is of one of the forms

- $\alpha$ , where  $\alpha$  admits equality;
- $\{\text{lab}_1 \mapsto \tau_1, \dots, \text{lab}_n \mapsto \tau_n\}$ , where each  $\tau_i$  admits equality;
- $\tau^{(k)}t$ , where  $t$  and all members of  $\tau^{(k)}$  admit equality;

- $(\tau')$ ref.

A type function  $\theta = \Lambda\alpha^{(k)}. \tau$  has arity  $k$ ; it must be *closed* – i.e.  $\text{tyvars}(\tau) \subseteq \alpha^{(k)}$  – and the bound variables must be distinct. Two type functions are considered equal if they only differ in their choice of bound variables (alpha-conversion). In particular, the equality attribute has no significance in a bound variable of a type function; for example,  $\Lambda\alpha. \alpha \rightarrow \alpha$  and  $\Lambda\beta. \beta \rightarrow \beta$  are equal type functions even if  $\alpha$  admits equality but  $\beta$  does not. Similarly, the imperative attribute has no significance in the bound variable of a type function. If  $t$  has arity  $k$ , then we write  $t$  to mean  $\Lambda\alpha^{(k)}. \alpha^{(k)}t$  (eta-conversion); thus  $\text{TyName} \subseteq \text{TypeFcn}$ .  $\theta = \Lambda\alpha^{(k)}. \tau$  is an *equality* type function, or *admits equality*, if when the type variables  $\alpha^{(k)}$  are chosen to admit equality then  $\tau$  also admits equality.

We write the application of a type function  $\theta$  to a vector  $\tau^{(k)}$  of types as  $\tau^{(k)}\theta$ . If  $\theta = \Lambda\alpha^{(k)}. \tau$  we set  $\tau^{(k)}\theta = \tau\{\tau^{(k)}/\alpha^{(k)}\}$  (beta-conversion).

We write  $\tau\{\theta^{(k)}/t^{(k)}\}$  for the result of substituting type functions  $\theta^{(k)}$  for type names  $t^{(k)}$  in  $\tau$ . We assume that all beta-conversions are carried out after substitution, so that for example

$$(\tau^{(k)}t)\{\Lambda\alpha^{(k)}. \tau/t\} = \tau\{\tau^{(k)}/\alpha^{(k)}\}.$$

A type is *imperative* if all type variables occurring in it are imperative.

## 4.5 Type Schemes

A type scheme  $\sigma = \forall\alpha^{(k)}. \tau$  *generalises* a type  $\tau'$ , written  $\sigma \succ \tau'$ , if  $\tau' = \tau\{\tau^{(k)}/\alpha^{(k)}\}$  for some  $\tau^{(k)}$ , where each member  $\tau_i$  of  $\tau^{(k)}$  admits equality if  $\alpha_i$  does, and  $\tau_i$  is imperative if  $\alpha_i$  is imperative. If  $\sigma' = \forall\beta^{(l)}. \tau'$  then  $\sigma$  *generalises*  $\sigma'$ , written  $\sigma \succ \sigma'$ , if  $\sigma \succ \tau'$  and  $\beta^{(l)}$  contains no free type variable of  $\sigma$ . It can be shown that  $\sigma \succ \sigma'$  iff, for all  $\tau''$ , whenever  $\sigma' \succ \tau''$  then also  $\sigma \succ \tau''$ .

Two type schemes  $\sigma$  and  $\sigma'$  are considered equal if they can be obtained from each other by renaming and reordering of bound type variables, and deleting type variables from the prefix which do not occur in the body. Here, in contrast to the case for type functions, the equality attribute must be respected in renaming; for example  $\forall\alpha. \alpha \rightarrow \alpha$  and  $\forall\beta. \beta \rightarrow \beta$  are only equal if either both  $\alpha$  and  $\beta$  admit equality, or neither does. Similarly, the imperative attribute of a bound type variable of a type scheme is significant. It can be shown that  $\sigma = \sigma'$  iff  $\sigma \succ \sigma'$  and  $\sigma' \succ \sigma$ .

We consider a type  $\tau$  to be a type scheme, identifying it with  $\forall(). \tau$ .

## 4.6 Scope of Explicit Type Variables

In the Core language, a type or datatype binding can explicitly introduce type variables whose scope is that binding. In the modules, a description of a value,

type, or datatype may contain explicit type variables whose scope is that description. However, we still have to account for the scope of an explicit type variable occurring in the “: *ty*” of a typed expression or pattern or in the “of *ty*” of an exception binding. For the rest of this section, we consider such occurrences of type variables only.

Every occurrence of a value declaration is said to *scope* a set of explicit type variables determined as follows.

First, an occurrence of  $\alpha$  in a value declaration `val valbind` is said to be *unguarded* if the occurrence is not part of a smaller value declaration within *valbind*. In this case we say that  $\alpha$  *occurs unguarded* in the value declaration.

Then we say that  $\alpha$  is *scoped* at a particular occurrence  $O$  of `val valbind` in a program if (1)  $\alpha$  occurs unguarded in this value declaration, and (2)  $\alpha$  does not occur unguarded in any larger value declaration containing the occurrence  $O$ .

Hence, associated with every occurrence of a value declaration there is a set  $U$  of the explicit type variables that are scoped at that occurrence. One may think of each occurrence of `val` as being implicitly decorated with such a set, for instance:

```
val $\{\}$  x = (let val $\{ 'a \}$  Id1: 'a -> 'a = fn z => z in Id1 Id1 end,
           let val $\{ 'a \}$  Id2: 'a -> 'a = fn z => z in Id2 Id2 end)
```

```
val $\{ 'a \}$  x = (let val $\{\}$  Id: 'a -> 'a = fn z => z in Id Id end,
              fn z => z: 'a)
```

According to the inference rules in Section 4.10 the first example can be elaborated, but the second cannot since `'a` is bound at the outer value declaration leaving no possibility of two different instantiations of the type of `Id` in the application `Id Id`.

## 4.7 Non-expansive Expressions

In order to treat polymorphic references and exceptions, the set `Exp` of expressions is partitioned into two classes, the *expansive* and the *non-expansive* expressions. Any variable, constructor and `fn` expression is non-expansive; all other expressions are said to be expansive. The idea is that the dynamic evaluation of a non-expansive expression will neither generate an exception nor extend the domain of the memory, while the evaluation of an expansive expression might.

## 4.8 Closure

Let  $\tau$  be a type and  $A$  a semantic object. Then  $\text{Clos}_A(\tau)$ , the *closure* of  $\tau$  with respect to  $A$ , is the type scheme  $\forall \alpha^{(k)}. \tau$ , where  $\alpha^{(k)} = \text{tyvars}(\tau) \setminus \text{tyvars } A$ . Commonly,  $A$  will be a context  $C$ . We abbreviate the *total* closure  $\text{Clos}_{\{\}}(\tau)$  to  $\text{Clos}(\tau)$ . If the range of a variable environment  $VE$  contains only types (rather than arbi-

trary type schemes) we set

$$\text{Clos}_A VE = \{id \mapsto \text{Clos}_A(\tau) ; VE(id) = \tau\}$$

with a similar definition for  $\text{Clos}_A CE$ .

Closing a variable environment  $VE$  that stems from the elaboration of a value binding  $valbind$  requires extra care to ensure type security of references and exceptions and correct scoping of explicit type variables. Recall that  $valbind$  is not allowed to bind the same variable twice. Thus, for each  $var \in \text{Dom } VE$  there is a unique  $pat = exp$  in  $valbind$  which binds  $var$ . If  $VE(var) = \tau$ , let  $\text{Clos}_{C, valbind} VE(var) = \forall \alpha^{(k)}. \tau$ , where

$$\alpha^{(k)} = \begin{cases} \text{tyvars } \tau \setminus \text{tyvars } C, & \text{if } exp \text{ is non-expansive;} \\ \text{apptyvars } \tau \setminus \text{tyvars } C, & \text{if } exp \text{ is expansive.} \end{cases}$$

Notice that the form of  $valbind$  does not affect the binding of applicative type variables, only the binding of imperative type variables.

## 4.9 Type Environments and Well-formedness

A type environment takes the form

$$TE = \{tycon_i \mapsto (\theta_i, CE_i) ; 1 \leq i \leq k\}$$

and is *well-formed* if it satisfies the following conditions:

1. Either  $CE_i = \{\}$ , or  $\theta_i$  has the form  $t_i$  and each  $CE_i(con)$  has the form  $\forall \alpha^{(k)}. (\tau \rightarrow \alpha^{(k)} t_i)$ . The latter case occurs when  $tycon_i$  is a datatype constructor; it is conveniently distinguished from an ordinary type constructor by possessing at least one value constructor.
2. If  $tycon_i$  is a datatype constructor different from `ref`, so that  $TE(tycon_i) = (t_i, CE_i)$  with  $CE_i \neq \{\}$ , then  $t_i$  admits equality only if, for each  $CE_i(con) = \forall \alpha^{(k)}. (\tau \rightarrow \alpha^{(k)} t_i)$ , the type function  $\Lambda \alpha^{(k)}. \tau$  also admits equality. Furthermore, as many such  $t_i$  as possible admit equality, subject to the foregoing condition.

This ensures that the equality predicate  $=$  will be applicable to a constructed value  $con(v)$  of type  $\tau^{(k)} t_i$  only when it is applicable to the value  $v$  itself, whose type is  $\tau \{ \tau^{(k)} / \alpha^{(k)} \}$ .

3. Different datatype constructors are bound to different type names; i.e., if  $i \neq j$  and  $TE(tycon_i) = (t_i, CE_i)$  and  $\text{Dom } CE_i \neq \emptyset$  and  $TE(tycon_j) = (t_j, CE_j)$  and  $\text{Dom } CE_j \neq \emptyset$  then  $t_i \neq t_j$ .



All type environments occurring in the rules are assumed well-formed.

For any  $TE$  of the form

$$TE = \{tycon_i \mapsto (t_i, CE_i) ; 1 \leq i \leq k\},$$

where no  $CE_i$  is the empty map, and for any  $E$  we define  $\text{Abs}(E, TE)$  to be the environment obtained from  $E$  and  $TE$  as follows. First, let  $\text{Abs}(TE)$  be the type environment  $\{tycon_i \mapsto (t_i, \{\}) ; 1 \leq i \leq k\}$  in which all constructor environments  $CE_i$  have been replaced by the empty map. (The effect of this first step is to convert each  $tycon_i$  into an ordinary type constructor.) Let  $t'_1, \dots, t'_k$  be new distinct type names none of which admit equality. Then  $\text{Abs}(E, TE)$  is the result of simultaneously substituting  $t'_i$  for  $t_i$ ,  $1 \leq i \leq k$ , throughout  $E + \text{Abs}(TE)$ . (The effect of this second step is to ensure that the use of equality on an **abstype** is restricted to the **with** part.)

## 4.10 Inference Rules

Each rule of the semantics allows inferences among sentences of the form

$$A \vdash \textit{phrase} \Rightarrow A'$$

where  $A$  is usually an environment or a context,  $\textit{phrase}$  is a phrase of the Core, and  $A'$  is a semantic object – usually a type or an environment. It may be pronounced “ $\textit{phrase}$  elaborates to  $A'$  in (context or environment)  $A$ ”. Some rules have extra hypotheses not of this form; they may be called side conditions.

In the presentation of the rules, phrases within single angle brackets  $\langle \rangle$  are called *first options*, and those within double angle brackets  $\langle\langle \rangle\rangle$  are called *second options*. To reduce the number of rules, we have adopted the following convention:

In each instance of a rule, the first options must be either all present or all absent; similarly the second options must be either all present or all absent.

Although not assumed in our definitions, it is intended that every context  $C = T, U, E$  has the property that tynames  $E \subseteq T$ . Thus  $T$  may be thought of, loosely, as containing all type names which “have been generated”. It is necessary to include  $T$  as a separate component in a context, since tynames  $E$  may not contain all the type names which have been generated; one reason is that a context  $T, \emptyset, E$  is a projection of the basis  $B = (M, T), F, G, E$  whose other components  $F$  and  $G$  could contain other such names – recorded in  $T$  but not present in  $E$ . Of course, remarks about what “has been generated” are not precise in terms of the semantic rules. But the following precise result may easily be demonstrated:

Let  $S$  be a sentence  $T, U, E \vdash \textit{phrase} \Rightarrow A$  such that tynames  $E \subseteq T$ , and let  $S'$  be a sentence  $T', U', E' \vdash \textit{phrase}' \Rightarrow A'$  occurring in a proof of  $S$ ; then also tynames  $E' \subseteq T'$ .

### Atomic Expressions

$$\boxed{C \vdash \textit{atexp} \Rightarrow \tau}$$

$$\frac{C(\textit{longvar}) \succ \tau}{C \vdash \textit{longvar} \Rightarrow \tau} \quad (1)$$

$$\frac{C(\textit{longcon}) \succ \tau}{C \vdash \textit{longcon} \Rightarrow \tau} \quad (2)$$

$$\frac{C(\textit{longexcon}) = \tau}{C \vdash \textit{longexcon} \Rightarrow \tau} \quad (3)$$

$$\frac{\langle C \vdash \textit{exprow} \Rightarrow \varrho \rangle}{C \vdash \{ \langle \textit{exprow} \rangle \} \Rightarrow \{ \} \langle + \varrho \rangle \text{ in Type}} \quad (4)$$

$$\frac{C \vdash dec \Rightarrow E \quad C \oplus E \vdash exp \Rightarrow \tau}{C \vdash \text{let } dec \text{ in } exp \text{ end} \Rightarrow \tau} \quad (5)$$

$$\frac{C \vdash exp \Rightarrow \tau}{C \vdash (exp) \Rightarrow \tau} \quad (6)$$

*Comments:*

- (1),(2) The instantiation of type schemes allows different occurrences of a single *longvar* or *longcon* to assume different types.
- (5) The use of  $\oplus$ , here and elsewhere, ensures that type names generated by the first sub-phrase are different from type names generated by the second sub-phrase.

### Expression Rows

$$\boxed{C \vdash exprow \Rightarrow \varrho}$$

$$\frac{C \vdash exp \Rightarrow \tau \quad \langle C \vdash exprow \Rightarrow \varrho \rangle}{C \vdash lab = exp \langle , exprow \rangle \Rightarrow \{lab \mapsto \tau\} \langle + \varrho \rangle} \quad (7)$$

### Expressions

$$\boxed{C \vdash exp \Rightarrow \tau}$$

$$\frac{C \vdash atexp \Rightarrow \tau}{C \vdash atexp \Rightarrow \tau} \quad (8)$$

$$\frac{C \vdash exp \Rightarrow \tau' \rightarrow \tau \quad C \vdash atexp \Rightarrow \tau'}{C \vdash exp atexp \Rightarrow \tau} \quad (9)$$

$$\frac{C \vdash exp \Rightarrow \tau \quad C \vdash ty \Rightarrow \tau}{C \vdash exp : ty \Rightarrow \tau} \quad (10)$$

$$\frac{C \vdash exp \Rightarrow \tau \quad C \vdash match \Rightarrow \text{exn} \rightarrow \tau}{C \vdash exp \text{ handle } match \Rightarrow \tau} \quad (11)$$

$$\frac{C \vdash exp \Rightarrow \text{exn}}{C \vdash \text{raise } exp \Rightarrow \tau} \quad (12)$$

$$\frac{C \vdash match \Rightarrow \tau}{C \vdash \text{fn } match \Rightarrow \tau} \quad (13)$$

*Comments:*

- (8) The relational symbol  $\vdash$  is overloaded for all syntactic classes (here atomic expressions and expressions).

- (10) Here  $\tau$  is determined by  $C$  and  $ty$ . Notice that type variables in  $ty$  cannot be instantiated in obtaining  $\tau$ ; thus the expression  $1: 'a$  will not elaborate successfully, nor will the expression  $(\text{fn } x \Rightarrow x): 'a \rightarrow 'b$ . The effect of type variables in an explicitly typed expression is to indicate exactly the degree of polymorphism present in the expression.
- (12) Note that  $\tau$  does not occur in the premise; thus a `raise` expression has “arbitrary” type.

**Matches**

$$\boxed{C \vdash match \Rightarrow \tau}$$

$$\frac{C \vdash mrule \Rightarrow \tau \quad \langle C \vdash match \Rightarrow \tau \rangle}{C \vdash mrule \langle | match \rangle \Rightarrow \tau} \quad (14)$$

**Match Rules**

$$\boxed{C \vdash mrule \Rightarrow \tau}$$

$$\frac{C \vdash pat \Rightarrow (VE, \tau) \quad C + VE \vdash exp \Rightarrow \tau'}{C \vdash pat \Rightarrow exp \Rightarrow \tau \rightarrow \tau'} \quad (15)$$

*Comment:* This rule allows new free type variables to enter the context. These new type variables will be chosen, in effect, during the elaboration of  $pat$  (i.e., in the inference of the first hypothesis). In particular, their choice may have to be made to agree with type variables present in any explicit type expression occurring within  $exp$  (see rule 10).

**Declarations**

$$\boxed{C \vdash dec \Rightarrow E}$$

$$\frac{C + U \vdash valbind \Rightarrow VE \quad VE' = \text{Clos}_{C, valbind} VE \quad U \cap \text{tyvars } VE' = \emptyset}{C \vdash \text{val}_U valbind \Rightarrow VE' \text{ in Env}} \quad (16)$$

$$\frac{C \vdash typbind \Rightarrow TE}{C \vdash \text{type } typbind \Rightarrow TE \text{ in Env}} \quad (17)$$

$$\frac{C \oplus TE \vdash datbind \Rightarrow VE, TE \quad \forall (t, CE) \in \text{Ran } TE, t \notin (T \text{ of } C)}{C \vdash \text{datatype } datbind \Rightarrow (VE, TE) \text{ in Env}} \quad (18)$$

$$\frac{C \oplus TE \vdash datbind \Rightarrow VE, TE \quad \forall (t, CE) \in \text{Ran } TE, t \notin (T \text{ of } C) \quad C \oplus (VE, TE) \vdash dec \Rightarrow E}{C \vdash \text{abstype } datbind \text{ with } dec \text{ end} \Rightarrow \text{Abs}(E, TE)} \quad (19)$$

$$\frac{C \vdash exbind \Rightarrow EE \quad VE = EE}{C \vdash \text{exception } exbind \Rightarrow (VE, EE) \text{ in Env}} \quad (20)$$

$$\frac{C \vdash dec_1 \Rightarrow E_1 \quad C \oplus E_1 \vdash dec_2 \Rightarrow E_2}{C \vdash \text{local } dec_1 \text{ in } dec_2 \text{ end} \Rightarrow E_2} \quad (21)$$

$$\frac{C(\text{longstrid}_1) = (m_1, E_1) \quad \dots \quad C(\text{longstrid}_n) = (m_n, E_n)}{C \vdash \text{open } longstrid_1 \dots longstrid_n \Rightarrow E_1 + \dots + E_n} \quad (22)$$

$$\overline{C \vdash \quad \Rightarrow \{\}} \text{ in Env} \quad (23)$$

$$\frac{C \vdash dec_1 \Rightarrow E_1 \quad C \oplus E_1 \vdash dec_2 \Rightarrow E_2}{C \vdash dec_1 \langle ; \rangle dec_2 \Rightarrow E_1 + E_2} \quad (24)$$

*Comments:*

(16) Here  $VE$  will contain types rather than general type schemes. The closure of  $VE$  is exactly what allows variables to be used polymorphically, via rule 1.

Moreover,  $U$  is the set of explicit type variables scoped at this particular occurrence of `val valbind`, cf. Section 4.6, page 20. The side-condition on  $U$  ensures that these explicit type variables are bound by the closure operation. On the other hand, no *other* explicit type variable occurring free in  $VE$  will become bound, since it must be in  $U$  of  $C$ , and is therefore excluded from closure by the definition of the closure operation (Section 4.8, page 21) since  $U$  of  $C \subseteq \text{tyvars } C$ .

(18),(19) The side condition is the formal way of expressing that the elaboration of each datatype binding generates new type names. Adding  $TE$  to the context on the left of the  $\vdash$  captures the recursive nature of the binding. Recall that  $TE$  is assumed well-formed (as defined in Section 4.9). If  $\text{tynames}(E \text{ of } C) \subseteq T$  of  $C$  and the side condition is satisfied then  $C \oplus TE$  is well-formed.

(19) The Abs operation was defined in Section 4.9, page 22.

(20) No closure operation is used here, since  $EE$  maps exception names to types rather than to general type schemes. Note that  $EE$  is also recorded in the `VarEnv` component of the resulting environment (see Section 4.3, page 18).

## Value Bindings

$$\boxed{C \vdash \text{valbind} \Rightarrow VE}$$

$$\frac{C \vdash pat \Rightarrow (VE, \tau) \quad C \vdash exp \Rightarrow \tau \quad \langle C \vdash \text{valbind} \Rightarrow VE' \rangle}{C \vdash pat = exp \langle \text{and } \text{valbind} \rangle \Rightarrow VE \langle + VE' \rangle} \quad (25)$$

$$\frac{C + VE \vdash \text{valbind} \Rightarrow VE}{C \vdash \text{rec } \text{valbind} \Rightarrow VE} \quad (26)$$

*Comments:*

- (25) When the option is present we have  $\text{Dom } VE \cap \text{Dom } VE' = \emptyset$  by the syntactic restrictions.
- (26) Modifying  $C$  by  $VE$  on the left captures the recursive nature of the binding. From rule 25 we see that any type scheme occurring in  $VE$  will have to be a type. Thus each use of a recursive function in its own body must be ascribed the same type.

### Type Bindings

$$\boxed{C \vdash \text{typbind} \Rightarrow TE}$$

$$\frac{\text{tyvarseq} = \alpha^{(k)} \quad C \vdash \text{ty} \Rightarrow \tau \quad \langle C \vdash \text{typbind} \Rightarrow TE \rangle}{C \vdash \text{tyvarseq } \text{tycon} = \text{ty} \langle \text{and } \text{typbind} \rangle \Rightarrow \{ \text{tycon} \mapsto (\Lambda \alpha^{(k)}. \tau, \{ \}) \} \langle + TE \rangle} \quad (27)$$

*Comment:* The syntactic restrictions ensure that the type function  $\Lambda \alpha^{(k)}. \tau$  satisfies the well-formedness constraints of Section 4.4 and they ensure  $\text{tycon} \notin \text{Dom } TE$ .

### Data Type Bindings

$$\boxed{C \vdash \text{datbind} \Rightarrow VE, TE}$$

$$\frac{\text{tyvarseq} = \alpha^{(k)} \quad C, \alpha^{(k)} t \vdash \text{conbind} \Rightarrow CE \quad \langle C \vdash \text{datbind} \Rightarrow VE, TE \rangle}{C \vdash \text{tyvarseq } \text{tycon} = \text{conbind} \langle \text{and } \text{datbind} \rangle \Rightarrow \text{Clos } CE \langle + VE \rangle, \{ \text{tycon} \mapsto (t, \text{Clos } CE) \} \langle + TE \rangle} \quad (28)$$

*Comment:* The syntactic restrictions ensure  $\text{Dom } VE \cap \text{Dom } CE = \emptyset$  and  $\text{tycon} \notin \text{Dom } TE$ .

### Constructor Bindings

$$\boxed{C, \tau \vdash \text{conbind} \Rightarrow CE}$$

$$\frac{\langle C \vdash \text{ty} \Rightarrow \tau' \rangle \quad \langle \langle C, \tau \vdash \text{conbind} \Rightarrow CE \rangle \rangle}{C, \tau \vdash \text{con} \langle \text{of } \text{ty} \rangle \langle \langle \mid \text{conbind} \rangle \rangle \Rightarrow \{ \text{con} \mapsto \tau \} \langle + \{ \text{con} \mapsto \tau' \rightarrow \tau \} \rangle \langle \langle + CE \rangle \rangle} \quad (29)$$

*Comment:* By the syntactic restrictions  $\text{con} \notin \text{Dom } CE$ .

### Exception Bindings

$$\boxed{C \vdash \text{exbind} \Rightarrow EE}$$

$$\frac{\langle C \vdash \text{ty} \Rightarrow \tau \quad \tau \text{ is imperative} \rangle \quad \langle \langle C \vdash \text{exbind} \Rightarrow EE \rangle \rangle}{C \vdash \text{excon} \langle \text{of } \text{ty} \rangle \langle \langle \text{and } \text{exbind} \rangle \rangle \Rightarrow \{ \text{excon} \mapsto \text{exn} \} \langle + \{ \text{excon} \mapsto \tau \rightarrow \text{exn} \} \rangle \langle \langle + EE \rangle \rangle} \quad (30)$$

$$\frac{C(\text{longexcon}) = \tau \quad \langle C \vdash \text{exbind} \Rightarrow EE \rangle}{C \vdash \text{excon} = \text{longexcon} \langle \text{and } \text{exbind} \rangle \Rightarrow \{ \text{excon} \mapsto \tau \} \langle + EE \rangle} \quad (31)$$

*Comments:*

(30) Notice that  $\tau$  must not contain any applicative type variables.

(30),(31) There is a unique  $EE$ , for each  $C$  and  $exbind$ , such that  $C \vdash exbind \Rightarrow EE$ .

### Atomic Patterns

$$\boxed{C \vdash atpat \Rightarrow (VE, \tau)}$$

$$\overline{C \vdash - \Rightarrow (\{\}, \tau)} \quad (32)$$

$$\overline{C \vdash var \Rightarrow (\{var \mapsto \tau\}, \tau)} \quad (33)$$

$$\frac{C(longcon) \succ \tau^{(k)}t}{C \vdash longcon \Rightarrow (\{\}, \tau^{(k)}t)} \quad (34)$$

$$\frac{C(longexcon) = \text{exn}}{C \vdash longexcon \Rightarrow (\{\}, \text{exn})} \quad (35)$$

$$\frac{\langle C \vdash patrow \Rightarrow (VE, \varrho) \rangle}{C \vdash \{ \langle patrow \rangle \} \Rightarrow ( \{ \} \langle + VE \rangle, \{ \} \langle + \varrho \rangle \text{ in Type } )} \quad (36)$$

$$\frac{C \vdash pat \Rightarrow (VE, \tau)}{C \vdash ( pat ) \Rightarrow (VE, \tau)} \quad (37)$$

*Comments:*

(33) Note that  $var$  can assume a type, not a general type scheme.

### Pattern Rows

$$\boxed{C \vdash patrow \Rightarrow (VE, \varrho)}$$

$$\overline{C \vdash \dots \Rightarrow (\{\}, \varrho)} \quad (38)$$

$$\frac{C \vdash pat \Rightarrow (VE, \tau) \quad \langle C \vdash patrow \Rightarrow (VE', \varrho) \quad lab \notin \text{Dom } \varrho \rangle}{C \vdash lab = pat \langle , patrow \rangle \Rightarrow (VE \langle + VE' \rangle, \{lab \mapsto \tau\} \langle + \varrho \rangle)} \quad (39)$$

*Comment:*

(39) By the syntactic restrictions,  $\text{Dom } VE \cap \text{Dom } VE' = \emptyset$ .

**Patterns**

$$\boxed{C \vdash pat \Rightarrow (VE, \tau)}$$

$$\frac{C \vdash atpat \Rightarrow (VE, \tau)}{C \vdash atpat \Rightarrow (VE, \tau)} \quad (40)$$

$$\frac{C(longcon) \succ \tau' \rightarrow \tau \quad C \vdash atpat \Rightarrow (VE, \tau')}{C \vdash longcon atpat \Rightarrow (VE, \tau)} \quad (41)$$

$$\frac{C(longexcon) = \tau \rightarrow \text{exn} \quad C \vdash atpat \Rightarrow (VE, \tau)}{C \vdash longexcon atpat \Rightarrow (VE, \text{exn})} \quad (42)$$

$$\frac{C \vdash pat \Rightarrow (VE, \tau) \quad C \vdash ty \Rightarrow \tau}{C \vdash pat : ty \Rightarrow (VE, \tau)} \quad (43)$$

$$\frac{C \vdash var \Rightarrow (VE, \tau) \quad \langle C \vdash ty \Rightarrow \tau \rangle}{C \vdash pat \Rightarrow (VE', \tau)} \quad (44)$$

$$\frac{}{C \vdash var \langle : ty \rangle \text{ as } pat \Rightarrow (VE + VE', \tau)}$$

*Comments:*

(44) By the syntactic restrictions,  $\text{Dom } VE \cap \text{Dom } VE' = \emptyset$ .

**Type Expressions**

$$\boxed{C \vdash ty \Rightarrow \tau}$$

$$\frac{tyvar = \alpha}{C \vdash tyvar \Rightarrow \alpha} \quad (45)$$

$$\frac{\langle C \vdash tyrow \Rightarrow \varrho \rangle}{C \vdash \{ \langle tyrow \rangle \} \Rightarrow \{ \} \langle + \varrho \rangle \text{ in Type}} \quad (46)$$

$$\frac{tyseq = ty_1 \cdots ty_k \quad C \vdash ty_i \Rightarrow \tau_i \ (1 \leq i \leq k) \quad C(longtycon) = (\theta, CE)}{C \vdash tyseq longtycon \Rightarrow \tau^{(k)}\theta} \quad (47)$$

$$\frac{C \vdash ty \Rightarrow \tau \quad C \vdash ty' \Rightarrow \tau'}{C \vdash ty \rightarrow ty' \Rightarrow \tau \rightarrow \tau'} \quad (48)$$

$$\frac{C \vdash ty \Rightarrow \tau}{C \vdash ( ty ) \Rightarrow \tau} \quad (49)$$

*Comments:*

(47) Recall that for  $\tau^{(k)}\theta$  to be defined,  $\theta$  must have arity  $k$ .

**Type-expression Rows**

$$\boxed{C \vdash tyrow \Rightarrow \varrho}$$

$$\frac{C \vdash ty \Rightarrow \tau \quad \langle C \vdash tyrow \Rightarrow \varrho \rangle}{C \vdash lab : ty \langle , tyrow \rangle \Rightarrow \{ lab \mapsto \tau \} \langle + \varrho \rangle} \quad (50)$$

*Comment:* The syntactic constraints ensure  $lab \notin \text{Dom } \varrho$ .



### 4.11 Further Restrictions

There are a few restrictions on programs which should be enforced by a compiler, but are better expressed separately from the preceding Inference Rules. They are as follows:

1. For each occurrence of a record pattern containing a record wildcard, i.e. of the form  $\{lab_1=pat_1, \dots, lab_m=pat_m, \dots\}$  the program context must determine uniquely the domain  $\{lab_1, \dots, lab_n\}$  of its record type, where  $m \leq n$ ; thus, the context must determine the labels  $\{lab_{m+1}, \dots, lab_n\}$  of the fields to be matched by the wildcard. For this purpose, an explicit type constraint may be needed. This restriction is necessary to ensure the existence of principal type schemes.
2. In a match of the form  $pat_1 \Rightarrow exp_1 \mid \dots \mid pat_n \Rightarrow exp_n$  the pattern sequence  $pat_1, \dots, pat_n$  should be *irredundant*; that is, each  $pat_j$  must match some value (of the right type) which is not matched by  $pat_i$  for any  $i < j$ . In the context  $\text{fn } match$ , the *match* must also be *exhaustive*; that is, every value (of the right type) must be matched by some  $pat_i$ . The compiler must give warning on violation of these restrictions, but should still compile the match. The restrictions are inherited by derived forms; in particular, this means that in the function binding  $\text{var } atpat_1 \dots atpat_n (: ty) = exp$  (consisting of one clause only), each separate  $atpat_i$  should be exhaustive by itself.

### 4.12 Principal Environments

Let  $C$  be a context, and suppose that  $C \vdash dec \Rightarrow E$  according to the preceding Inference Rules. Then  $E$  is *principal* (for  $dec$  in the context  $C$ ) if, for all  $E'$  for which  $C \vdash dec \Rightarrow E'$ , we have  $E \succ E'$ . We claim that if  $dec$  elaborates to any environment in  $C$  then it elaborates to a principal environment in  $C$ . Strictly, we must allow for the possibility that type names which do not occur in  $C$ , are chosen differently for  $E$  and  $E'$ . Moreover, some imperative type variables may occur free in  $E$  without occurring free in  $C$ . The stated claim is therefore made up to such variation.

## 5 Static Semantics for Modules

### 5.1 Semantic Objects

The simple objects for Modules static semantics are exactly as for the Core. The compound objects are those for the Core, augmented by those in Figure 11.

$$\begin{aligned}
 M &\in \text{StrNameSet} = \text{Fin}(\text{StrName}) \\
 N \text{ or } (M, T) &\in \text{NameSet} = \text{StrNameSet} \times \text{TyNameSet} \\
 \Sigma \text{ or } (N)S &\in \text{Sig} = \text{NameSet} \times \text{Str} \\
 \Phi \text{ or } (N)(S, (N')S') &\in \text{FunSig} = \text{NameSet} \times (\text{Str} \times \text{Sig}) \\
 G &\in \text{SigEnv} = \text{SigId} \xrightarrow{\text{fin}} \text{Sig} \\
 F &\in \text{FunEnv} = \text{FunId} \xrightarrow{\text{fin}} \text{FunSig} \\
 B \text{ or } N, F, G, E &\in \text{Basis} = \text{NameSet} \times \text{FunEnv} \times \text{SigEnv} \times \text{Env}
 \end{aligned}$$

Figure 11: Further Compound Semantic Objects

The prefix  $(N)$ , in signatures and functor signatures, binds both type names and structure names. We shall always consider a set  $N$  of names as partitioned into a pair  $(M, T)$  of sets of the two kinds of name.

It is sometimes convenient to work with an arbitrary semantic object  $A$ , or assembly  $A$  of such objects. As with the function tyname,  $\text{strnames}(A)$  and  $\text{names}(A)$  denote respectively the set of structure names and the set of names occurring free in  $A$ .

We shall often need to change bound names in semantic objects. For example, we sometimes require that  $N \cap N' = \emptyset$  in a functor signature. More generally, for arbitrary  $A$  it is sometimes convenient to assume that *all* nameset prefixes  $N$  occurring in  $A$  are disjoint. In that case we say that we are *disjoining bound names* in  $A$ .

For any structure  $S = (m, (SE, TE, VE, EE))$  we call  $m$  the *structure name* or *name* of  $S$ ; also, the *proper substructures* of  $S$  are the members of  $\text{Ran } SE$  and their proper substructures. The *substructures* of  $S$  are  $S$  itself and its proper substructures. The structures *occurring in* an object or assembly  $A$  are the structures and substructures from which it is built.

The operations of projection, injection and modification are as for the Core. Moreover, we define  $C$  of  $B$  to be the context  $(T \text{ of } B, \emptyset, E \text{ of } B)$ , i.e. with an empty set of explicit type variables. Also, we frequently need to modify a basis  $B$  by an environment  $E$  (or a structure environment  $SE$  say), at the same time extending  $N$  of  $B$  to include the type names and structure names of  $E$  (or of  $SE$  say). We therefore define  $B \oplus SE$ , for example, to mean  $B + (\text{names } SE, SE)$ .

## 5.2 Consistency

A set of type structures is said to be *consistent* if, for all  $(\theta_1, CE_1)$  and  $(\theta_2, CE_2)$  in the set, if  $\theta_1 = \theta_2$  then

$$CE_1 = \{\} \text{ or } CE_2 = \{\} \text{ or } CE_1 = CE_2$$

A semantic object  $A$  or assembly  $A$  of objects is said to be *consistent* if, after disjointing bound names, for all  $S_1$  and  $S_2$  occurring in  $A$  and for every *longstrid* and every *longtycon*

1. If  $m$  of  $S_1 = m$  of  $S_2$ , and both  $S_1(\textit{longstrid})$  and  $S_2(\textit{longstrid})$  exist, then

$$m \text{ of } S_1(\textit{longstrid}) = m \text{ of } S_2(\textit{longstrid})$$

2. If  $m$  of  $S_1 = m$  of  $S_2$ , and both  $S_1(\textit{longtycon})$  and  $S_2(\textit{longtycon})$  exist, then

$$\theta \text{ of } S_1(\textit{longtycon}) = \theta \text{ of } S_2(\textit{longtycon})$$

3. The set of all type structures in  $A$  is consistent

As an example, a functor signature  $(N)(S, (N')S')$  is consistent if, assuming first that  $N \cap N' = \emptyset$ , the assembly  $A = \{S, S'\}$  is consistent.

We may loosely say that two structures  $S_1$  and  $S_2$  are consistent if  $\{S_1, S_2\}$  is consistent, but must remember that this is stronger than the assertion that  $S_1$  is consistent and  $S_2$  is consistent.

Note that if  $A$  is a consistent assembly and  $A' \subset A$  then  $A'$  is also a consistent assembly.

## 5.3 Well-formedness

Conditions for the well-formedness of type environments  $TE$  are given with the Core static semantics.

A signature  $(N)S$  is *well-formed* if, whenever  $(m, E)$  is a substructure of  $S$  and  $m \notin N$ , then  $N \cap (\textit{names } E) = \emptyset$ . A functor signature  $(N)(S, (N')S')$  is *well-formed* if  $(N)S$ ,  $(N')S'$  and  $(N \cup N')S'$  are well-formed, and  $\textit{names}(N')S' \cap N \subseteq \textit{names } S$  (the latter condition is satisfied automatically for user defined functors).

An object or assembly  $A$  is *well-formed* if every type environment, signature and functor signature occurring in  $A$  is well-formed.

## 5.4 Cycle-freedom

An object or assembly  $A$  is *cycle-free* if it contains no cycle of structure names; that is, there is no sequence

$$m_0, \dots, m_{k-1}, m_k = m_0 \quad (k > 0)$$

of structure names such that, for each  $i$  ( $0 \leq i < k$ ) some structure with name  $m_i$  occurring in  $A$  has a proper substructure with name  $m_{i+1}$ .

## 5.5 Admissibility

An object or assembly  $A$  is *admissible* if it is consistent, well-formed and cycle-free. Henceforth it is assumed that all objects mentioned are admissible; in particular, the admissibility of each semantic object mentioned is taken as a condition throughout the semantic rules which follow. (In our semantic description we have not undertaken to indicate how admissibility should be checked in an implementation.)

## 5.6 Type Realisation

A *type realisation* is a map  $\varphi_{\text{Ty}} : \text{TyName} \rightarrow \text{TypeFcn}$  such that  $t$  and  $\varphi_{\text{Ty}}(t)$  have the same arity, and if  $t$  admits equality then so does  $\varphi_{\text{Ty}}(t)$ .

The *support*  $\text{Supp } \varphi_{\text{Ty}}$  of a type realisation  $\varphi_{\text{Ty}}$  is the set of type names  $t$  for which  $\varphi_{\text{Ty}}(t) \neq t$ .

## 5.7 Realisation

A *realisation* is a function  $\varphi$  of names, partitioned into a type realisation  $\varphi_{\text{Ty}} : \text{TyName} \rightarrow \text{TypeFcn}$  and a function  $\varphi_{\text{Str}} : \text{StrName} \rightarrow \text{StrName}$ . The *support*  $\text{Supp } \varphi$  of a realisation  $\varphi$  is the set of names  $n$  for which  $\varphi(n) \neq n$ . The *yield*  $\text{Yield } \varphi$  of a realisation  $\varphi$  is the set of names which occur in some  $\varphi(n)$  for which  $n \in \text{Supp } \varphi$ .

Realisations  $\varphi$  are extended to apply to all semantic objects; their effect is to replace each name  $n$  by  $\varphi(n)$ . In applying  $\varphi$  to an object with bound names, such as a signature  $(N)S$ , first bound names must be changed so that, for each binding prefix  $(N)$ ,

$$N \cap (\text{Supp } \varphi \cup \text{Yield } \varphi) = \emptyset .$$

## 5.8 Signature Instantiation

A structure  $S_2$  is an *instance* of a signature  $\Sigma_1 = (N_1)S_1$ , written  $\Sigma_1 \geq S_2$ , if there exists a realisation  $\varphi$  such that  $\varphi(S_1) = S_2$  and  $\text{Supp } \varphi \subseteq N_1$ . A signature  $\Sigma_2 = (N_2)S_2$  is an *instance* of  $\Sigma_1 = (N_1)S_1$ , written  $\Sigma_1 \geq \Sigma_2$ , if  $\Sigma_1 \geq S_2$  and  $N_2 \cap (\text{names } \Sigma_1) = \emptyset$ . We claim that  $\Sigma_1 \geq \Sigma_2$  iff, for all  $S$ , whenever  $\Sigma_2 \geq S$  then  $\Sigma_1 \geq S$ .

## 5.9 Functor Signature Instantiation

A pair  $(S, (N')S')$  is called a *functor instance*. Given  $\Phi = (N_1)(S_1, (N'_1)S'_1)$ , a functor instance  $(S_2, (N'_2)S'_2)$  is an *instance* of  $\Phi$ , written  $\Phi \geq (S_2, (N'_2)S'_2)$ , if there exists a realisation  $\varphi$  such that  $\varphi(S_1, (N'_1)S'_1) = (S_2, (N'_2)S'_2)$  and  $\text{Supp } \varphi \subseteq N_1$ .

### 5.10 Enrichment

In matching a structure to a signature, the structure will be allowed both to have more components, and to be more polymorphic, than (an instance of) the signature. Precisely, we define enrichment of structures, environments and type structures by mutual recursion as follows.

A structure  $S_1 = (m_1, E_1)$  *enriches* another structure  $S_2 = (m_2, E_2)$ , written  $S_1 \succ S_2$ , if

1.  $m_1 = m_2$
2.  $E_1 \succ E_2$

An environment  $E_1 = (SE_1, TE_1, VE_1, EE_1)$  *enriches* another environment  $E_2 = (SE_2, TE_2, VE_2, EE_2)$ , written  $E_1 \succ E_2$ , if

1.  $\text{Dom } SE_1 \supseteq \text{Dom } SE_2$ , and  $SE_1(\text{strid}) \succ SE_2(\text{strid})$  for all  $\text{strid} \in \text{Dom } SE_2$
2.  $\text{Dom } TE_1 \supseteq \text{Dom } TE_2$ , and  $TE_1(\text{tycon}) \succ TE_2(\text{tycon})$  for all  $\text{tycon} \in \text{Dom } TE_2$
3.  $\text{Dom } VE_1 \supseteq \text{Dom } VE_2$ , and  $VE_1(\text{id}) \succ VE_2(\text{id})$  for all  $\text{id} \in \text{Dom } VE_2$
4.  $\text{Dom } EE_1 \supseteq \text{Dom } EE_2$ , and  $EE_1(\text{excon}) = EE_2(\text{excon})$  for all  $\text{excon} \in \text{Dom } EE_2$

Finally, a type structure  $(\theta_1, CE_1)$  *enriches* another type structure  $(\theta_2, CE_2)$ , written  $(\theta_1, CE_1) \succ (\theta_2, CE_2)$ , if

1.  $\theta_1 = \theta_2$
2. Either  $CE_1 = CE_2$  or  $CE_2 = \{\}$

### 5.11 Signature Matching

A structure  $S$  *matches* a signature  $\Sigma_1$  if there exists a structure  $S^-$  such that  $\Sigma_1 \geq S^- \prec S$ . Thus matching is a combination of instantiation and enrichment. There is at most one such  $S^-$ , given  $\Sigma_1$  and  $S$ . Moreover, writing  $\Sigma_1 = (N_1)S_1$ , if  $\Sigma_1 \geq S^-$  then there exists a realisation  $\varphi$  with  $\text{Supp } \varphi \subseteq N_1$  and  $\varphi(S_1) = S^-$ . We shall then say that  $S$  matches  $\Sigma_1$  *via*  $\varphi$ .

A signature  $\Sigma_2$  *matches* a signature  $\Sigma_1$  if for all structures  $S$ , if  $S$  matches  $\Sigma_2$  then  $S$  matches  $\Sigma_1$ . We claim that  $\Sigma_2 = (N_2)S_2$  matches  $\Sigma_1 = (N_1)S_1$  if and only if there exists a realisation  $\varphi$  with  $\text{Supp } \varphi \subseteq N_1$  and  $\varphi(S_1) \prec S_2$  and  $N_2 \cap \text{names } \Sigma_1 = \emptyset$ .

## 5.12 Principal Signatures

Let  $B$  be a basis, and suppose that  $B \vdash \text{sigexp} \Rightarrow S$  according to the rules below. Then  $(N)S$  is *principal* (for  $\text{sigexp}$  in the basis  $B$ ) if  $(N \text{ of } B) \cap N = \emptyset$ , and for all  $S'$  for which  $B \vdash \text{sigexp} \Rightarrow S'$  we have  $(N)S \geq S'$ . We claim that if  $\text{sigexp}$  elaborates to any structure  $S$  in  $B$  then it possesses a principal signature in  $B$ .

### 5.13 Inference Rules

As for the Core, the rules of the Modules static semantics allow sentences of the form

$$A \vdash \textit{phrase} \Rightarrow A'$$

to be inferred, where in this case  $A$  is either a basis, a context or an environment and  $A'$  is a semantic object. The convention for options is as in the Core semantics.

Although not assumed in our definitions, it is intended that every basis  $B = N, F, G, E$  in which a *topdec* is elaborated has the property that names  $F \cup \text{names } G \cup \text{names } E \subseteq N$ . This is not the case for bases in which signature expressions and specifications are elaborated, but the following Theorem can be proved:

Let  $S$  be an inferred sentence  $B \vdash \textit{topdec} \Rightarrow B'$  in which  $B$  satisfies the above condition. Then  $B'$  also satisfies the condition.

Moreover, if  $S'$  is a sentence of the form  $B'' \vdash \textit{phrase} \Rightarrow A$  occurring in a proof of  $S$ , where *phrase* is either a structure expression or a structure-level declaration, then  $B''$  also satisfies the condition.

Finally, if  $T, U, E \vdash \textit{phrase} \Rightarrow A$  occurs in a proof of  $S$ , where *phrase* is a phrase of the Core, then  $\text{tynames } E \subseteq T$ .

#### Structure Expressions

$$\boxed{B \vdash \textit{strexpr} \Rightarrow S}$$

$$\frac{B \vdash \textit{strdec} \Rightarrow E \quad m \notin (N \text{ of } B) \cup \text{names } E}{B \vdash \textit{struct strdec end} \Rightarrow (m, E)} \quad (51)$$

$$\frac{B(\textit{longstrid}) = S}{B \vdash \textit{longstrid} \Rightarrow S} \quad (52)$$

$$\frac{\begin{array}{c} B \vdash \textit{strexpr} \Rightarrow S \\ B(\textit{funid}) \geq (S'', (N')S'), S \succ S'' \\ (N \text{ of } B) \cap N' = \emptyset \end{array}}{B \vdash \textit{funid} (\textit{strexpr}) \Rightarrow S'} \quad (53)$$

$$\frac{B \vdash \textit{strdec} \Rightarrow E \quad B \oplus E \vdash \textit{strexpr} \Rightarrow S}{B \vdash \textit{let strdec in strexpr end} \Rightarrow S} \quad (54)$$

*Comments:*

- (51) The side condition ensures that each generative structure expression receives a new name. If the expression occurs in a functor body the structure name will be bound by  $(N')$  in rule 95; this will ensure that for each application of the functor, by rule 53, a new distinct name will be chosen for the structure generated.

- (53) The side condition  $(N \text{ of } B) \cap N' = \emptyset$  can always be satisfied by renaming bound names in  $(N')S'$  thus ensuring that the generated structures receive new names.

Let  $B(\text{funid}) = (N)(S_f, (N')S'_f)$ . Then the realisation  $\varphi$  for which  $\varphi(S_f, (N')S'_f) = (S'', (N')S')$  is uniquely determined by  $S$ , since  $S \succ S''$  can only hold if the type names and structure names in  $S$  and  $S''$  agree. Recall that enrichment  $\succ$  allows more components and more polymorphism, while instantiation  $\geq$  does not.

Sharing specified in the declaration of the functor *funid* is represented by the occurrence of the same name in both  $S_f$  and  $S'_f$ , and this repeated occurrence is preserved by  $\varphi$ , yielding sharing between the argument structure  $S$  and the result structure  $S'$  of this functor application.

- (54) The use of  $\oplus$ , here and elsewhere, ensures that structure and type names generated by the first sub-phrase are distinct from names generated by the second sub-phrase.

### Structure-level Declarations

$$\boxed{B \vdash \text{strdec} \Rightarrow E}$$

$$\frac{C \text{ of } B \vdash \text{dec} \Rightarrow E \quad E \text{ principal in } (C \text{ of } B) \quad \text{imptyvars } E = \emptyset}{B \vdash \text{dec} \Rightarrow E} \quad (55)$$

$$\frac{B \vdash \text{strbind} \Rightarrow SE}{B \vdash \text{structure strbind} \Rightarrow SE \text{ in Env}} \quad (56)$$

$$\frac{B \vdash \text{strdec}_1 \Rightarrow E_1 \quad B \oplus E_1 \vdash \text{strdec}_2 \Rightarrow E_2}{B \vdash \text{local strdec}_1 \text{ in strdec}_2 \text{ end} \Rightarrow E_2} \quad (57)$$

$$\frac{}{B \vdash \quad \Rightarrow \{\} \text{ in Env}} \quad (58)$$

$$\frac{B \vdash \text{strdec}_1 \Rightarrow E_1 \quad B \oplus E_1 \vdash \text{strdec}_2 \Rightarrow E_2}{B \vdash \text{strdec}_1 \langle ; \rangle \text{ strdec}_2 \Rightarrow E_1 + E_2} \quad (59)$$

*Comments:*

- (55) The side conditions ensure that all type schemes in  $E$  are as general as possible and that no imperative type variables occur free in  $E$ .



**Structure Bindings**

$$\boxed{B \vdash \text{strbind} \Rightarrow SE}$$

$$\frac{B \vdash \text{strexpr} \Rightarrow S \quad \langle B \vdash \text{sigexpr} \Rightarrow S', S \succ S' \rangle \quad \langle \langle B + \text{names } S \vdash \text{strbind} \Rightarrow SE \rangle \rangle}{B \vdash \text{strid} \langle : \text{sigexpr} \rangle = \text{strexpr} \langle \langle \text{and strbind} \rangle \rangle \Rightarrow \{ \text{strid} \mapsto S \langle ' \rangle \} \langle \langle + SE \rangle \rangle} \quad (60)$$

*Comment:* If present, *sigexpr* has the effect of restricting the view which *strid* provides of *S* while retaining sharing of names. The notation  $S \langle ' \rangle$  means  $S'$ , if the first option is present, and  $S$  if not.

**Signature Expressions**

$$\boxed{B \vdash \text{sigexpr} \Rightarrow S}$$

$$\frac{B \vdash \text{spec} \Rightarrow E}{B \vdash \text{sig spec end} \Rightarrow (m, E)} \quad (61)$$

$$\frac{B(\text{sigid}) \geq S}{B \vdash \text{sigid} \Rightarrow S} \quad (62)$$

*Comments:*

- (61) In contrast to rule 51,  $m$  is not here required to be new. The name  $m$  may be chosen to achieve the sharing required in rule 84, or to achieve the enrichment side conditions of rule 60 or 95. The choice of  $m$  must result in an admissible object.
- (62) The instance  $S$  of  $B(\text{sigid})$  is not determined by this rule, but – as in rule 61 – the instance may be chosen to achieve sharing properties or enrichment conditions.

**Signature Declarations**

$$\boxed{B \vdash \text{sigdec} \Rightarrow G}$$

$$\frac{B \vdash \text{sigbind} \Rightarrow G}{B \vdash \text{signature sigbind} \Rightarrow G} \quad (63)$$

$$\overline{B \vdash \quad \Rightarrow \{ \}} \quad (64)$$

$$\frac{B \vdash \text{sigdec}_1 \Rightarrow G_1 \quad B + G_1 \vdash \text{sigdec}_2 \Rightarrow G_2}{B \vdash \text{sigdec}_1 \langle ; \rangle \text{sigdec}_2 \Rightarrow G_1 + G_2} \quad (65)$$

*Comments:*

- (63) The first closure restriction of Section 3.6 can be enforced by replacing the  $B$  in the premise by  $B_0 + G$  of  $B$ .
- (65) A signature declaration does not create any new structures or types; hence the use of  $+$  instead of  $\oplus$ .

## Signature Bindings

$$\boxed{B \vdash \text{sigbind} \Rightarrow G}$$

$$\frac{B \vdash \text{sigexp} \Rightarrow S \quad (N)S \text{ principal in } B \quad \langle B \vdash \text{sigbind} \Rightarrow G \rangle}{B \vdash \text{sigid} = \text{sigexp} \langle \text{and sigbind} \rangle \Rightarrow \{\text{sigid} \mapsto (N)S\} \langle + G \rangle} \quad (66)$$

*Comment:* The principality condition ensures that the signature found is as general as possible given the sharing constraints present in *sigexp*. The set  $N$  is determined by the definition of principality in Section 5.12.

## Specifications

$$\boxed{B \vdash \text{spec} \Rightarrow E}$$

$$\frac{C \text{ of } B \vdash \text{valdesc} \Rightarrow VE}{B \vdash \text{val valdesc} \Rightarrow \text{Clos}VE \text{ in Env}} \quad (67)$$

$$\frac{C \text{ of } B \vdash \text{typdesc} \Rightarrow TE}{B \vdash \text{type typdesc} \Rightarrow TE \text{ in Env}} \quad (68)$$

$$\frac{C \text{ of } B \vdash \text{typdesc} \Rightarrow TE \quad \forall (\theta, CE) \in \text{Ran } TE, \theta \text{ admits equality}}{B \vdash \text{eqtype typdesc} \Rightarrow TE \text{ in Env}} \quad (69)$$

$$\frac{C \text{ of } B + TE \vdash \text{datdesc} \Rightarrow VE, TE}{B \vdash \text{datatype datdesc} \Rightarrow (VE, TE) \text{ in Env}} \quad (70)$$

$$\frac{C \text{ of } B \vdash \text{exdesc} \Rightarrow EE \quad VE = EE}{B \vdash \text{exception exdesc} \Rightarrow (VE, EE) \text{ in Env}} \quad (71)$$

$$\frac{B \vdash \text{strdesc} \Rightarrow SE}{B \vdash \text{structure strdesc} \Rightarrow SE \text{ in Env}} \quad (72)$$

$$\frac{B \vdash \text{shareq} \Rightarrow \{\}}{B \vdash \text{sharing shareq} \Rightarrow \{\} \text{ in Env}} \quad (73)$$

$$\frac{B \vdash \text{spec}_1 \Rightarrow E_1 \quad B + E_1 \vdash \text{spec}_1 \Rightarrow E_2}{B \vdash \text{local spec}_1 \text{ in spec}_2 \text{ end} \Rightarrow E_2} \quad (74)$$

$$\frac{B(\text{longstrid}_1) = (m_1, E_1) \quad \dots \quad B(\text{longstrid}_n) = (m_n, E_n)}{B \vdash \text{open longstrid}_1 \dots \text{longstrid}_n \Rightarrow E_1 + \dots + E_n} \quad (75)$$

$$\frac{B(\text{sigid}_1) \geq (m_1, E_1) \quad \dots \quad B(\text{sigid}_n) \geq (m_n, E_n)}{B \vdash \text{include sigid}_1 \dots \text{sigid}_n \Rightarrow E_1 + \dots + E_n} \quad (76)$$

$$\frac{}{B \vdash \quad \Rightarrow \{\} \text{ in Env}} \quad (77)$$

$$\frac{B \vdash \text{spec}_1 \Rightarrow E_1 \quad B + E_1 \vdash \text{spec}_1 \Rightarrow E_2}{B \vdash \text{spec}_1 \langle ; \rangle \text{ spec}_2 \Rightarrow E_1 + E_2} \quad (78)$$

*Comments:*

- (67)  $VE$  is determined by  $B$  and  $valdesc$ .
- (68)–(70) The type functions in  $TE$  may be chosen to achieve the sharing hypothesis of rule 85 or the enrichment conditions of rules 60 and 95. In particular, the type names in  $TE$  in rule 70 need not be new. Also, in rule 68 the type functions in  $TE$  may admit equality.
- (71)  $EE$  is determined by  $B$  and  $exdesc$  and contains monotypes only.
- (76) The names in the instances may be chosen to achieve sharing or enrichment conditions.

### Value Descriptions

$$\boxed{C \vdash valdesc \Rightarrow VE}$$

$$\frac{C \vdash ty \Rightarrow \tau \quad \langle C \vdash valdesc \Rightarrow VE \rangle}{C \vdash var : ty \langle \text{and } valdesc \rangle \Rightarrow \{var \mapsto \tau\} \langle + VE \rangle} \quad (79)$$

### Type Descriptions

$$\boxed{C \vdash typdesc \Rightarrow TE}$$

$$\frac{tyvarseq = \alpha^{(k)} \quad \langle C \vdash typdesc \Rightarrow TE \rangle \quad \text{arity } \theta = k}{C \vdash tyvarseq \ tycon \langle \text{and } typdesc \rangle \Rightarrow \{tycon \mapsto (\theta, \{\})\} \langle + TE \rangle} \quad (80)$$

*Comment:* Note that any  $\theta$  of arity  $k$  may be chosen but that the constructor environment in the resulting type structure must be empty. For example, datatype  $s=c$  type  $t$  sharing  $s=t$  is a legal specification, but the type structure bound to  $t$  does not bind any value constructors.

### Datatype Descriptions

$$\boxed{C \vdash datdesc \Rightarrow VE, TE}$$

$$\frac{tyvarseq = \alpha^{(k)} \quad C, \alpha^{(k)}t \vdash conbind \Rightarrow CE \quad \langle C \vdash datdesc \Rightarrow VE, TE \rangle}{C \vdash tyvarseq \ tycon = conbind \langle \text{and } datdesc \rangle \Rightarrow \text{Clos}CE \langle + VE \rangle, \{tycon \mapsto (t, \text{Clos}CE)\} \langle + TE \rangle} \quad (81)$$

### Exception Descriptions

$$\boxed{C \vdash exdesc \Rightarrow EE}$$

$$\frac{\langle C \vdash ty \Rightarrow \tau \quad \text{tyvars}(\tau) = \emptyset \rangle \quad \langle \langle C \vdash exdesc \Rightarrow EE \rangle \rangle}{C \vdash excon \langle \text{of } ty \rangle \langle \langle \text{and } exdesc \rangle \rangle \Rightarrow \{excon \mapsto \text{exn}\} \langle + \{excon \mapsto \tau \rightarrow \text{exn}\} \rangle \langle \langle + EE \rangle \rangle} \quad (82)$$

### Structure Descriptions

$$\boxed{B \vdash strdesc \Rightarrow SE}$$

$$\frac{B \vdash sigexp \Rightarrow S \quad \langle B \vdash strdesc \Rightarrow SE \rangle}{B \vdash strid : sigexp \langle \text{and } strdesc \rangle \Rightarrow \{strid \mapsto S\} \langle + SE \rangle} \quad (83)$$

**Sharing Equations**

$$\boxed{B \vdash \text{shareq} \Rightarrow \{\}}$$

$$\frac{m \text{ of } B(\text{longstrid}_1) = \dots = m \text{ of } B(\text{longstrid}_n)}{B \vdash \text{longstrid}_1 = \dots = \text{longstrid}_n \Rightarrow \{\}} \quad (84)$$

$$\frac{\theta \text{ of } B(\text{longtycon}_1) = \dots = \theta \text{ of } B(\text{longtycon}_n)}{B \vdash \text{type } \text{longtycon}_1 = \dots = \text{longtycon}_n \Rightarrow \{\}} \quad (85)$$

$$\frac{B \vdash \text{shareq}_1 \Rightarrow \{\} \quad B \vdash \text{shareq}_2 \Rightarrow \{\}}{B \vdash \text{shareq}_1 \text{ and } \text{shareq}_2 \Rightarrow \{\}} \quad (86)$$

*Comments:*

(84) By the definition of consistency the premise is weaker than  $B(\text{longstrid}_1) = \dots = B(\text{longstrid}_n)$ . Two different structures with the same name may be thought of as representing different views. The requirement that  $B$  is consistent forces different views to be consistent.

(85) By the definition of consistency the premise is weaker than  $B(\text{longtycon}_1) = \dots = B(\text{longtycon}_n)$ . A type structure with empty constructor environment may have the same type name as one with a non-empty constructor environment; the former could arise from a type description, and the latter from a datatype description. However, the requirement that  $B$  is consistent will prevent two type structures with different non-empty constructor environments from sharing the same type name.

**Functor Specifications**

$$\boxed{B \vdash \text{funspec} \Rightarrow F}$$

$$\frac{B \vdash \text{fundesc} \Rightarrow F}{B \vdash \text{functor } \text{fundesc} \Rightarrow F} \quad (87)$$

$$\overline{B \vdash \quad \Rightarrow \{\}} \quad (88)$$

$$\frac{B \vdash \text{funspec}_1 \Rightarrow F_1 \quad B + F_1 \vdash \text{funspec}_2 \Rightarrow F_2}{B \vdash \text{funspec}_1 \langle ; \rangle \text{funspec}_2 \Rightarrow F_1 + F_2} \quad (89)$$

*Comments:*

(87) The second closure restriction of Section 3.6 can be enforced by replacing the  $B$  in the premise by  $B_0 + G$  of  $B$ .

**Functor Descriptions**

$$\boxed{B \vdash \text{fundesc} \Rightarrow F}$$

$$\frac{B \vdash \text{funsigexp} \Rightarrow \Phi \quad \langle B \vdash \text{fundesc} \Rightarrow F \rangle}{B \vdash \text{funid } \text{funsigexp} \langle \text{and } \text{fundesc} \rangle \Rightarrow \{\text{funid} \mapsto \Phi\} \langle + F \rangle} \quad (90)$$

**Functor Signature Expressions**

$$\boxed{B \vdash \text{funsigexp} \Rightarrow \Phi}$$

$$\frac{B \vdash \text{sigexp} \Rightarrow S \quad (N)S \text{ principal in } B \quad B \oplus \{\text{strid} \mapsto S\} \vdash \text{sigexp}' \Rightarrow S' \quad (N')S' \text{ principal in } B \oplus \{\text{strid} \mapsto S\}}{B \vdash (\text{strid} : \text{sigexp}) : \text{sigexp}' \Rightarrow (N)(S, (N')S')} \quad (91)$$

**Functor Declarations**

$$\boxed{B \vdash \text{fundec} \Rightarrow F}$$

$$\frac{B \vdash \text{funbind} \Rightarrow F}{B \vdash \text{functor funbind} \Rightarrow F} \quad (92)$$

$$\overline{B \vdash \quad \Rightarrow \{\}} \quad (93)$$

$$\frac{B \vdash \text{fundec}_1 \Rightarrow F_1 \quad B + F_1 \vdash \text{fundec}_2 \Rightarrow F_2}{B \vdash \text{fundec}_1 \langle ; \rangle \text{fundec}_2 \Rightarrow F_1 + F_2} \quad (94)$$

*Comments:*

(92) The third closure restriction of Section 3.6 can be enforced by replacing the  $B$  in the premise by  $B_0 + (G \text{ of } B) + (F \text{ of } B)$ .

**Functor Bindings**

$$\boxed{B \vdash \text{funbind} \Rightarrow F}$$

$$\frac{B \vdash \text{sigexp} \Rightarrow S \quad (N)S \text{ principal in } B \quad B \oplus \{\text{strid} \mapsto S\} \vdash \text{strex} \Rightarrow S' \quad \langle B \oplus \{\text{strid} \mapsto S\} \vdash \text{sigexp}' \Rightarrow S'', S' \succ S'' \rangle \quad N' = \text{names } S' \setminus ((N \text{ of } B) \cup N) \quad \langle \langle B \vdash \text{funbind} \Rightarrow F \rangle \rangle}{B \vdash \text{funid} (\text{strid} : \text{sigexp}) \langle : \text{sigexp}' \rangle = \text{strex} \langle \langle \text{and funbind} \rangle \rangle \Rightarrow \{\text{funid} \mapsto (N)(S, (N')S'(\prime))\} \langle \langle + F \rangle \rangle} \quad (95)$$

*Comment:* Here  $(N)S$  is required to be principal so as to be as general as possible given the sharing constraints in  $\text{sigexp}$ . Since  $\oplus$  is used, any structure name  $m$  and type name  $t$  in  $S$  acts like a constant in the functor body; in particular, it ensures that further names generated during elaboration of the body are distinct from  $m$  and  $t$ . The set  $N'$  is chosen such that every name free in  $(N)S$  or  $(N)(S, (N')S')$  is free in  $B$ .

**Top-level Declarations**

$$\boxed{B \vdash \text{topdec} \Rightarrow B'}$$

$$\frac{B \vdash \text{strdec} \Rightarrow E}{B \vdash \text{strdec} \Rightarrow (\text{names } E, E) \text{ in Basis}} \quad (96)$$

$$\frac{B \vdash \text{sigdec} \Rightarrow G}{B \vdash \text{sigdec} \Rightarrow (\text{names } G, G) \text{ in Basis}} \quad (97)$$

$$\frac{B \vdash \text{fundec} \Rightarrow F}{B \vdash \text{fundec} \Rightarrow (\text{names } F, F) \text{ in Basis}} \quad (98)$$

## 5.14 Functor Signature Matching

As pointed out in Section 3.4 on the grammar for Modules, there is no phrase class whose elaboration requires matching one functor signature to another functor signature. But a precise definition of this matching is needed, since a functor  $g$  may only be separately compiled in the presence of specification of any functor  $f$  to which  $g$  refers, and then a real functor  $f$  must match this specification. In the case, then, that  $f$  has been specified by a functor signature

$$\Phi_1 = (N_1)(S_1, (N'_1)S'_1)$$

and that later  $f$  is declared with functor signature

$$\Phi_2 = (N_2)(S_2, (N'_2)S'_2)$$

the following matching rule will be employed:

A functor signature  $\Phi_2 = (N_2)(S_2, (N'_2)S'_2)$  matches another functor signature,  $\Phi_1 = (N_1)(S_1, (N'_1)S'_1)$ , if there exists a realisation  $\varphi$  such that

1.  $(N_1)S_1$  matches  $(N_2)S_2$  via  $\varphi$ , and
2.  $\varphi((N'_2)S'_2)$  matches  $(N'_1)S'_1$ .

The first condition ensures that the real functor signature  $\Phi_2$  for  $f$  requires the argument *strexp* of any application  $f(\text{strexp})$  to have no more sharing, and no more richness, than was predicted by the specified signature  $\Phi_1$ . The second condition ensures that the real functor signature  $\Phi_2$ , instantiated to  $(\varphi S_2, \varphi((N'_2)S'_2))$ , provides in the result of the application  $f(\text{strexp})$  no less sharing, and no less richness, than was predicted by the specified signature  $\Phi_1$ .

## 6 Dynamic Semantics for the Core

### 6.1 Reduced Syntax

Since types are fully dealt with in the static semantics, the dynamic semantics ignores them. The Core syntax is therefore reduced by the following transformations, for the purpose of the dynamic semantics:

- All explicit type ascriptions “: *ty*” are omitted, and qualifications “of *ty*” are omitted from exception bindings.
- Any declaration of the form “type *typbind*” or “datatype *datbind*” is replaced by the empty declaration.
- A declaration of the form “abstype *datbind* with *dec* end” is replaced by “*dec*”.
- The Core phrase classes *typbind*, *datbind*, *conbind*, *ty* and *tyrow* are omitted.

### 6.2 Simple Objects

All objects in the dynamic semantics are built from identifier classes together with the simple object classes shown (with the variables which range over them) in Figure 12.

$a$	$\in$	Addr	addresses
$en$	$\in$	ExName	exception names
$b$	$\in$	BasVal	basic values
		{FAIL}	failure

Figure 12: Simple Semantic Objects

Addr and ExName are infinite sets. BasVal is described below. FAIL is the result of a failing attempt to match a value and a pattern. Thus FAIL is neither a value nor an exception, but simply a semantic object used in the rules to express operationally how matching proceeds.

Exception constructors evaluate to exception names, unlike value constructors which simply evaluate to themselves. This is to accommodate the generative nature of exception bindings; each evaluation of a declaration of an exception constructor binds it to a new unique name.

$$\begin{aligned}
v &\in \text{Val} = \{:=\} \cup \text{BasVal} \cup \text{Con} \cup (\text{Con} \times \text{Val}) \cup \\
&\quad \text{ExVal} \cup \text{Record} \cup \text{Addr} \cup \text{Closure} \\
r &\in \text{Record} = \text{Lab} \xrightarrow{\text{fin}} \text{Val} \\
e &\in \text{ExVal} = \text{ExName} \cup (\text{ExName} \times \text{Val}) \\
[e] \text{ or } p &\in \text{Pack} = \text{ExVal} \\
(\text{match}, E, VE) &\in \text{Closure} = \text{Match} \times \text{Env} \times \text{VarEnv} \\
\text{mem} &\in \text{Mem} = \text{Addr} \xrightarrow{\text{fin}} \text{Val} \\
\text{ens} &\in \text{ExNameSet} = \text{Fin}(\text{ExName}) \\
(\text{mem}, \text{ens}) \text{ or } s &\in \text{State} = \text{Mem} \times \text{ExNameSet} \\
(SE, VE, EE) \text{ or } E &\in \text{Env} = \text{StrEnv} \times \text{VarEnv} \times \text{ExConEnv} \\
SE &\in \text{StrEnv} = \text{StrId} \xrightarrow{\text{fin}} \text{Env} \\
VE &\in \text{VarEnv} = \text{Var} \xrightarrow{\text{fin}} \text{Val} \\
EE &\in \text{ExConEnv} = \text{ExCon} \xrightarrow{\text{fin}} \text{ExName}
\end{aligned}$$

Figure 13: Compound Semantic Objects

### 6.3 Compound Objects

The compound objects for the dynamic semantics are shown in Figure 13. Many conventions and notations are adopted as in the static semantics; in particular projection, injection and modification all retain their meaning. We generally omit the injection functions taking  $\text{Con}$ ,  $\text{Con} \times \text{Val}$  etc into  $\text{Val}$ . For records  $r \in \text{Record}$  however, we write this injection explicitly as “in  $\text{Val}$ ”; this accords with the fact that there is a separate phrase class  $\text{ExpRow}$ , whose members evaluate to records.

We take  $\cup$  to mean disjoint union over semantic object classes. We also understand all the defined object classes to be disjoint. A particular case deserves mention;  $\text{ExVal}$  and  $\text{Pack}$  (exception values and packets) are isomorphic classes, but the latter class corresponds to exceptions which have been raised, and therefore has different semantic significance from the former, which is just a subclass of values.

Although the same names, e.g.  $E$  for an environment, are used as in the static semantics, the objects denoted are different. This need cause no confusion since the static and dynamic semantics are presented separately. An important point is that structure names  $m$  have no significance at all in the dynamic semantics; this explains why the object class  $\text{Str} = \text{StrName} \times \text{Env}$  is absent here – for the dynamic semantics the concepts *structure* and *environment* coincide.



## 6.4 Basic Values

The basic values in `BasVal` are the values bound to predefined variables. These values are denoted by the identifiers to which they are bound in the initial dynamic basis (see Appendix D), and are as follows:

```
abs floor real sqrt sin cos arctan exp ln
size chr ord explode implode div mod
~ / * + - = <> < > <= >=
std_in std_out open_in open_out close_in close_out
input output lookahead end_of_stream
```

The meaning of basic values (almost all of which are functions) is represented by the function

$$\text{APPLY} : \text{BasVal} \times \text{Val} \rightarrow \text{Val} \cup \text{Pack}$$

which is detailed in Appendix D.

## 6.5 Basic Exceptions

A subset `BasExName`  $\subset$  `ExName` of the exception names are bound to predefined exception constructors. These names are denoted by the identifiers to which they are bound in the initial dynamic basis (see Appendix D), and are as follows:

```
Ord Chr Div Mod Quot Prod
Sum Diff Floor Sqrt Exp Ln
Io Match Bind Interrupt
```

The exceptions on the first two lines are raised by corresponding basic functions, where `/ * + -` correspond respectively to `Quot Prod Sum Diff`. The details are given in Appendix D. The exception `Io(s)`, where `s` is a string, is raised by certain of the basic input/output functions, as detailed in Appendix D. The exceptions `Match` and `Bind` are raised upon failure of pattern-matching in evaluating a function `fn match` or a `valbind`, as detailed in the rules to follow. Finally, `Interrupt` is raised by external intervention.

Recall from Section 4.11 that in the context `fn match`, the `match` must be irredundant and exhaustive and that the compiler should flag the `match` if it violates these restrictions. The exception `Match` can only be raised for a `match` which is not exhaustive, and has therefore been flagged by the compiler.

For each value binding `pat = exp` the compiler must issue a report (but still compile) if *either* `pat` is not exhaustive *or* `pat` contains no variable. This will (on both counts) detect a mistaken declaration like `val nil = exp` in which the user expects to declare a new variable `nil` (whereas the language dictates that `nil` is here a constant pattern, so no variable gets declared). However, these warnings should not be given when the binding is a component of a top-level declaration `val valbind`; e.g. `val x :: l = exp1 and y = exp2` is not faulted by the compiler at top level, but may of course generate a `Bind` exception.

## 6.6 Closures

The informal understanding of a *closure*  $(match, E, VE)$  is as follows: when the closure is applied to a value  $v$ ,  $match$  will be evaluated against  $v$ , in the environment  $E$  modified in a special sense by  $VE$ . The domain  $\text{Dom } VE$  of this third component contains those function identifiers to be treated recursively in the evaluation. To achieve this effect, the evaluation of  $match$  will take place not in  $E + VE$  but in  $E + \text{Rec } VE$ , where

$$\text{Rec} : \text{VarEnv} \rightarrow \text{VarEnv}$$

is defined as follows:

- $\text{Dom}(\text{Rec } VE) = \text{Dom } VE$
- If  $VE(var) \notin \text{Closure}$ , then  $(\text{Rec } VE)(var) = VE(var)$
- If  $VE(var) = (match', E', VE')$  then  $(\text{Rec } VE)(var) = (match', E', VE)$

The effect is that, before application of  $(match, E, VE)$  to  $v$ , the closure values in  $\text{Ran } VE$  are “unrolled” once, to prepare for their possible recursive application during the evaluation of  $match$  upon  $v$ .

This device is adopted to ensure that all semantic objects are finite (by controlling the unrolling of recursion). The operator  $\text{Rec}$  is invoked in just two places in the semantic rules: in the rule for recursive value bindings of the form “*rec valbind*”, and in the rule for evaluating an application expression “*exp atexp*” in the case that  $exp$  evaluates to a closure.

## 6.7 Inference Rules

The semantic rules allow sentences of the form

$$s, A \vdash \textit{phrase} \Rightarrow A', s'$$

to be inferred, where  $A$  is usually an environment,  $A'$  is some semantic object and  $s, s'$  are the states before and after the evaluation represented by the sentence. Some hypotheses in rules are not of this form; they are called *side-conditions*. The convention for options is the same as for the Core static semantics.

In most rules the states  $s$  and  $s'$  are omitted from sentences; they are only included for those rules which are directly concerned with the state – either referring to its contents or changing it. When omitted, the convention for restoring them is as follows. If the rule is presented in the form

$$\frac{A_1 \vdash \textit{phrase}_1 \Rightarrow A'_1 \quad A_2 \vdash \textit{phrase}_2 \Rightarrow A'_2 \quad \dots \quad \dots \quad A_n \vdash \textit{phrase}_n \Rightarrow A'_n}{A \vdash \textit{phrase} \Rightarrow A'}$$

then the full form is intended to be

$$\frac{s_0, A_1 \vdash \textit{phrase}_1 \Rightarrow A'_1, s_1 \quad s_1, A_2 \vdash \textit{phrase}_2 \Rightarrow A'_2, s_2 \quad \dots \quad \dots \quad s_{n-1}, A_n \vdash \textit{phrase}_n \Rightarrow A'_n, s_n}{s_0, A \vdash \textit{phrase} \Rightarrow A', s_n}$$

(Any side-conditions are left unaltered). Thus the left-to-right order of the hypotheses indicates the order of evaluation. Note that in the case  $n = 0$ , when there are no hypotheses (except possibly side-conditions), we have  $s_n = s_0$ ; this implies that the rule causes no side effect. The convention is called the *state convention*, and must be applied to each version of a rule obtained by inclusion or omission of its options.

A second convention, the *exception convention*, is adopted to deal with the propagation of exception packets  $p$ . For each rule whose full form (ignoring side-conditions) is

$$\frac{s_1, A_1 \vdash \textit{phrase}_1 \Rightarrow A'_1, s'_1 \quad \dots \quad s_n, A_n \vdash \textit{phrase}_n \Rightarrow A'_n, s'_n}{s, A \vdash \textit{phrase} \Rightarrow A', s'}$$

and for each  $k$ ,  $1 \leq k \leq n$ , for which the result  $A'_k$  is not a packet  $p$ , an extra rule is added of the form

$$\frac{s_1, A_1 \vdash \textit{phrase}_1 \Rightarrow A'_1, s'_1 \quad \dots \quad s_k, A_k \vdash \textit{phrase}_k \Rightarrow p', s'}{s, A \vdash \textit{phrase} \Rightarrow p', s'}$$

where  $p'$  does not occur in the original rule.<sup>1</sup> This indicates that evaluation of phrases in the hypothesis terminates with the first whose result is a packet (other than one already treated in the rule), and this packet is the result of the phrase in the conclusion.

A third convention is that we allow compound variables (variables built from the variables in Figure 13 and the symbol “/”) to range over unions of semantic objects. For instance the compound variable  $v/p$  ranges over  $\text{Val} \cup \text{Pack}$ . We also allow  $x/\text{FAIL}$  to range over  $X/\text{FAIL}$  where  $x$  ranges over  $X$ ; furthermore, we extend environment modification to allow for failure as follows:

$$VE + \text{FAIL} = \text{FAIL}.$$

## Atomic Expressions

$$\boxed{E \vdash \textit{atexp} \Rightarrow v/p}$$

$$\frac{E(\textit{longvar}) = v}{E \vdash \textit{longvar} \Rightarrow v} \quad (99)$$

<sup>1</sup>There is one exception to the exception convention; no extra rule is added for rule 114 which deals with handlers, since a handler is the only means by which propagation of an exception can be arrested.

$$\frac{\text{longcon} = \text{strid}_1 \dots \text{strid}_k . \text{con}}{E \vdash \text{longcon} \Rightarrow \text{con}} \quad (100)$$

$$\frac{E(\text{longexcon}) = \text{en}}{E \vdash \text{longexcon} \Rightarrow \text{en}} \quad (101)$$

$$\frac{\langle E \vdash \text{exprow} \Rightarrow r \rangle}{E \vdash \{ \langle \text{exprow} \rangle \} \Rightarrow \{ \} \langle + r \rangle \text{ in Val}} \quad (102)$$

$$\frac{E \vdash \text{dec} \Rightarrow E' \quad E + E' \vdash \text{exp} \Rightarrow v}{E \vdash \text{let dec in exp end} \Rightarrow v} \quad (103)$$

$$\frac{E \vdash \text{exp} \Rightarrow v}{E \vdash ( \text{exp} ) \Rightarrow v} \quad (104)$$

*Comments:*

(100) Value constructors denote themselves.

(101) Exception constructors are looked up in the exception environment component of  $E$ .

## Expression Rows

$$\boxed{E \vdash \text{exprow} \Rightarrow r/p}$$

$$\frac{E \vdash \text{exp} \Rightarrow v \quad \langle E \vdash \text{exprow} \Rightarrow r \rangle}{E \vdash \text{lab} = \text{exp} \langle , \text{exprow} \rangle \Rightarrow \{ \text{lab} \mapsto v \} \langle + r \rangle} \quad (105)$$

*Comment:* We may think of components as being evaluated from left to right, because of the state and exception conventions.

## Expressions

$$\boxed{E \vdash \text{exp} \Rightarrow v/p}$$

$$\frac{E \vdash \text{atexp} \Rightarrow v}{E \vdash \text{atexp} \Rightarrow v} \quad (106)$$

$$\frac{E \vdash \text{exp} \Rightarrow \text{con} \quad \text{con} \neq \text{ref} \quad E \vdash \text{atexp} \Rightarrow v}{E \vdash \text{exp atexp} \Rightarrow (\text{con}, v)} \quad (107)$$

$$\frac{E \vdash \text{exp} \Rightarrow \text{en} \quad E \vdash \text{atexp} \Rightarrow v}{E \vdash \text{exp atexp} \Rightarrow (\text{en}, v)} \quad (108)$$

$$\frac{s, E \vdash \text{exp} \Rightarrow \text{ref}, s' \quad s', E \vdash \text{atexp} \Rightarrow v, s'' \quad a \notin \text{Dom}(\text{mem of } s'')}{s, E \vdash \text{exp atexp} \Rightarrow a, s'' + \{ a \mapsto v \}} \quad (109)$$

$$\frac{s, E \vdash \text{exp} \Rightarrow :=, s' \quad s', E \vdash \text{atexp} \Rightarrow \{ 1 \mapsto a, 2 \mapsto v \}, s''}{s, E \vdash \text{exp atexp} \Rightarrow \{ \} \text{ in Val}, s'' + \{ a \mapsto v \}} \quad (110)$$

$$\frac{E \vdash \text{exp} \Rightarrow b \quad E \vdash \text{atexp} \Rightarrow v \quad \text{APPLY}(b, v) = v'}{E \vdash \text{exp atexp} \Rightarrow v'} \quad (111)$$

$$\frac{E \vdash \text{exp} \Rightarrow (\text{match}, E', VE) \quad E \vdash \text{atexp} \Rightarrow v \quad E' + \text{Rec } VE, v \vdash \text{match} \Rightarrow v'}{E \vdash \text{exp atexp} \Rightarrow v'} \quad (112)$$

$$\frac{E \vdash \text{exp} \Rightarrow (\text{match}, E', VE) \quad E \vdash \text{atexp} \Rightarrow v \quad E' + \text{Rec } VE, v \vdash \text{match} \Rightarrow \text{FAIL}}{E \vdash \text{exp atexp} \Rightarrow [\text{Match}]} \quad (113)$$

$$\frac{E \vdash \text{exp} \Rightarrow v}{E \vdash \text{exp handle match} \Rightarrow v} \quad (114)$$

$$\frac{E \vdash \text{exp} \Rightarrow [e] \quad E, e \vdash \text{match} \Rightarrow v}{E \vdash \text{exp handle match} \Rightarrow v} \quad (115)$$

$$\frac{E \vdash \text{exp} \Rightarrow [e] \quad E, e \vdash \text{match} \Rightarrow \text{FAIL}}{E \vdash \text{exp handle match} \Rightarrow [e]} \quad (116)$$

$$\frac{E \vdash \text{exp} \Rightarrow e}{E \vdash \text{raise exp} \Rightarrow [e]} \quad (117)$$

$$\frac{}{E \vdash \text{fn match} \Rightarrow (\text{match}, E, \{\})} \quad (118)$$

*Comments:*

(109) The side condition ensures that a new address is chosen. There are no rules concerning disposal of inaccessible addresses (“garbage collection”).

(107)–(113) Note that none of the rules for function application has a premise in which the operator evaluates to a constructed value, a record or an address. This is because we are interested in the evaluation of well-typed programs only, and in such programs *exp* will always have a functional type, so *v* will be either a closure, a constructor, a basic value or *:=*.

(114) This is the only rule to which the exception convention does not apply. If the operator evaluates to a packet then rule 115 must be used.

(116) Packets that are not handled by the *match* propagate.

(118) The third component of the closure is empty because the *match* does not introduce new recursively defined values.

**Matches**

$$\boxed{E, v \vdash match \Rightarrow v'/p/FAIL}$$

$$\frac{E, v \vdash mrule \Rightarrow v'}{E, v \vdash mrule \langle | match \rangle \Rightarrow v'} \quad (119)$$

$$\frac{E, v \vdash mrule \Rightarrow FAIL}{E, v \vdash mrule \Rightarrow FAIL} \quad (120)$$

$$\frac{E, v \vdash mrule \Rightarrow FAIL \quad E, v \vdash match \Rightarrow v'/FAIL}{E \vdash mrule | match \Rightarrow v'/FAIL} \quad (121)$$

*Comment:* A value  $v$  occurs on the left of the turnstile, in evaluating a *match*. We may think of a *match* as being evaluated *against* a value; similarly, we may think of a pattern as being evaluated *against* a value. Alternative match rules are tried from left to right.

**Match Rules**

$$\boxed{E, v \vdash mrule \Rightarrow v'/p/FAIL}$$

$$\frac{E, v \vdash pat \Rightarrow VE \quad E + VE \vdash exp \Rightarrow v'}{E, v \vdash pat \Rightarrow exp \Rightarrow v'} \quad (122)$$

$$\frac{E, v \vdash pat \Rightarrow FAIL}{E, v \vdash pat \Rightarrow exp \Rightarrow FAIL} \quad (123)$$

**Declarations**

$$\boxed{E \vdash dec \Rightarrow E'/p}$$

$$\frac{E \vdash valbind \Rightarrow VE}{E \vdash val valbind \Rightarrow VE \text{ in Env}} \quad (124)$$

$$\frac{E \vdash exbind \Rightarrow EE}{E \vdash exception exbind \Rightarrow EE \text{ in Env}} \quad (125)$$

$$\frac{E \vdash dec_1 \Rightarrow E_1 \quad E + E_1 \vdash dec_2 \Rightarrow E_2}{E \vdash local dec_1 \text{ in } dec_2 \text{ end} \Rightarrow E_2} \quad (126)$$

$$\frac{E(longstrid_1) = E_1 \quad \dots \quad E(longstrid_k) = E_k}{E \vdash open longstrid_1 \dots longstrid_n \Rightarrow E_1 + \dots + E_k} \quad (127)$$

$$\frac{}{E \vdash \{ \} \text{ in Env}} \quad (128)$$

$$\frac{E \vdash dec_1 \Rightarrow E_1 \quad E + E_1 \vdash dec_2 \Rightarrow E_2}{E \vdash dec_1 \langle ; \rangle dec_2 \Rightarrow E_1 + E_2} \quad (129)$$

## Value Bindings

$$\boxed{E \vdash \text{valbind} \Rightarrow VE/p}$$

$$\frac{E \vdash \text{exp} \Rightarrow v \quad E, v \vdash \text{pat} \Rightarrow VE \quad \langle E \vdash \text{valbind} \Rightarrow VE' \rangle}{E \vdash \text{pat} = \text{exp} \langle \text{and valbind} \rangle \Rightarrow VE \langle + VE' \rangle} \quad (130)$$

$$\frac{E \vdash \text{exp} \Rightarrow v \quad E, v \vdash \text{pat} \Rightarrow \text{FAIL}}{E \vdash \text{pat} = \text{exp} \langle \text{and valbind} \rangle \Rightarrow [\text{Bind}]} \quad (131)$$

$$\frac{E \vdash \text{valbind} \Rightarrow VE}{E \vdash \text{rec valbind} \Rightarrow \text{Rec } VE} \quad (132)$$

## Exception Bindings

$$\boxed{E \vdash \text{exbind} \Rightarrow EE/p}$$

$$\frac{en \notin \text{ens of } s \quad s' = s + \{en\} \quad \langle s', E \vdash \text{exbind} \Rightarrow EE, s'' \rangle}{s, E \vdash \text{excon} \langle \text{and exbind} \rangle \Rightarrow \{\text{excon} \mapsto en\} \langle + EE \rangle, s' \langle ' \rangle} \quad (133)$$

$$\frac{E(\text{longexcon}) = en \quad \langle E \vdash \text{exbind} \Rightarrow EE \rangle}{E \vdash \text{excon} = \text{longexcon} \langle \text{and exbind} \rangle \Rightarrow \{\text{excon} \mapsto en\} \langle + EE \rangle} \quad (134)$$

Comments:

(133) The two side conditions ensure that a new exception name is generated and recorded as “used” in subsequent states.

## Atomic Patterns

$$\boxed{E, v \vdash \text{atpat} \Rightarrow VE/\text{FAIL}}$$

$$\frac{}{E, v \vdash \_ \Rightarrow \{ \}} \quad (135)$$

$$\frac{}{E, v \vdash \text{var} \Rightarrow \{\text{var} \mapsto v\}} \quad (136)$$

$$\frac{\text{longcon} = \text{strid}_1 \dots \text{strid}_k \text{.con} \quad v = \text{con}}{E, v \vdash \text{longcon} \Rightarrow \{ \}} \quad (137)$$

$$\frac{\text{longcon} = \text{strid}_1 \dots \text{strid}_k \text{.con} \quad v \neq \text{con}}{E, v \vdash \text{longcon} \Rightarrow \text{FAIL}} \quad (138)$$

$$\frac{E(\text{longexcon}) = v}{E, v \vdash \text{longexcon} \Rightarrow \{ \}} \quad (139)$$

$$\frac{E(\text{longexcon}) \neq v}{E, v \vdash \text{longexcon} \Rightarrow \text{FAIL}} \quad (140)$$

$$\frac{v = \{ \} \langle +r \rangle \text{ in Val} \quad \langle E, r \vdash \text{patrow} \Rightarrow VE/\text{FAIL} \rangle}{E, v \vdash \{ \langle \text{patrow} \rangle \} \Rightarrow \{ \} \langle +VE/\text{FAIL} \rangle} \quad (141)$$

$$\frac{E, v \vdash pat \Rightarrow VE}{E, v \vdash (pat) \Rightarrow VE} \quad (142)$$

*Comments:*

(138),(140) Any evaluation resulting in FAIL must do so because rule 138, rule 140, rule 148, or rule 150 has been applied.

### Pattern Rows

$$\boxed{E, r \vdash patrow \Rightarrow VE/FAIL}$$

$$\overline{E, r \vdash \dots \Rightarrow \{\}} \quad (143)$$

$$\frac{E, r(lab) \vdash pat \Rightarrow FAIL}{E, r \vdash lab = pat \langle , patrow \rangle \Rightarrow FAIL} \quad (144)$$

$$\frac{E, r(lab) \vdash pat \Rightarrow VE \quad \langle E, r \vdash patrow \Rightarrow VE'/FAIL \rangle}{E, r \vdash lab = pat \langle , patrow \rangle \Rightarrow VE(+ VE'/FAIL)} \quad (145)$$

*Comments:*

(144),(145) For well-typed programs *lab* will be in the domain of *r*.

### Patterns

$$\boxed{E, v \vdash pat \Rightarrow VE/FAIL}$$

$$\frac{E, v \vdash atpat \Rightarrow VE/FAIL}{E, v \vdash atpat \Rightarrow VE/FAIL} \quad (146)$$

$$\frac{\begin{array}{l} longcon = strid_1 \dots strid_k . con \neq \mathbf{ref} \quad v = (con, v') \\ E, v' \vdash atpat \Rightarrow VE/FAIL \end{array}}{E, v \vdash longcon atpat \Rightarrow VE/FAIL} \quad (147)$$

$$\frac{longcon = strid_1 \dots strid_k . con \neq \mathbf{ref} \quad v \notin \{con\} \times \mathbf{Val}}{E, v \vdash longcon atpat \Rightarrow FAIL} \quad (148)$$

$$\frac{\begin{array}{l} E(longexcon) = en \quad v = (en, v') \\ E, v' \vdash atpat \Rightarrow VE/FAIL \end{array}}{E, v \vdash longexcon atpat \Rightarrow VE/FAIL} \quad (149)$$

$$\frac{E(longexcon) = en \quad v \notin \{en\} \times \mathbf{Val}}{E, v \vdash longexcon atpat \Rightarrow FAIL} \quad (150)$$

$$\frac{s(a) = v \quad s, E, v \vdash atpat \Rightarrow VE/FAIL, s}{s, E, a \vdash \mathbf{ref} atpat \Rightarrow VE/FAIL, s} \quad (151)$$

$$\frac{E, v \vdash pat \Rightarrow VE/FAIL}{E, v \vdash var\langle : ty \rangle \mathbf{as} pat \Rightarrow \{var \mapsto v\} + VE/FAIL} \quad (152)$$

*Comments:*



(148),(150) Any evaluation resulting in FAIL must do so because rule 138, rule 140, rule 148, or rule 150 has been applied.

## 7 Dynamic Semantics for Modules

### 7.1 Reduced Syntax

Since signature expressions are mostly dealt with in the static semantics, the dynamic semantics need only take limited account of them. Unlike types, it cannot ignore them completely; the reason is that an explicit signature ascription plays the role of restricting the “view” of a structure - that is, restricting the domains of its component environments. However, the types and the sharing properties of structures and signatures are irrelevant to dynamic evaluation; the syntax is therefore reduced by the following transformations (in addition to those for the Core), for the purpose of the dynamic semantics of Modules:

- Qualifications “of *ty*” are omitted from exception descriptions.
- Any specification of the form “**type** *tydesc*”, “**eqtype** *tydesc*”, “**datatype** *datdesc*” or “**sharing** *shareq*” is replaced by the empty specification.
- The Modules phrase classes *tydesc*, *datdesc* and *shareq* are omitted.

### 7.2 Compound Objects

The compound objects for the Modules dynamic semantics, extra to those for the Core dynamic semantics, are shown in Figure 14. An *interface*  $I \in \text{Int}$  represents

$$\begin{aligned}
 (\text{strid} : I, \text{strexpr}(\cdot : I'), B) &\in \text{FunctorClosure} \\
 &= (\text{StrId} \times \text{Int}) \times (\text{StrExp}(\times \text{Int})) \times \text{Basis} \\
 (IE, \text{vars}, \text{excons}) \text{ or } I &\in \text{Int} = \text{IntEnv} \times \text{Fin}(\text{Var}) \times \text{Fin}(\text{ExCon}) \\
 IE &\in \text{IntEnv} = \text{StrId} \xrightarrow{\text{fn}} \text{Int} \\
 G &\in \text{SigEnv} = \text{SigId} \xrightarrow{\text{fn}} \text{Int} \\
 F &\in \text{FunEnv} = \text{FunId} \xrightarrow{\text{fn}} \text{FunctorClosure} \\
 (F, G, E) \text{ or } B &\in \text{Basis} = \text{FunEnv} \times \text{SigEnv} \times \text{Env} \\
 (G, IE) \text{ or } IB &\in \text{IntBasis} = \text{SigEnv} \times \text{IntEnv}
 \end{aligned}$$

Figure 14: Compound Semantic Objects

a “view” of a structure. Specifications and signature expressions will evaluate to interfaces; moreover, during the evaluation of a specification or signature expression, structures (to which a specification or signature expression may refer via “open”) are represented only by their interfaces. To extract an interface from a dynamic environment we define the operation

$$\text{Inter} : \text{Env} \rightarrow \text{Int}$$

as follows:

$$\text{Inter}(SE, VE, EE) = (IE, \text{Dom } VE, \text{Dom } EE)$$

where

$$IE = \{strid \mapsto \text{Inter } E ; SE(strid) = E\} .$$

An *interface basis*  $IB = (G, IE)$  is that part of a basis needed to evaluate signature expressions and specifications. The function  $\text{Inter}$  is extended to create an interface basis from a basis  $B$  as follows:

$$\text{Inter}(F, G, E) = (G, IE \text{ of } (\text{Inter } E))$$

A further operation

$$\downarrow : \text{Env} \times \text{Int} \rightarrow \text{Env}$$

is required, to cut down an environment  $E$  to a given interface  $I$ , representing the effect of an explicit signature ascription. It is defined as follows:

$$(SE, VE, EE) \downarrow (IE, vars, excons) = (SE', VE', EE')$$

where

$$SE' = \{strid \mapsto E \downarrow I ; SE(strid) = E \text{ and } IE(strid) = I\}$$

and (taking  $\downarrow$  now to mean restriction of a function domain)

$$VE' = VE \downarrow vars, EE' = EE \downarrow excons.$$

It is important to note that an interface is also a projection of the *static* value  $\Sigma$  of a signature expression; it is obtained by omitting structure names  $m$  and type environments  $TE$ , and replacing each variable environment  $VE$  and each exception environment  $EE$  by its domain. Thus in an implementation interfaces would naturally be obtained from the static elaboration; we choose to give separate rules here for obtaining them in the dynamic semantics since we wish to maintain our separation of the static and dynamic semantics, for reasons of presentation.

### 7.3 Inference Rules

The semantic rules allow sentences of the form

$$s, A \vdash \text{phrase} \Rightarrow A', s'$$

to be inferred, where  $A$  is either a basis or an interface basis or empty,  $A'$  is some semantic object and  $s, s'$  are the states before and after the evaluation represented by the sentence. Some hypotheses in rules are not of this form; they are called *side-conditions*. The convention for options is the same as for the Core static semantics.

The state and exception conventions are adopted as in the Core dynamic semantics. However, it may be shown that the only Modules phrases whose evaluation may cause a side-effect or generate an exception packet are of the form *strexpr*, *strdec*, *strbind* or *topdec*.

## Structure Expressions

$$\boxed{B \vdash \text{strex} \Rightarrow E/p}$$

$$\frac{B \vdash \text{strdec} \Rightarrow E}{B \vdash \text{struct strdec end} \Rightarrow E} \quad (153)$$

$$\frac{B(\text{longstrid}) = E}{B \vdash \text{longstrid} \Rightarrow E} \quad (154)$$

$$\frac{B(\text{funid}) = (\text{strid} : I, \text{strex}'(\downarrow I'), B') \quad B \vdash \text{strex} \Rightarrow E \quad B' + \{\text{strid} \mapsto E \downarrow I\} \vdash \text{strex}' \Rightarrow E'}{B \vdash \text{funid} (\text{strex}) \Rightarrow E'(\downarrow I')} \quad (155)$$

$$\frac{B \vdash \text{strdec} \Rightarrow E \quad B + E \vdash \text{strex} \Rightarrow E'}{B \vdash \text{let strdec in strex end} \Rightarrow E'} \quad (156)$$

*Comments:*

- (155) Before the evaluation of the functor body  $\text{strex}'$ , the actual argument  $E$  is cut down by the formal parameter interface  $I$ , so that any opening of  $\text{strid}$  resulting from the evaluation of  $\text{strex}'$  will produce no more components than anticipated during the static elaboration.

## Structure-level Declarations

$$\boxed{B \vdash \text{strdec} \Rightarrow E/p}$$

$$\frac{E \text{ of } B \vdash \text{dec} \Rightarrow E}{B \vdash \text{dec} \Rightarrow E} \quad (157)$$

$$\frac{B \vdash \text{strbind} \Rightarrow SE}{B \vdash \text{structure strbind} \Rightarrow SE \text{ in Env}} \quad (158)$$

$$\frac{B \vdash \text{strdec}_1 \Rightarrow E_1 \quad B + E_1 \vdash \text{strdec}_2 \Rightarrow E_2}{B \vdash \text{local strdec}_1 \text{ in strdec}_2 \text{ end} \Rightarrow E_2} \quad (159)$$

$$\overline{B \vdash \quad \Rightarrow \{\}} \text{ in Env} \quad (160)$$

$$\frac{B \vdash \text{strdec}_1 \Rightarrow E_1 \quad B + E_1 \vdash \text{strdec}_2 \Rightarrow E_2}{B \vdash \text{strdec}_1 \langle ; \rangle \text{ strdec}_2 \Rightarrow E_1 + E_2} \quad (161)$$

**Structure Bindings**

$$\boxed{B \vdash \text{strbind} \Rightarrow SE/p}$$

$$\frac{B \vdash \text{strex} \Rightarrow E \quad \langle \text{Inter } B \vdash \text{sigexp} \Rightarrow I \rangle \quad \langle \langle B \vdash \text{strbind} \Rightarrow SE \rangle \rangle}{B \vdash \text{strid} \langle : \text{sigexp} \rangle = \text{strex} \langle \langle \text{and strbind} \rangle \rangle \Rightarrow \{ \text{strid} \mapsto E \langle \downarrow I \rangle \} \langle \langle + SE \rangle \rangle} \quad (162)$$

*Comment:* As in the static semantics, when present, *sigexp* constrains the “view” of the structure. The restriction must be done in the dynamic semantics to ensure that any dynamic opening of the structure produces no more components than anticipated during the static elaboration.

**Signature Expressions**

$$\boxed{IB \vdash \text{sigexp} \Rightarrow I}$$

$$\frac{IB \vdash \text{spec} \Rightarrow I}{IB \vdash \text{sig spec end} \Rightarrow I} \quad (163)$$

$$\frac{IB(\text{sigid}) = I}{IB \vdash \text{sigid} \Rightarrow I} \quad (164)$$

**Signature Declarations**

$$\boxed{IB \vdash \text{sigdec} \Rightarrow G}$$

$$\frac{IB \vdash \text{sigbind} \Rightarrow G}{IB \vdash \text{signature sigbind} \Rightarrow G} \quad (165)$$

$$\overline{IB \vdash \quad \Rightarrow \{ \}} \quad (166)$$

$$\frac{IB \vdash \text{sigdec}_1 \Rightarrow G_1 \quad IB + G_1 \vdash \text{sigdec}_2 \Rightarrow G_2}{IB \vdash \text{sigdec}_1 \langle ; \rangle \text{sigdec}_2 \Rightarrow G_1 + G_2} \quad (167)$$

**Signature Bindings**

$$\boxed{IB \vdash \text{sigbind} \Rightarrow G}$$

$$\frac{IB \vdash \text{sigexp} \Rightarrow I \quad \langle IB \vdash \text{sigbind} \Rightarrow G \rangle}{IB \vdash \text{sigid} = \text{sigexp} \langle \text{and sigbind} \rangle \Rightarrow \{ \text{sigid} \mapsto I \} \langle + G \rangle} \quad (168)$$

**Specifications**

$$\boxed{IB \vdash \text{spec} \Rightarrow I}$$

$$\frac{\vdash \text{valdesc} \Rightarrow \text{vars}}{IB \vdash \text{val valdesc} \Rightarrow \text{vars in Int}} \quad (169)$$

$$\frac{\vdash \text{exdesc} \Rightarrow \text{excons}}{IB \vdash \text{exception exdesc} \Rightarrow \text{excons in Int}} \quad (170)$$

$$\frac{IB \vdash \text{strdesc} \Rightarrow IE}{IB \vdash \text{structure } \text{strdesc} \Rightarrow IE \text{ in Int}} \quad (171)$$

$$\frac{IB \vdash \text{spec}_1 \Rightarrow I_1 \quad IB + IE \text{ of } I_1 \vdash \text{spec}_1 \Rightarrow I_2}{IB \vdash \text{local } \text{spec}_1 \text{ in } \text{spec}_2 \text{ end} \Rightarrow I_2} \quad (172)$$

$$\frac{IB(\text{longstrid}_1) = I_1 \quad \dots \quad IB(\text{longstrid}_n) = I_n}{IB \vdash \text{open } \text{longstrid}_1 \dots \text{longstrid}_n \Rightarrow I_1 + \dots + I_n} \quad (173)$$

$$\frac{IB(\text{sigid}_1) = I_1 \quad \dots \quad IB(\text{sigid}_n) = I_n}{IB \vdash \text{include } \text{sigid}_1 \dots \text{sigid}_n \Rightarrow I_1 + \dots + I_n} \quad (174)$$

$$\frac{}{IB \vdash \quad \Rightarrow \{\} \text{ in Int}} \quad (175)$$

$$\frac{IB \vdash \text{spec}_1 \Rightarrow I_1 \quad IB + IE \text{ of } I_1 \vdash \text{spec}_2 \Rightarrow I_2}{IB \vdash \text{spec}_1 \langle ; \rangle \text{spec}_2 \Rightarrow I_1 + I_2} \quad (176)$$

Comments:

(172),(176) Note that *vars* of  $I_1$  and *excons* of  $I_1$  are not needed for the evaluation of  $\text{spec}_2$ .

### Value Descriptions

$$\boxed{\vdash \text{valdesc} \Rightarrow \text{vars}}$$

$$\frac{\langle \vdash \text{valdesc} \Rightarrow \text{vars} \rangle}{\vdash \text{var } \langle \text{and } \text{valdesc} \rangle \Rightarrow \{\text{var}\} \langle \cup \text{vars} \rangle} \quad (177)$$

### Exception Descriptions

$$\boxed{\vdash \text{exdesc} \Rightarrow \text{excons}}$$

$$\frac{\langle \vdash \text{exdesc} \Rightarrow \text{excons} \rangle}{\vdash \text{excon } \langle \text{exdesc} \rangle \Rightarrow \{\text{excon}\} \langle \cup \text{excons} \rangle} \quad (178)$$

### Structure Descriptions

$$\boxed{IB \vdash \text{strdesc} \Rightarrow IE}$$

$$\frac{IB \vdash \text{sigexp} \Rightarrow I \quad \langle IB \vdash \text{strdesc} \Rightarrow IE \rangle}{IB \vdash \text{strid} : \text{sigexp} \langle \text{and } \text{strdesc} \rangle \Rightarrow \{\text{strid} \mapsto I\} \langle + IE \rangle} \quad (179)$$

### Functor Bindings

$$\boxed{B \vdash \text{funbind} \Rightarrow F}$$

$$\frac{\text{Inter } B \vdash \text{sigexp} \Rightarrow I \quad \langle \text{Inter } B + \{\text{strid} \mapsto I\} \vdash \text{sigexp}' \Rightarrow I' \rangle \quad \langle \langle B \vdash \text{funbind} \Rightarrow F \rangle \rangle}{B \vdash \text{funid } ( \text{strid} : \text{sigexp} ) \langle : \text{sigexp}' \rangle = \text{strexp } \langle \langle \text{and } \text{funbind} \rangle \rangle \Rightarrow \{ \text{funid} \mapsto ( \text{strid} : I, \text{strexp} \langle : I' \rangle, B ) \} \langle \langle + F \rangle \rangle} \quad (180)$$

**Functor Declarations**

$$\boxed{B \vdash \text{fundec} \Rightarrow F}$$

$$\frac{B \vdash \text{funbind} \Rightarrow F}{B \vdash \text{functor funbind} \Rightarrow F} \quad (181)$$

$$\overline{B \vdash \quad \Rightarrow \{\}} \quad (182)$$

$$\frac{B \vdash \text{fundec}_1 \Rightarrow F_1 \quad B + F_1 \vdash \text{fundec}_2 \Rightarrow F_2}{B \vdash \text{fundec}_1 \langle ; \rangle \text{fundec}_2 \Rightarrow F_1 + F_2} \quad (183)$$

**Top-level Declarations**

$$\boxed{B \vdash \text{topdec} \Rightarrow B'/p}$$

$$\frac{B \vdash \text{strdec} \Rightarrow E}{B \vdash \text{strdec} \Rightarrow E \text{ in Basis}} \quad (184)$$

$$\frac{\text{Inter } B \vdash \text{sigdec} \Rightarrow G}{B \vdash \text{sigdec} \Rightarrow G \text{ in Basis}} \quad (185)$$

$$\frac{B \vdash \text{fundec} \Rightarrow F}{B \vdash \text{fundec} \Rightarrow F \text{ in Basis}} \quad (186)$$

## 8 Programs

The phrase class Program of programs is defined as follows

$$program ::= topdec ; \langle program \rangle$$

Hitherto, the semantic rules have not exposed the interactive nature of the language. During an ML session the user can type in a phrase, more precisely a phrase of the form *topdec* as defined in Figure 8, page 14. Upon the following semicolon, the machine will then attempt to parse, elaborate and evaluate the phrase returning either a result or, if any of the phases fail, an error message. The outcome is significant for what the user subsequently types, so we need to answer question such as: if the elaboration of a top-level declaration succeeds, but its evaluation fails, then does the result of the elaboration get recorded in the static basis?

In practice, ML implementations may provide a directive as a form of top-level declaration for including programs from files rather than directly from the terminal. In case a file consists of a sequence of top-level declarations (separated by semicolons) and the machine detects an error in one of these, it is probably sensible to abort the execution of the directive. Rather than introducing a distinction between, say, batch programs and interactive programs, we shall tacitly regard all programs as interactive, and leave to implementors to clarify how the inclusion of files, if provided, affects the updating of the static and dynamic basis. Moreover, we shall focus on elaboration and evaluation and leave the handling of parse errors to implementors (since it naturally depends on the kind of parser being employed). Hence, in this section the *execution* of a program means the combined elaboration and evaluation of the program.

So far, for simplicity, we have used the same notation  $B$  to stand for both a static and a dynamic basis, and this has been possible because we have never needed to discuss static and dynamic semantics at the same time. In giving the semantics of programs, however, let us rename as *StaticBasis* the class of *Basis* defined in the static semantics of modules, Section 5.1, and let us use  $B_{\text{STAT}}$  to range over *StaticBasis*. Similarly, let us rename as *DynamicBasis* the class *Basis* defined in the dynamic semantics of modules, Section 7.2, ranged over by  $B_{\text{DYN}}$ . We now define

$$B \text{ or } (B_{\text{STAT}}, B_{\text{DYN}}) \in \text{Basis} = \text{StaticBasis} \times \text{DynamicBasis}.$$

Further, we shall use  $\vdash_{\text{STAT}}$  for elaboration as defined in Section 5, and  $\vdash_{\text{DYN}}$  for evaluation as defined in Section 7. Then  $\vdash$  will be reserved for the execution of programs, which thus is expressed by a sentence of the form

$$s, B \vdash program \Rightarrow B', s'$$

This may be read as follows: starting in basis  $B$  with state  $s$  the execution of *program* results in a basis  $B'$  and a state  $s'$ .



It must be understood that executing a program never results in an exception. If the evaluation of a *topdec* yield an exception (either because of a **raise** expression or because of external intervention) then the result of executing the program "*topdec ;*" is the original basis together with the state which is in force when the exception is generated. In particular, the exception convention of Section 6.7 is not applicable to the ensuing rules.

We represent the non-elaboration of a top-level declaration by  $\dots \vdash_{\text{STAT}} \text{topdec} \not\Rightarrow$ . (This covers also the case in which a user interrupts the elaboration).

### Programs

$$\boxed{s, B \vdash \text{program} \Rightarrow B', s'}$$

$$\frac{B_{\text{STAT}} \text{ of } B \vdash_{\text{STAT}} \text{topdec} \not\Rightarrow \quad \langle s, B \vdash \text{program} \Rightarrow B', s' \rangle}{s, B \vdash \text{topdec} ; \langle \text{program} \rangle \Rightarrow B\langle' \rangle, s\langle' \rangle} \quad (187)$$

$$\frac{B_{\text{STAT}} \text{ of } B \vdash_{\text{STAT}} \text{topdec} \Rightarrow B_{\text{STAT}}^{(1)} \quad s, B_{\text{DYN}} \text{ of } B \vdash_{\text{DYN}} \text{topdec} \Rightarrow p, s' \quad \langle s', B \vdash \text{program} \Rightarrow B', s'' \rangle}{s, B \vdash \text{topdec} ; \langle \text{program} \rangle \Rightarrow B\langle' \rangle, s'\langle' \rangle} \quad (188)$$

$$\frac{B_{\text{STAT}} \text{ of } B \vdash_{\text{STAT}} \text{topdec} \Rightarrow B_{\text{STAT}}^{(1)} \quad s, B_{\text{DYN}} \text{ of } B \vdash \text{topdec} \Rightarrow B_{\text{DYN}}^{(1)}, s' \quad B' = B \oplus (B_{\text{STAT}}^{(1)}, B_{\text{DYN}}^{(1)}) \quad \langle s', B' \vdash \text{program} \Rightarrow B'', s'' \rangle}{s, B \vdash \text{topdec} ; \langle \text{program} \rangle \Rightarrow B'\langle' \rangle, s'\langle' \rangle} \quad (189)$$

*Comments:*

(187) A failing elaboration has no effect whatever.

(188) An evaluation which yields an exception nullifies the change in the static basis, but does not nullify side-effects on the state which may have occurred before the exception was raised.

## A Appendix: Derived Forms

Several derived grammatical forms are provided in the Core; they are presented in Figures 15, 16 and 17. Each derived form is given with its equivalent form. Thus, each row of the tables should be considered as a rewriting rule

Derived form  $\implies$  Equivalent form

and these rules may be applied repeatedly to a phrase until it is transformed into a phrase of the bare language. See Appendix B for the full Core grammar, including all the derived forms.

In the derived forms for tuples, in terms of records, we use  $\bar{n}$  to mean the ML numeral which stands for the natural number  $n$ .

Note that a new phrase class `FvalBind` of function-value bindings is introduced, accompanied by a new declaration form `fun fvalbind`. The mixed forms `val rec fvalbind`, `val fvalbind` and `fun valbind` are not allowed – though the first form arises during translation into the bare language.

The following notes refer to Figure 17:

- In the equivalent form for a function-value binding, the variables  $var_1, \dots, var_n$  must be chosen not to occur in the derived form. The condition  $m, n \geq 1$  applies.
- In the two forms involving `withtype`, the identifiers bound by `datbind` and by `typbind` must be distinct. Then the transformed binding `datbind'` in the equivalent form is obtained from `datbind` by expanding out all the definitions made by `typbind`. More precisely, if `typbind` is

$$tyvarseq_1 \ tycon_1 = ty_1 \ \text{and} \ \dots \ \text{and} \ tyvarseq_n \ tycon_n = ty_n$$

then `datbind'` is the result of simultaneous replacement (in `datbind`) of every type expression  $tyseq_i \ tycon_i$  ( $1 \leq i \leq n$ ) by the corresponding defining expression

$$ty_i\{tyseq_i/tyvarseq_i\}$$

- The abbreviation of `val it = exp` to `exp` is only permitted at top-level, i.e. as a `program`.

Figure 18 shows derived forms for functors. They allow functors to take, say, a single type or value as a parameter, in cases where it would seem clumsy to “wrap up” the argument as a structure expression. These forms are currently more experimental than the bare syntax of modules, but we recommend implementors to include them so that they can be tested in practice. In the derived forms for functor bindings and functor signature expressions, `strid` is a new structure identifier and the form of `sigexp'` depends on the form of `sigexp` as follows. If `sigexp` is simply a signature identifier `sigid`, then `sigexp'` is also `sigid`; otherwise `sigexp` must take the form `sig spec1 end`, and then `sigexp'` is `sig local open strid in spec1 end end`.

Derived Form	Equivalent Form	
<b>Expressions <math>exp</math></b>		
$()$	$\{ \}$	
$(exp_1, \dots, exp_n)$	$\{1=exp_1, \dots, \bar{n}=exp_n\}$	$(n \geq 2)$
$\# lab$	$fn \{lab=var, \dots\} \Rightarrow var$	$(var \text{ new})$
$case\ exp\ of\ match$	$(fn\ match)(exp)$	
$if\ exp\ then\ exp_1\ else\ exp_2$	$case\ exp\ of\ true \Rightarrow exp_1$ $\quad   \text{ false} \Rightarrow exp_2$	
$exp_1\ or\ else\ exp_2$	$if\ exp_1\ then\ true\ else\ exp_2$	
$exp_1\ and\ also\ exp_2$	$if\ exp_1\ then\ exp_2\ else\ false$	
$(exp_1 ; \dots ; exp_n ; exp)$	$case\ exp_1\ of\ (-) \Rightarrow$ $\quad \dots$ $case\ exp_n\ of\ (-) \Rightarrow exp$	$(n \geq 1)$
$let\ dec\ in$ $\quad exp_1 ; \dots ; exp_n\ end$	$let\ dec\ in$ $\quad (exp_1 ; \dots ; exp_n)\ end$	$(n \geq 2)$
$while\ exp_1\ do\ exp_2$	$let\ val\ rec\ var = fn\ () \Rightarrow$ $\quad if\ exp_1\ then\ (exp_2 ; var())\ else\ ()$ $\quad in\ var()\ end$	$(var \text{ new})$
$[exp_1, \dots, exp_n]$	$exp_1 :: \dots :: exp_n :: nil$	$(n \geq 0)$

Figure 15: Derived forms of Expressions

Derived Form	Equivalent Form	
<b>Patterns <math>pat</math></b>		
$()$	$\{ \}$	
$(pat_1, \dots, pat_n)$	$\{1=pat_1, \dots, \bar{n}=pat_n\}$	$(n \geq 2)$
$[pat_1, \dots, pat_n]$	$pat_1 :: \dots :: pat_n :: nil$	$(n \geq 0)$
<b>Pattern Rows <math>patrow</math></b>		
$id{:ty} \langle as\ pat \rangle \langle ,\ patrow \rangle$	$id = id{:ty} \langle as\ pat \rangle \langle ,\ patrow \rangle$	
<b>Type Expressions <math>ty</math></b>		
$ty_1 * \dots * ty_n$	$\{1:ty_1, \dots, \bar{n}:ty_n\}$	$(n \geq 2)$

Figure 16: Derived forms of Patterns and Type Expressions

Derived Form	Equivalent Form
<b>Function-value Bindings <i>fvalbind</i></b>	
$\langle \text{op} \rangle \text{var } \text{atpat}_{11} \cdots \text{atpat}_{1n} \langle : \text{ty} \rangle = \text{exp}_1$ $  \langle \text{op} \rangle \text{var } \text{atpat}_{21} \cdots \text{atpat}_{2n} \langle : \text{ty} \rangle = \text{exp}_2$ $  \quad \dots \quad \dots$ $  \langle \text{op} \rangle \text{var } \text{atpat}_{m1} \cdots \text{atpat}_{mn} \langle : \text{ty} \rangle = \text{exp}_m$ $\langle \text{and } fvalbind \rangle$	$\langle \text{op} \rangle \text{var} = \text{fn } \text{var}_1 \Rightarrow \dots \text{fn } \text{var}_n \Rightarrow$ $\text{case } (\text{var}_1, \dots, \text{var}_n) \text{ of}$ $(\text{atpat}_{11}, \dots, \text{atpat}_{1n}) \Rightarrow \text{exp}_1 \langle : \text{ty} \rangle$ $  (\text{atpat}_{21}, \dots, \text{atpat}_{2n}) \Rightarrow \text{exp}_2 \langle : \text{ty} \rangle$ $  \quad \dots \quad \dots$ $  (\text{atpat}_{m1}, \dots, \text{atpat}_{mn}) \Rightarrow \text{exp}_m \langle : \text{ty} \rangle$ $\langle \text{and } fvalbind \rangle$ <p style="text-align: center;">(<math>\text{var}_1, \dots, \text{var}_n</math> distinct and new)</p>
<b>Declarations <i>dec</i></b>	
<b>fun <i>fvalbind</i></b>	<b>val rec <i>fvalbind</i></b>
<b>datatype <i>datbind</i> withtype <i>tybind</i></b>	<b>datatype <i>datbind'</i> ; type <i>tybind</i></b>
<b>abstype <i>datbind</i> withtype <i>tybind</i></b> <b>with <i>dec</i> end</b>	<b>abstype <i>datbind'</i></b> <b>with type <i>tybind</i> ; <i>dec</i> end</b>
<b><i>exp</i></b>	<b>val <i>it</i> = <i>exp</i></b>
(see note in text concerning <i>datbind'</i> )	

Figure 17: Derived forms of Function-value Bindings and Declarations

Derived Form	Equivalent Form
<b>Structure Expressions <i>strex</i></b>	
<b><i>funid</i> ( <i>strdec</i> )</b>	<b><i>funid</i> ( struct <i>strdec</i> end )</b>
<b>Functor Bindings <i>funbind</i></b>	
<b><i>funid</i> ( <i>spec</i> ) &lt; : <i>sigexp</i> &gt; =</b> <b><i>strex</i> &lt; and <i>funbind</i> &gt;</b>	<b><i>funid</i> ( <i>strid</i> : sig <i>spec</i> end ) &lt; : <i>sigexp'</i> &gt; =</b> <b>let open <i>strid</i> in <i>strex</i> end &lt; and <i>funbind</i> &gt;</b> ( <i>strid</i> new; see note in text concerning <i>sigexp'</i> )
<b>Functor Signature Expressions <i>funsigexp</i></b>	
<b>( <i>spec</i> ) : <i>sigexp</i></b>	<b>( <i>strid</i> : sig <i>spec</i> end ) : <i>sigexp'</i></b> ( <i>strid</i> new; see note in text concerning <i>sigexp'</i> )

Figure 18: Derived forms of Functors

## B Appendix: Full Grammar of the Core

In this Appendix, the full Core grammar is given for reference purposes. Roughly, it consists of the grammar of Section 2 augmented by the derived forms of Appendix A. But there is a further difference: two additional subclasses of the phrase class `Exp` are introduced, namely `AppExp` (application expressions) and `InfExp` (infix expressions). The inclusion relation among the four classes is as follows:

$$\text{AtExp} \subset \text{AppExp} \subset \text{InfExp} \subset \text{Exp}$$

The effect is that certain phrases, such as “`2 + while ... do ...`”, are now disallowed.

The grammatical conventions are exactly as in Section 2, namely:

- The brackets `< >` enclose optional phrases.
- For any syntax class `X` (over which `x` ranges) we define the syntax class `Xseq` (over which `xseq` ranges) as follows:

$$\begin{aligned} xseq ::= x & \quad (\text{singleton sequence}) \\ & \quad (\text{empty sequence}) \\ & \quad (x_1, \dots, x_n) \quad (\text{sequence, } n \geq 1) \end{aligned}$$

(Note that the “...” used here, a meta-symbol indicating syntactic repetition, must not be confused with “...” which is a reserved word of the language.)

- Alternative forms for each phrase class are in order of decreasing precedence.
- L (resp. R) means left (resp. right) association.
- The syntax of types binds more tightly than that of expressions.
- Each iterated construct (e.g. `match, ...`) extends as far right as possible; thus, parentheses may be needed around an expression which terminates with a `match`, e.g. “`fn match`”, if this occurs within a larger `match`.

The grammatical rules are displayed in Figures 19, 20, 21 and 22.

<i>atexp</i>	::=	$\langle \text{op} \rangle \text{longvar}$ $\langle \text{op} \rangle \text{longcon}$ $\langle \text{op} \rangle \text{longexcon}$ $\{ \langle \text{exprow} \rangle \}$ $\# \text{lab}$ $()$ $(\text{exp}_1, \dots, \text{exp}_n)$ $[\text{exp}_1, \dots, \text{exp}_n]$ $(\text{exp}_1; \dots; \text{exp}_n)$ $\text{let } \text{dec} \text{ in } \text{exp}_1; \dots; \text{exp}_n \text{ end}$ $(\text{exp})$	value variable value constructor exception constructor record record selector 0-tuple $n$ -tuple, $n \geq 2$ list, $n \geq 0$ sequence, $n \geq 1$ local declaration, $n \geq 1$
<i>exprow</i>	::=	$\text{lab} = \text{exp} \langle , \text{exprow} \rangle$	expression row
<i>appexp</i>	::=	$\text{atexp}$ $\text{appexp } \text{atexp}$	application expression
<i>infxp</i>	::=	$\text{appexp}$ $\text{infxp } \text{id} \text{ infxp}$	infix expression
<i>exp</i>	::=	$\text{infxp}$ $\text{exp} : \text{ty}$ $\text{exp andalso } \text{exp}$ $\text{exp orelse } \text{exp}$ $\text{exp handle } \text{match}$ $\text{raise } \text{exp}$ $\text{if } \text{exp} \text{ then } \text{exp}_1 \text{ else } \text{exp}_2$ $\text{while } \text{exp}_1 \text{ do } \text{exp}_2$ $\text{case } \text{exp} \text{ of } \text{match}$ $\text{fn } \text{match}$	typed (L) conjunction disjunction handle exception raise exception conditional iteration case analysis function
<i>match</i>	::=	$\text{mrule} \langle   \text{match} \rangle$	
<i>mrule</i>	::=	$\text{pat} \Rightarrow \text{exp}$	

Figure 19: Grammar: Expressions and Matches

<i>dec</i>	<pre>  ::= val <i>valbind</i>     fun <i>fvalbind</i>     type <i>typbind</i>     datatype <i>datbind</i> &lt;withtype <i>typbind</i>&gt;     abstype <i>datbind</i> &lt;withtype <i>typbind</i>&gt;       with <i>dec</i> end     exception <i>exbind</i>     local <i>dec</i><sub>1</sub> in <i>dec</i><sub>2</sub> end     open <i>longstrid</i><sub>1</sub> ... <i>longstrid</i><sub><i>n</i></sub>      <i>dec</i><sub>1</sub> &lt;;&gt; <i>dec</i><sub>2</sub>     infix &lt;<i>d</i>&gt; <i>id</i><sub>1</sub> ... <i>id</i><sub><i>n</i></sub>     infixr &lt;<i>d</i>&gt; <i>id</i><sub>1</sub> ... <i>id</i><sub><i>n</i></sub>     nonfix <i>id</i><sub>1</sub> ... <i>id</i><sub><i>n</i></sub>     <i>exp</i> </pre>	<pre> value declaration function declaration type declaration datatype declaration abstype declaration exception declaration local declaration open declaration, <i>n</i> ≥ 1 empty declaration sequential declaration infix (L) directive, <i>n</i> ≥ 1 infix (R) directive, <i>n</i> ≥ 1 nonfix directive, <i>n</i> ≥ 1 expression (top-level only) </pre>
<i>valbind</i>	<pre>  ::= <i>pat</i> = <i>exp</i> &lt;and <i>valbind</i>&gt;     rec <i>valbind</i> </pre>	
<i>fvalbind</i>	<pre>  ::= &lt;op&gt; <i>var</i> <i>atpat</i><sub>11</sub> ... <i>atpat</i><sub>1<i>n</i></sub> &lt;: <i>ty</i>&gt; = <i>exp</i><sub>1</sub>       &lt;op&gt; <i>var</i> <i>atpat</i><sub>21</sub> ... <i>atpat</i><sub>2<i>n</i></sub> &lt;: <i>ty</i>&gt; = <i>exp</i><sub>2</sub>       ...       &lt;op&gt; <i>var</i> <i>atpat</i><sub><i>m</i>1</sub> ... <i>atpat</i><sub><i>m</i><i>n</i></sub> &lt;: <i>ty</i>&gt; = <i>exp</i><sub><i>m</i></sub>       &lt;and <i>fvalbind</i>&gt; </pre>	<pre> <i>m, n</i> ≥ 1 See also note below </pre>
<i>typbind</i>	<pre>  ::= <i>tyvarseq tycon</i> = <i>ty</i> &lt;and <i>typbind</i>&gt; </pre>	
<i>datbind</i>	<pre>  ::= <i>tyvarseq tycon</i> = <i>conbind</i> &lt;and <i>datbind</i>&gt; </pre>	
<i>conbind</i>	<pre>  ::= &lt;op&gt; <i>con</i> &lt;of <i>ty</i>&gt; &lt;   <i>conbind</i>&gt; </pre>	
<i>exbind</i>	<pre>  ::= <i>excon</i> &lt;of <i>ty</i>&gt; &lt;and <i>exbind</i>&gt;     <i>excon</i> = <i>longexcon</i> &lt;and <i>exbind</i>&gt; </pre>	

Note: In the *fvalbind* form, if *var* has infix status then either *op* must be present, or *var* must be infix. Thus, at the start of any clause, “*op var (atpat, atpat')* ...” may be written “*(atpat var atpat')* ...”; the parentheses may also be dropped if “*:ty*” or “*=*” follows immediately.

Figure 20: Grammar: Declarations and Bindings

<i>atpat</i>	::=	-	wildcard
		$\langle \text{op} \rangle \text{var}$	variable
		<i>longcon</i>	constant
		<i>longexcon</i>	exception constant
		{ $\langle \text{patrow} \rangle$ }	record
		()	0-tuple
		( $\text{pat}_1, \dots, \text{pat}_n$ )	$n$ -tuple, $n \geq 2$
		[ $\text{pat}_1, \dots, \text{pat}_n$ ]	list, $n \geq 0$
		( <i>pat</i> )	
<i>patrow</i>	::=	...	wildcard
		<i>lab</i> = <i>pat</i> $\langle , \text{patrow} \rangle$	pattern row
		<i>id</i> $\langle : \text{ty} \rangle$ $\langle \text{as } \text{pat} \rangle \langle , \text{patrow} \rangle$	label as variable
<i>pat</i>	::=	<i>atpat</i>	atomic
		$\langle \text{op} \rangle \text{longcon } \text{atpat}$	value construction
		$\langle \text{op} \rangle \text{longexcon } \text{atpat}$	exception construction
		<i>pat</i> <sub>1</sub> <i>con</i> <i>pat</i> <sub>2</sub>	infix value construction
		<i>pat</i> <sub>1</sub> <i>excon</i> <i>pat</i> <sub>2</sub>	infix exception construction
		<i>pat</i> : <i>ty</i>	typed
		$\langle \text{op} \rangle \text{var} \langle : \text{ty} \rangle \text{ as } \text{pat}$	layered

Figure 21: Grammar: Patterns

<i>ty</i>	::=	<i>tyvar</i>	type variable
		{ $\langle \text{tyrow} \rangle$ }	record type expression
		<i>tyseq longtycon</i>	type construction
		$\text{ty}_1 * \dots * \text{ty}_n$	tuple type, $n \geq 2$
		$\text{ty} \rightarrow \text{ty}'$	function type expression
		( <i>ty</i> )	
<i>tyrow</i>	::=	<i>lab</i> : <i>ty</i> $\langle , \text{tyrow} \rangle$	type-expression row

Figure 22: Grammar: Type expressions



## C Appendix: The Initial Static Basis

We shall indicate components of the initial basis by the subscript 0. The initial static basis is

$$B_0 = (M_0, T_0), F_0, G_0, E_0$$

where

- $M_0 = \emptyset$
- $T_0 = \{\text{bool}, \text{int}, \text{real}, \text{string}, \text{list}, \text{ref}, \text{exn}, \text{instream}, \text{outstream}\}$
- $F_0 = \{\}$
- $G_0 = \{\}$
- $E_0 = (SE_0, TE_0, VE_0, EE_0)$

The members of  $T_0$  are type names, not type constructors; for convenience we have used type-constructor identifiers to stand also for the type names which are bound to them in the initial static type environment  $TE_0$ . Of these type names, `list` and `ref` have arity 1, the rest have arity 0; all except `exn`, `instream` and `outstream` admit equality.

The components of  $E_0$  are as follows:

- $SE_0 = \{\}$
- $VE_0$  is shown in Figures 23 and 24. Note that  $\text{Dom } VE_0$  contains those identifiers (`true`, `false`, `nil`, `::`) which are basic value constructors, for reasons discussed in Section 4.3.  $VE_0$  also includes  $EE_0$ , for the same reasons.
- $TE_0$  is shown in Figure 25. Note that the type structures in  $TE_0$  contain the type schemes of all basic value constructors.
- $\text{Dom } EE_0 = \text{BasExName}$ , the set of basic exception names listed in Section 6.5. In each case the associated type is `exn`, except that  $EE_0(\text{Io}) = \text{string} \rightarrow \text{exn}$ .

NONFIX	INFIX
$var \mapsto \sigma$	$var \mapsto \sigma$
map $\mapsto \forall 'a 'b. ('a \rightarrow 'b) \rightarrow$ $'a \text{ list} \rightarrow 'b \text{ list}$	Precedence 7 : / $\mapsto \text{real} * \text{real} \rightarrow \text{real}$
rev $\mapsto \forall 'a. 'a \text{ list} \rightarrow 'a \text{ list}$	div $\mapsto \text{int} * \text{int} \rightarrow \text{int}$
not $\mapsto \text{bool} \rightarrow \text{bool}$	mod $\mapsto \text{int} * \text{int} \rightarrow \text{int}$
~ $\mapsto \text{num} \rightarrow \text{num}$	* $\mapsto \text{num} * \text{num} \rightarrow \text{num}$
abs $\mapsto \text{num} \rightarrow \text{num}$	Precedence 6 : + $\mapsto \text{num} * \text{num} \rightarrow \text{num}$
floor $\mapsto \text{real} \rightarrow \text{int}$	- $\mapsto \text{num} * \text{num} \rightarrow \text{num}$
real $\mapsto \text{int} \rightarrow \text{real}$	^ $\mapsto \text{string} * \text{string} \rightarrow \text{string}$
sqrt $\mapsto \text{real} \rightarrow \text{real}$	Precedence 5 : :: $\mapsto \forall 'a. 'a * 'a \text{ list} \rightarrow 'a \text{ list}$
sin $\mapsto \text{real} \rightarrow \text{real}$	@ $\mapsto \forall 'a. 'a \text{ list}$ $* 'a \text{ list} \rightarrow 'a \text{ list}$
cos $\mapsto \text{real} \rightarrow \text{real}$	Precedence 4 : = $\mapsto \forall 'a. ''a * ''a \rightarrow \text{bool}$
arctan $\mapsto \text{real} \rightarrow \text{real}$	<> $\mapsto \forall 'a. ''a * ''a \rightarrow \text{bool}$
exp $\mapsto \text{real} \rightarrow \text{real}$	< $\mapsto \text{num} * \text{num} \rightarrow \text{bool}$
ln $\mapsto \text{real} \rightarrow \text{real}$	> $\mapsto \text{num} * \text{num} \rightarrow \text{bool}$
size $\mapsto \text{string} \rightarrow \text{int}$	<= $\mapsto \text{num} * \text{num} \rightarrow \text{bool}$
chr $\mapsto \text{int} \rightarrow \text{string}$	>= $\mapsto \text{num} * \text{num} \rightarrow \text{bool}$
ord $\mapsto \text{string} \rightarrow \text{int}$	Precedence 3 : := $\mapsto \forall 'a. 'a \text{ ref} * 'a \rightarrow \text{unit}$
explode $\mapsto \text{string} \rightarrow \text{string list}$	o $\mapsto \forall 'a 'b 'c. ('b \rightarrow 'c)$ $* ('a \rightarrow 'b) \rightarrow ('a \rightarrow 'c)$
implode $\mapsto \text{string list} \rightarrow \text{string}$	
! $\mapsto \forall 'a. 'a \text{ ref} \rightarrow 'a$	
ref $\mapsto \forall '_a. '_a \rightarrow '_a \text{ ref}$	
true $\mapsto \text{bool}$	
false $\mapsto \text{bool}$	
nil $\mapsto \forall 'a. 'a \text{ list}$	

Notes:

- In type schemes we have taken the liberty of writing  $ty_1 * ty_2$  in place of  $\{1 \mapsto ty_1, 2 \mapsto ty_2\}$ .
- An identifier with type involving `num` stands for two functions – one in which `num` is replaced by `int` in its type, and another in which `num` is replaced by `real` in its type. Sometimes an explicit type constraint will be needed if the surrounding text does not determine the type of a particular occurrence of `+` (for example). For this purpose, the surrounding text is no larger than the enclosing top-level declaration; an implementation may require that a smaller context determines the type.
- The type schemes associated with special constants are given in Figure 25 which shows the initial static type environment.

Figure 23: Static  $VE_0$  (except for Input/Output and  $EE_0$ )

<i>var</i>	$\mapsto \sigma$
<code>std_in</code>	<code>instream</code>
<code>open_in</code>	<code>string <math>\rightarrow</math> instream</code>
<code>input</code>	<code>instream * int <math>\rightarrow</math> string</code>
<code>lookahead</code>	<code>instream <math>\rightarrow</math> string</code>
<code>close_in</code>	<code>instream <math>\rightarrow</math> unit</code>
<code>end_of_stream</code>	<code>instream <math>\rightarrow</math> bool</code>
<code>std_out</code>	<code>ostream</code>
<code>open_out</code>	<code>string <math>\rightarrow</math> ostream</code>
<code>output</code>	<code>ostream * string <math>\rightarrow</math> unit</code>
<code>close_out</code>	<code>ostream <math>\rightarrow</math> unit</code>

Figure 24: Static  $VE_0$  (Input/Output)

<i>tycon</i>	$\mapsto \{ \theta, \{ con_1 \mapsto \sigma_1, \dots, con_n \mapsto \sigma_n \} \} \quad (n \geq 0)$
<code>unit</code>	$\{ \Lambda().\{ \}, \{ \} \}$
<code>bool</code>	$\{ \text{bool}, \{ \text{true} \mapsto \text{bool}, \text{false} \mapsto \text{bool} \} \}$
<code>int</code>	$\{ \text{int}, \{ i \mapsto \text{int} ; i \text{ an integer constant} \} \}$
<code>real</code>	$\{ \text{real}, \{ r \mapsto \text{real} ; r \text{ a real constant} \} \}$
<code>string</code>	$\{ \text{string}, \{ s \mapsto \text{string} ; s \text{ a string constant} \} \}$
<code>list</code>	$\{ \text{list}, \{ \text{nil} \mapsto \forall 'a . 'a \text{ list}, \text{::} \mapsto \forall 'a . 'a * 'a \text{ list} \rightarrow 'a \text{ list} \} \}$
<code>ref</code>	$\{ \text{ref}, \{ \text{ref} \mapsto \forall '_a . '_a \rightarrow '_a \text{ ref} \} \}$
<code>exn</code>	$\{ \text{exn}, \{ \} \}$
<code>instream</code>	$\{ \text{instream}, \{ \} \}$
<code>ostream</code>	$\{ \text{ostream}, \{ \} \}$

Figure 25: Static  $TE_0$

## D Appendix: The Initial Dynamic Basis

We shall indicate components of the initial basis by the subscript 0. The initial dynamic basis is

$$B_0 = F_0, G_0, E_0$$

where

- $F_0 = \{\}$
- $G_0 = \{\}$
- $E_0 = E'_0 + E''_0$

$E'_0$  contains bindings of identifiers to the basic values `BasVal` and basic exception names `BasExName`; in fact  $E'_0 = SE'_0, VE'_0, EE'_0$ , where:

- $SE'_0 = \{\}$
- $VE'_0 = \{id \mapsto id ; id \in \text{BasVal}\} \cup \{:= \mapsto :=\}$
- $EE'_0 = \{id \mapsto id ; id \in \text{BasExName}\}$

Note that  $VE'_0$  is the identity function on `BasVal`; this is because we have chosen to denote these values by the names of variables to which they are initially bound. The semantics of these basic values (most of which are functions) lies principally in their behaviour under `APPLY`, which we describe below. On the other hand the semantics of `:=` is provided by a special semantic rule, rule 110. Similarly,  $EE'_0$  is the identity function on `BasExName`, the set of basic exception names, because we have also chosen these names to be just those exception constructors to which they are initially bound. These exceptions are raised by `APPLY` as described below.

$E''_0$  contains initial variable bindings which, unlike `BasVal`, are definable in ML; it is the result of evaluating the following declaration in the basis  $F_0, G_0, E'_0$ . For convenience, we have also included all basic infix directives in this declaration.

```

infix 3  o
infix 4  = <> < > <= >=
infix 5  @
infixr 5  ::
infix 6  + - ^
infix 7  div mod / *

fun (F o G)x = F(G x)

fun nil @ M = M
  | (x::L) @ M = x::(L @ M)

```

```

fun s ^ s' = implode((explode s) @ (explode s'))

fun map F nil = nil
  | map F (x::L) = (F x)::(map F L)

fun rev nil = nil
  | rev (x::L) = (rev L) @ [x]

fun not true = false
  | not false = true

fun ! (ref x) = x

```

We now describe the effect of APPLY upon each value in BasVal. We shall normally use  $i$ ,  $r$ ,  $n$ ,  $s$  to range over integers, reals, numbers (integer or real), strings respectively. We also take the liberty of abbreviating “APPLY(**abs**,  $r$ )” to “**abs**( $r$ )”, “APPLY(**mod**,  $\{1 \mapsto i, 2 \mapsto d\}$ )” to “ $i \bmod d$ ”, etc. .

- $\sim(n)$  returns the negation of  $n$ .
- **abs**( $n$ ) returns the absolute value of  $n$ .
- **floor**( $r$ ) returns the largest integer  $i$  not greater than  $r$ ; it returns the packet [Floor] if  $i$  is out of range.
- **real**( $i$ ) returns the real value equal to  $i$ .
- **sqrt**( $r$ ) returns the square root of  $r$ , or the packet [Sqrt] if  $r$  is negative.
- **sin**( $r$ ), **cos**( $r$ ) return the result of the appropriate trigonometric functions.
- **arctan**( $r$ ) returns the result of the appropriate trigonometric function in the range  $\pm\pi/2$ .
- **exp**( $r$ ), **ln**( $r$ ) return respectively the exponential and the natural logarithm of  $r$ , or an exception packet [Exp] or [Ln] if the result is out of range.
- **size**( $s$ ) returns the number of characters in  $s$ .
- **chr**( $i$ ) returns the  $i$ 'th ASCII character – or the packet [Chr] if none exists.
- **ord**( $s$ ) returns the ASCII ordinal number of the first character in  $s$ , or the packet [Ord] if  $s$  is empty.
- **explode**( $s$ ) returns the list of characters (as single-character strings) of which  $s$  consists.

- `implode(L)` returns the string formed by concatenating all members of the list  $L$  of strings.
- The arithmetic functions `/,*,+,-` all return the results of the usual arithmetic operations, or exception packets respectively `[Quot]`, `[Prod]`, `[Sum]`, `[Diff]` if the result is undefined or out of range.
- `i mod d`, `i div d` return integers  $r, q$  (remainder, quotient) determined by the equation  $d \times q + r = i$ , where either  $0 \leq r < d$  or  $d < r \leq 0$ . Thus the remainder has the same sign as the divisor  $d$ . The packet `[Mod]` or `[Div]` is returned if  $d = 0$ .
- The order relations `<,>,<=,>=` return boolean values in accord with their usual meanings.
- `v1 = v2` returns the boolean value of  $v_1 = v_2$ , where the equality of values (`=`) is defined recursively as follows:
  - If  $v_1, v_2$  are constants (including nullary constructors) or addresses, then  $v_1 = v_2$  iff  $v_1$  and  $v_2$  are identical.
  - $(con_1, v_1) = (con_2, v_2)$  iff  $con_1, con_2$  are identical and  $v_1 = v_2$ .
  - $r_1 = r_2$  (for records  $r_1, r_2$ ) iff  $Dom\ r_1 = Dom\ r_2$  and, for each  $lab \in Dom\ r_1$ ,  $r_1(lab) = r_2(lab)$ .

The type discipline (in particular, the fact that function types do not admit equality) makes it unnecessary to specify equality in any other cases.

- `v1 <> v2` returns the opposite boolean value to  $v_1 = v_2$ .

It remains to define the effect of `APPLY` upon basic values concerned with input/output; we therefore proceed to describe the ML input/output system.

Input/Output in ML uses the concept of a *stream*. A stream is a finite or infinite sequence of characters; if finite, it may or may not be terminated. (It may be convenient to think of a special end-of-stream character signifying termination, provided one realises that this “character” is never treated as data). Input streams – or *instreams* – are of type `instream` and will be denoted by *is*; output streams – or *outstreams* – are of type `outstream` and will be denoted by *os*. Both these types of stream are *abstract*, in the sense that streams may only be manipulated by the functions provided in `BasVal`.

Associated with an *instream* is a *producer*, normally an I/O device or file; similarly an *outstream* is associated with a *consumer*. After this association has been established – either initially or by the `open_in` or `open_out` function – the stream acts as a vehicle for character transmission from producer to program, or from program to consumer. The association can be broken by the `close_in` or

`close_out` function. A closed stream permits no further character transmission; a closed instream is equivalent to one which is empty and terminated.

There are two streams in `BasVal`:

- `std_in`: an instream whose producer is the terminal.
- `std_out`: an outstream whose consumer is the terminal.

The other basic values concerned with Input/Output are all functional, and the effect of `APPLY` upon each of them given below. We take the liberty of abbreviating “`APPLY(open_in, s)`” to “`open_in(s)`” etc., and we shall use  $s$  and  $n$  to range over strings and integers respectively.

- `open_in(s)` returns a new instream  $is$ , whose producer is the external file named  $s$ . It returns exception packet

`[Io("Cannot open s")]`

if file  $s$  does not exist or does not provide read access.

- `open_out(s)` returns a new outstream  $os$ , whose consumer is the external file named  $s$ . If file  $s$  is non-existent, it is taken to be initially empty.
- `input(is, n)` returns a string  $s$  containing the first  $n$  characters of  $is$ , also removing them from  $is$ . If only  $k < n$  characters are available on  $is$ , then
  - If  $is$  is terminated after these  $k$  characters, the returned string  $s$  contains them alone, and they are removed from  $is$ .
  - Otherwise no result is returned until the producer of  $is$  either supplies  $n$  characters or terminates the stream.
- `lookahead(is)` returns a single-character string  $s$  containing the next character of  $is$ , without removing it. If no character is available on  $is$  then
  - If  $is$  is closed, the empty string is returned.
  - Otherwise no result is returned until the producer of  $is$  either supplies a character or closes the stream.
- `close_in(is)` empties and terminates the instream  $is$ .
- `end_of_stream(is)` is equivalent to `(lookahead(is)=="")`; it detects the end of the instream  $is$ .
- `output(os, s)` writes the characters of  $s$  to the outstream  $os$ , unless  $os$  is closed, in which case it returns the exception packet
 

`[Io("Output stream is closed")]`
- `close_out(os)` terminates the outstream  $os$ .

## E Appendix: The Development of ML

This Appendix records the main stages in the development of ML, and the people principally involved. The main emphasis is upon the design of the language; there is also a section devoted to implementation. On the other hand, no attempt is made to record work on implementation environments, or on applications of the language.

### Origins

ML and its semantic description have evolved over a period of about fourteen years. It is a fusion of many ideas from many people; in this appendix we try to record and to acknowledge the important precursors of its ideas, the important influences upon it, and the important contributions to its design, implementation and semantic description.

ML, which stands for meta language, was conceived as a medium for finding and performing proofs in a formal logical system. This application was the focus of the initial design effort, by Robin Milner in collaboration first with Malcolm Newey and Lockwood Morris, then with Michael Gordon and Christopher Wadsworth [11]. The intended application to proof affected the design considerably. Higher order functions in full generality seemed necessary for programming proof tactics and strategies, and also a robust type system (see below). At the same time, imperative features were important for practical reasons; no-one had experience of large useful programs written in a pure functional style. In particular, an exception-raising mechanism was highly desirable for the natural presentation of tactics.

The full definition of this first version of ML was included in a book [12] which describes LCF, the proof system which ML was designed to support. The details of how the proof application exerted an influence on design is reported by Milner [22]. Other early influences were the applicative languages already in use in Artificial Intelligence, principally LISP [19], ISWIM [17] and POP2 [5].

### Polymorphic types

The polymorphic type discipline and the associated type-assignment algorithm were prompted by the need for security; it is vital to know that when a program produces an object which it claims to be a theorem, then it is indeed a theorem. A type discipline provides the security, but a polymorphic discipline also permits considerable flexibility.

The key ideas of the type discipline were evolved in combinatory logic by Haskell Curry and Roger Hindley, who arrived at different but equivalent algorithms for computing principal type schemes. Curry's [7] algorithm was by equation-solving; Hindley [14] used the unification algorithm of Alan Robinson



[27] and also presented the precursor of our type inference system. James Morris [24] independently gave an equation-solving algorithm very similar to Curry's. The idea of an algorithm for finding principal type schemes is very natural and may well have been known earlier. I am grateful to Roger Hindley for pointing out that Carew Meredith's inference rule for propositional logic called Condensed Detachment, defined in the early 1950s, clearly suggests that he knew such an algorithm [20].

Milner [21], during the design of ML, rediscovered principal types and their calculation by unification, for a language (slightly richer than combinatory logic) containing local declarations. He and Damas [9] presented the ML type inference systems following Hindley's style. Damas [8], using ideas from Michael Gordon, also devised the first mathematical treatment of polymorphism in the presence of references and assignment; recently Tofte [29] has produced a treatment which differs in some respects, but is easier to follow and has a simpler semantic presentation.

## Refinement of the Core Language

Two movements led to the re-design of ML. One was the work of Rod Burstall and his group on specifications, crystallised in the specification language CLEAR [4] and in the functional programming language HOPE [3]; the latter was for expressing executable specifications. The outcome of this work which is relevant here was twofold. First, there were elegant programming features in HOPE, particularly pattern matching and clausal function definitions; second, there were ideas on modular construction of specifications, using signatures in the interfaces. A smaller but significant movement was by Luca Cardelli, who extended the data-type repertoire in ML by adding named records and variant types.

In 1983, Milner (prompted by Bernard Sufrin) wrote the first draft of a standard form of ML attempting to unite these ideas; over the next three years it evolved into the Standard ML Core Language. Notable here was the harmony found among polymorphism, HOPE patterns and Cardelli records, and the nice generalisations of ML exceptions due to ideas from Alan Mycroft, Brian Monahan and Don Sannella. A simple stream-based I/O mechanism was developed from ideas of Cardelli by Milner and Harper. The Standard ML Core Language is described in detail in a composite report [15] which also contains a description of the I/O mechanism and MacQueen's proposal for program modules (see later for discussion of this). Since then only few changes to the Core Language have occurred. Milner proposed equality types, and these were added, together with a few minor adjustments [23]. The latest and final development has been in the exception mechanism, by MacQueen using an idea from Burstall [1]; it unites the ideas of exception and data type construction.

## Modules

Besides contributory ideas to the Core Language, HOPE [3] contained a simple notion of program module. The most important and original feature of ML Modules, however, stems from the work on parameterised specifications in CLEAR [4]. MacQueen, who was a member of Burstall's group at the time, designed [18] a new parametric module feature for HOPE inspired by the CLEAR work. He later extended the parameterisation ideas by a novel method of specifying sharing of components among the structure parameters of a function, and produced a draft design which accommodated features already present in ML – in particular the polymorphic type system. This design was discussed in detail at Edinburgh, leading to MacQueen's first report on Modules [15].

Thereafter, the design came under close scrutiny through a draft operational static semantics and prototype implementation of it by Harper, through Kevin Mitchell's implementation of the evaluation, through a denotational semantics written by Don Sannella, and then through further work on operational semantics by Milner and Tofte. (More is said about this in the later section on Semantics.) In all of this work the central ideas withstood scrutiny, while it also became clear that there were gaps in the design and ambiguities in interpretation. (An example of a gap was the inability to specify sharing between a function argument structure and its result structure; an example of an ambiguity was the question of whether sharing exists in a structure over and above what is specified in the signature expression which accompanies its declaration.)

Much discussion ensued; it was possible for a wider group to comment on Modules through using Harper's prototype implementation, while Harper, Milner and Tofte gained understanding during development of this semantics. In parallel, Sannella and Tarlecki explored the implications of Modules for the methodology of program development [28]. Tofte, in his thesis [29], proved several technical properties of Modules in a skeletal language, which generated considerable confidence in this design. A key point in this development was the proof of the existence of principal signatures, and, in the careful distinction between the notion of *enrichment* of structures, which allows more polymorphism and more components, and *realisation* which allows more sharing.

At a meeting in Edinburgh in 1987 a choice of two designs was presented, hinging upon whether or not a functor application should coerce its actual argument to its argument signature. The meeting chose coercion, and thereafter the production of Section 5 of this report – the Static Semantics of Modules – was a matter of detailed care. That section is undoubtedly the most original and demanding part of this semantics, just as the ideas of MacQueen upon which it is based are the most far-reaching extension to the original design of ML.

## Implementation

The first implementation of ML was by Malcolm Newey, Lockwood Morris and Robin Milner in 1974, for the DEC10. Later Mike Gordon and Chris Wadsworth joined; their work was mainly in specialising ML towards machine-assisted reasoning. Around 1980 Luca Cardelli implemented a version on VAX; his work was later extended by Alan Mycroft, Kevin Mitchell and John Scott. This version contained one or two new data-type features, and was based upon the Functional Abstract Machine (FAM), a virtual machine which has been a considerable stimulus to later implementation. By providing a reasonably efficient implementation, this work enabled the language to be taught to students; this, in turn, prompted the idea that it could become a useful general purpose language.

In Gothenburg, an implementation was developed by Lennart Augustsson and Thomas Johnsson in 1982, using lazy evaluation rather than call-by-value; the result was called Lazy ML and is reported in [2]. This work is part of continuing research in many places on implementation of lazy evaluation in pure functional languages. But for ML, which includes exceptions and assignment, the emphasis has been mainly upon strict evaluation (call-by-value).

In Cambridge, in the early 1980s, Larry Paulson made considerable improvements to the Edinburgh ML compiler, as part of his wider programme of improving Edinburgh LCF to become Cambridge LCF [25]. This system was supported larger proofs than the Edinburgh system, and with greater convenience; in particular, the compiled ML code ran four to five times faster.

Around the same time Gérard Huet at INRIA (Versailles) adapted ML to Maclisp on Multics, again for use in machine-assisted proof. There was close collaboration between INRIA and Cambridge in this period. ML has undergone a separate development in the group at INRIA, arriving at a language and implementation known as CAML [6]; this is close to the core language of Standard ML, but does not include the Modules.

The first implementation of the Standard ML core language was by Mitchell, Mycroft and John Scott of Edinburgh, around 1984, and this was shortly followed by an implementation by David Matthews at Cambridge, carried out in his language Poly.

The prototype implementation of Modules, before that part of the language settled down, was done in 1985-6; Mitchell dealt with evaluation, while Harper tackled the elaboration (or 'signature checking') which raised problems of a kind not previously encountered. The Edinburgh implementation continues to play the role of a test-bed for language development.

Meanwhile Matthews' Cambridge implementation also advanced to embrace Modules, and now adheres to the Standard. This implementation has supported applications of considerable size, both for machine-assisted proof and for hardware design. It is now available commercially from Imperial Software Technology.

In 1986, as the Modules definition was settling down, David MacQueen began

an implementation at Bell AT&T Laboratories, assisted by Andrew Appel, based upon the Edinburgh work. They were shortly joined by Trevor Jim. At the time of writing (May 1988) first release of this implementation is completed, and adheres to the Standard. Work continues to improve its performance.

The Bell and Cambridge implementations, led by MacQueen and Matthews respectively, are currently the most complete and highly engineered. Other currently active implementations are by Michael Hedlund at the Rutherford-Appleton Laboratory and by Malcolm Newey and his group at the Australian National University.

## Semantics

The description of the first version of ML [12] was informal, and in an operational style; around the same time a denotational semantics was written, but never published, by Mike Gordon and Robin Milner. Meanwhile structured operational semantics, presented as an inference system, was gaining credence as a tractable medium. This originates with the reduction rules of  $\lambda$ -calculus, but was developed more widely through the work of Plotkin [26], and also by Milner. This was at first only used for dynamic semantics, but later the benefit of using inference systems for both static and dynamic semantics became apparent. This advantage was realised when Gilles Kahn and his group at INRIA were able to execute early versions of both forms of semantics for the ML Core Language using their Typol system [10]. The static and dynamic semantics of the Core reached a final form mostly through work by Mads Tofte and Robin Milner.

The modules of ML presented little difficulty as far as dynamic semantics is concerned, but the static semantics of Modules was a concerted effort by several people. MacQueen's original informal description [15] was the starting point; Sannella wrote a denotational semantics for several versions, which showed that several issues had not been settled by the informal description. Robert Harper, while writing the first implementation of Modules, made the first draft of the static semantics. Harper's version made clear the importance of structure names; work by Milner and Tofte introduced further ideas including realisation; thereafter a concerted effort by all three led to several suggestions for modification of the language, and a small range of alternative interpretations; these were assessed in discussion with MacQueen, and more widely with the principal users of the language, and an agreed form was reached.

There is no doubt that the interaction between design and semantic description of Modules has been one of the most striking phases in the entire language development, leading (in the opinion of those involved) to a high degree of confidence both in the language and in the semantic method.

## **Literature**

The present document is the definition of Standard ML; further versions of it will be produced as the language develops (but the intention is to minimise the number of versions). An informal definition, consistent with Version 2 of this document as far as the Core Language is concerned, is provided by [15], as modified by [23] and [1]. An elementary textbook covering the Core language has been recently published, written by Åke Wikström [30]. Robert Harper [13] has written a shorter introduction which also includes material on Modules.

## **Further acknowledgments**

Apart from the people mentioned above we also acknowledge the following, all of whom have contributed in some way to the evolution of ML: Guy Cousineau, Jim Hook, Gerard Huet, Gilles Kahn, Brian Monahan, Peter Mosses, Alan Mycroft, David Park, David Rydeheard, David Schmidt, Stefan Sokolowski, Bernard Sufrin, Philip Wadler.

## References

- [1] Appel, A., MacQueen, D.B., Milner, A.J.R.G. and Tofte, M., *Unifying Exceptions with Constructors in Standard ML*, Report ECS-LFCS-88-55, Laboratory for Foundations of Computer Science, Computer Science Dept, Edinburgh University, 1988.
- [2] Augustsson L. and Johnsson, T., *Lazy ML User's Manual*, Dept. of Computer Sciences, Chalmers University of Technology, Gothenburg, 1987.
- [3] Burstall R.M., MacQueen, D.B. and Sannella, D.T., *HOPE: An Experimental Applicative Language*, Report CSR-62-80, Computer Science Dept, Edinburgh University, 1980.
- [4] Burstall, R.M. and Goguen, J.A., *Putting Theories together to make Specifications*, Proc Fifth Annual Joint Conference on Artificial Intelligence, Cambridge, Mass., 1977, pp 1045–1058.
- [5] Burstall, R.M. and Popplestone, R., *POP-2 Reference Manual*, Machine Intelligence 2, ed Dale and Michie, Oliver and Boyd, 1968.
- [6] Cousineau, G., Curien, P.L. and Mauny, M., *The Categorical Abstract Machine*, in Functional Programming Languages and Computer Architecture, ed Jouannaud, Lecture Notes in Computer Science Vol 201, Springer Verlag, 1985, pp 50–64.
- [7] Curry, H.B., *Modified Basic Functionality in Combinatory Logic*, *Dialectica* 23, 1969, pp 83–92.
- [8] Damas, L., *Type Assignment in Programming Languages*, PhD thesis, CST-33-85, Computer Science Department, Edinburgh University, 1985.
- [9] Damas, L. and Milner, A.J.R.G., *Principal Type-schemes for Functional Programs*, Proc 9th annual symposium on Principles of Programming Languages, ACM, 1982.
- [10] Despeyroux, T., *Executable Specification of Static Semantics*, Proc Symposium on Semantics of Data Types, Sophia Antipolis, Springer-Verlag Lecture Notes in Computer Science, Vol.173, 1984.
- [11] Gordon, M.J.C., Milner, A.J.R.G., Morris, L., Newey, M.C. and Wadsworth, C.P., *A Metalanguage for Interactive Proof in LCF*, Proc 5th ACM Symposium on Principles of Programming Languages, Tucson, 1978.
- [12] Gordon, M.J.C., Milner, A.J.R.G. and Wadsworth, C.P., *Edinburgh LCF: a Mechanised Logic of Computation*, Springer-Verlag Lecture Notes in Computer Science, Vol.78, 1979.

- [13] Harper, R.W., *Introduction to Standard ML*, Report ECS-LFCS-86-14, Laboratory for Foundations of Computer Science, Computer Science Department, Edinburgh University, 1986.
- [14] Hindley, R., *The Principal Type-scheme of an Object in Combinatory Logic*, Transactions of AMS 146, pp29–60, 1969.
- [15] Harper, R.M., MacQueen, D.B. and Milner, A.J.R.G., *Standard ML*, Report ECS-LFCS-86-2, Laboratory for Foundations of Computer Science, Computer Science Department, Edinburgh University, 1986.
- [16] Harper, R.M., Milner, A.J.R.G., Tofte, M., *The Semantics of Standard ML, Version 1* Report ECS-LFCS-87-36, Laboratory for Foundations of Computer Science, Computer Science Department, Edinburgh University, 1987.
- [17] Landin, P.J., *The next 700 Programming Languages*, CACM, Vol.9, No.3, 1966, pp57–164.
- [18] MacQueen, D.D., *Structures and parameterisation in a typed functional language*, Proc. Symposium on Functional Programming and Computer Architecture, Aspinas, Sweden, 1981.
- [19] McCarthy, J. et al., *LISP 1.5 Programming Manual*, The MIT Press, Cambridge, Mass, 1956.
- [20] Meredith, D., *In memoriam Carew Arthur Meredith*, Notre Dame J. Formal Logic, Vol 18, 1977, pp 513–516.
- [21] Milner, A.J.R.G., *A theory of type polymorphism in programming*, J. Comp. Sys.Sci, Vol 17, 1978, pp 348–375.
- [22] Milner, R., *How ML Evolved*, Polymorphism (The ML/LCF/Hope Newsletter), Vol.1, No.1, 1983.
- [23] Milner, A.J.R.G., *Changes to the Standard ML Core Language*, Report ECS-LFCS-87-33, Laboratory for Foundations of Computer Science, Computer Science Department, Edinburgh University, 1987.
- [24] Morris, J.H., *Lambda Calculus Models of Programming Languages*, MAC-TR-57 (Thesis), Project MAC, M.I.T., 1968.
- [25] Paulson, L.C., *Logic and Computation: Interactive Proof with LCF*, Cambridge Tracts in Theoretical Computer Science 2, Cambridge University Press, 1987.
- [26] Plotkin, G.D., *A Structural Approach to Operational Semantics*, Technical Report DAIMI FN-19, Computer Science Department, Aarhus University, 1981.

- [27] Robinson, J.A., *A Machine-oriented Logic based upon the Resolution Principle*, Journal of ACM, Vol 12, No 1, pp23-41, 1965.
- [28] Sannella, D.T. and Tarlecki, A., *Program Specification and Development in Standard ML*, Proc 12th ACM Symposium on Principles of Programming Languages, New Orleans, 1985.
- [29] Tofte, M., *Operational Semantics and Polymorphic Type Inference*, PhD Thesis CST-52-88, Computer Science Department, Edinburgh University, 1988. (Also appears as Report ECS-LFCS-88-54 of the Laboratory for Foundations of Computer Science.)
- [30] Wikström, Å., *Functional Programming using Standard ML*, Prentice Hall, 1987.



## Index

- () (0-tuple), 64, 67, 69
- ( ), 3
  - in expression, 7, 8, 24, 49, 64, 66, 67
  - in pattern, 9, 28, 53, 64, 69
  - in sequence, 7, 66
  - in type expression, 9, 29, 69
- [ ], 3, 64, 67, 69
- { }, 3
  - in atomic expression, 8, 23, 49, 67
  - in pattern, 9, 28, 52, 69
  - in record type expression, 9, 29, 69
- (\* \*) (comment brackets), 4, 5
- , (comma), 3, 7, 64, 66, 67, 69
- ... (wildcard pattern row), 3, 9, 28, 30, 53, 69
- \_ (underbar)
  - wildcard pattern, 3, 28, 52, 69
  - in identifier, 4
- |, 3, 4, 67, 68
- =, 3, 4, 46, 73, 75
- =>, 3
  - in a match rule, 8, 67
- >, 3, 9, 29, 69
- ~, 3, 4, 46, 71, 74
- . (period)
  - in real constants, 3
  - in long identifiers, 4
- ", 3
- \, 3, 4
- !, 4, 71, 74
- %, 4
- &, 4
- \$, 4
- #, 3, 4, 64, 67
- +, 4, 46, 71, 73, 75
- , 4, 46, 71, 73, 75
- /, 4, 46, 71, 73, 75
- : (see also type constraint), 4
  - :=, 70, 71, 72, 73
  - := (assignment), 45, 49, 71, 73
  - <, 4, 46, 71, 73, 75
  - >, 4, 46, 71, 73, 75
  - <=, 46, 71, 73, 75
  - >=, 46, 71, 73, 75
  - <>, 46, 71, 73, 75
  - ?, 4
  - @, 4, 71, 73
  - ’, 4
  - ^, 4, 71, 73
  - \*, 4, 46, 64, 69, 71, 73, 75
  - { } (empty map), 17
  - + (modification), 17, 18, 48
  - ⊕, 18, 31
  - Λ (in type function), 17, 19, 27
  - ∀ (in type scheme), 17, 19
    - see also generalisation
  - α (see type variable)
  - ρ (see record type)
  - τ (see type)
  - τ<sup>(k)</sup> (type vector), 17, 18, 19
  - σ (type scheme), 17, 19, 20–21, 23, 27, 34, 40, 71–72
  - ∀α<sup>(k)</sup>.τ (see type scheme)
  - (function type), 17, 24, 29
  - ↓ (restriction), 56
  - θ (see type function)
  - (θ, CE) (see type structure)
  - Λα<sup>(k)</sup>.τ (see type function)
  - Σ (see signature)
  - (N)S (see signature)
  - Φ (see functor signature)
  - (N)(S, (N’)S’) (see functor signature)
  - φ<sub>Ty</sub> (type realisation), 33
  - φ<sub>Str</sub> (structure realisation), 33
  - φ (realisation), 33, 34, 43
  - ≥ (see instance)
  - ⤵ (see generalisation and enrichment)
  - ⊢ (turnstile), 2, 23, 24, 36, 47, 56, 61

$\vdash_{\text{DYN}}$  (evaluation), 61  
 $\vdash_{\text{STAT}}$  (elaboration), 61  
 $\Rightarrow$ , 2, 23, 36, 47, 56, 61  
 $\langle \rangle$  (see options)

## A

*a* (see address)  
Abs (abstype operation), 22, 25  
abs, 46, 71, 74  
abstype, 3, 8, 22, 25, 65, 68  
abstype declaration, 8, 22, 25, 68  
addition of numbers (+), 4, 46, 71, 73, 75  
Addr (addresses), 44, 45  
address (*a*), 44  
  fresh, 49  
admissibility, 33  
and, 3, 12–14, 68  
andalso, 3, 64, 67  
appending lists (@), 4, 71, 73  
 $appexp$  (application expression), 66, 67  
application, 8, 24  
  of basic value (APPLY), 46, 50, 74  
  of (function) closure, 50  
  of value constructor, 49  
  of exception name, 49  
  of ref, 49  
  of :=, 49, 71  
  infix, 8  
application of functor (see functor application)  
application of type function, 19, 29  
application expression, 66, 67  
applicative type variable (see type variable)  
APPLY (see application)  
AppTyVar (applicative type variables), 5  
apptyvars (free applicative type variables), 17

arctan, 46, 71, 74  
arity  
  of type name, 16  
  of type function, 19, 40  
arrow type (see function type expression)  
as, 3, 9, 29, 53, 69  
assignment (:=), 45, 49, 71, 73  
 $atexp$  (atomic expression), 7, 8, 23, 48, 64, 67  
atomic expression, 7, 8, 23, 48, 64, 67  
  as expression, 8, 24, 49  
atomic pattern, 7, 9, 28, 52, 64, 69  
  as pattern, 9, 29, 53, 69  
 $atpat$  (atomic pattern), 7, 9, 28, 52, 64, 69

## B

*b* (see basic value)  
*B* (see basis)  
 $B_0$  (initial basis)  
  static, 70  
  dynamic, 73  
bare language, 1  
BasExName (basic exception names), 46, 73  
basic value (*b*), 44–46, 73–76  
basis (*B*), 1  
  static, 23, 31, 36, 61, 70  
  dynamic, 55, 61, 73  
  combined, 61  
Basis (bases), 31, 55, 61  
BasVal (basic values), 44–46, 73–76  
 $B_{\text{DYN}}$  (dynamic basis), 61  
Bind (exception), 46, 52  
bool, 70, 72  
bound names, 31, 32, 33  
 $B_{\text{STAT}}$  (static basis), 61

## C

*C* (context), 17, 18, 23, 23–30  
“Cannot open *s*”, 76

case, 3, 64, 67  
*CE* (constructor environment), 17, 21–22, 27, 41  
 chr, 46, 71, 74  
 Chr, 46, 74  
 Clos (closure of types etc.), 20–21, 25, 27, 39, 40  
 close\_in, 46, 72, 75, 76  
 close\_out, 46, 72, 76  
 Closure (function closures), 45  
     recursion, 47  
 closure rules (signatures and functors), 14, 38, 41, 42  
 coercion of numbers (*real*), 46, 71, 74  
 comments, 4, 5  
 composition of functions (*o*), 71, 73  
*con* (see value constructor)  
 Con (value constructors), 4, 45  
*conbind* (constructor binding), 7, 8, 27, 68  
 ConBind (constructor bindings), 7  
 concatenating strings (*^*), 4, 71, 73  
 ConEnv (constructor environments), 17  
 “consing” an element to a list (*::*), 70, 71, 72, 73  
 consistency  
     of type structures, 32, 41  
     of semantic object, 32, 33, 41  
 constant (see also value constant and exception constant)  
     special, 3  
 construction (see value construction and exception construction)  
 constructor binding (*conbind*), 7, 8, 27, 68  
 constructor environment (*CE*), 17, 21–22, 27, 41  
 ConsType (constructed types), 17  
 contents of (see dereferencing)  
 context (*C*), 17, 18, 23, 23–30  
 Context (contexts), 17  
 Core Language, 1

syntax, 3  
     static semantics, 16  
     dynamic semantics, 44  
 cos, 46, 71, 74  
 cycle-freedom, 32, 33

## D

datatype, 3, 8, 13, 25, 39, 55, 65, 68  
 datatype binding, 7, 8, 27, 68  
 datatype declaration, 8, 25, 68  
 datatype description, 11, 13, 40  
 datatype specification, 13, 39, 55  
*datbind* (datatype binding), 7, 8, 27, 68  
 DatBind (datatype bindings), 7  
*datdesc* (datatype description), 11, 13, 40  
 DatDesc (datatype descriptions), 11  
*dec* (declaration), 7, 8, 25, 51, 65, 68  
 Dec (declarations), 7  
 declaration (Core), 7, 8, 25, 51, 65, 68  
     as structure-level declaration, 12, 37, 57  
 dereferencing (*!*), 4, 71, 74  
 derived forms, 1, 6, 10, 63–65  
 Diff, 46, 75  
 digit  
     in identifier, 4  
     in integers and reals, 3  
*dir* (fixity directive), 6, 8, 10  
 directive, 8  
 disjoining bound names, 31, 33  
 div, 46, 71, 73, 75  
 Div, 46, 75  
 division of reals (*/*), 46, 71, 73, 75  
 do, 3, 64, 67  
 Dom (domain), 17  
 dynamic  
     semantics (Core), 44  
     semantics (Modules), 55  
     basis (see basis)

## E

- e* (exception value), 45
- [*e*] (see packet)
- E** (exponent), 3
- E* (environment)
  - static, 17, 22, 23, 25–26
  - dynamic, 45, 48–54, 56, 57
- EE* (see exception constructor environment)
- elaboration, 1, 2, 23, 36, 61
- else**, 3, 64, 67
- empty
  - declaration (Core), 8, 26, 51, 68
  - functor declaration, 14, 42, 60
  - functor specification, 14, 41
  - signature declaration, 12, 38, 58
  - specification, 13, 39, 59
  - structure-level declaration, 12, 37, 57
- en* (exception name), 44, 52
- end**, 3, 8–8, 12–13, 67–68
- end\_of\_stream**, 46, 72, 76
- enrichment ( $\succ$ ), 34, 36, 38, 42
- ens* (exception name set), 45, 52
- Env** (environments), 17, 45
- eqtype**, 10, 13, 39, 55
- equality
  - on abstract types, 22
  - of structures (sharing), 41
  - of type functions (sharing), 19, 41
  - of type schemes, 19
  - of values (=), 18, 71, 73, 75
- equality attribute
  - of type name, 16, 18, 21–22, 33, 39
  - of type variable, 4, 16, 18, 19
- equality type, 18, 71
- equality type function, 19
- equality type specification, 13, 39, 55
- equality type variable, 4, 16, 18, 19
- escape sequence, 3
- evaluation, 1, 2, 47, 56, 61
- exbind* (exception binding), 7, 8, 27, 52, 68
- ExBind** (exception bindings), 7
- exception**, 3, 8, 13, 25, 39, 51, 58, 68
- exception binding, 7, 8, 27, 52, 68
- exception constant (*excon* or *longexcon*)
  - as atomic pattern, 9, 28, 52, 69
- exception construction
  - as pattern, 9, 29, 53, 69
  - infix, as pattern, 6, 9, 69
- exception constructor
  - as atomic expression, 8, 23, 49, 67
- exception constructor environment (*EE*)
  - static, 17, 18, 27, 56
  - dynamic, 45, 52, 56
- exception convention, 48, 49, 50, 62
- exception declaration, 8, 25, 51, 68
- exception description, 11, 13, 40, 59
- exception name (*en*), 44
  - fresh, 52
- exception name set (*ens*), 45, 52
- exception packet (see packet)
- exception specification, 13, 39, 58
- exception value (*e*), 45
- excon* (see exception constant or constructor)
- ExCon** (exception constructors), 4
- ExConEnv** (exception constructor environments), 17, 45
- excons* (exception constructor set), 55, 59
- exdesc* (exception description), 11, 13, 40, 59
- ExDesc** (exception descriptions), 11
- execution, 1, 61
- exhaustive patterns, 30–30, 46
- exn**, 24, 28, 29, 40, 70, 72
- ExName** (exception names), 44
- ExNameSet** (exception name sets), 45
- exp* (expression), 7, 8, 24, 49, 64, 67
- Exp** (expressions), 7
- exp** (exponential), 46, 71, 74
- Exp**, 46, 74
- expansive expression, 20, 21
- explode** (a string), 46, 71, 74

expression, 7, 8, 24, 49, 64, 67  
 expression row, 7, 8, 24, 49, 67  
*exprow* (expression row), 7, 8, 24, 49, 67  
 ExpRow (expression rows), 7  
 ExVal (exception values), 45

## F

$F$  (functor environment), 31, 42, 55, 59, 60  
 FAIL (failure in pattern matching), 44, 48, 50, 52, 53, 54  
 false, 70, 71, 72  
 $\overset{\text{fn}}{\mapsto}$  (finite map), 16  
 Fin (finite subset), 16  
 floor, 46, 71, 74  
 Floor, 46, 74  
 fn, 3, 8, 9, 24, 50, 67  
 formatting character, 3  
 fun, 3, 63, 65, 68  
*funbind* (functor binding), 11, 14, 42, 59, 63, 65  
 FunBind (functor bindings), 11  
 function (*fn match*), 8, 24, 50, 67  
 function declaration (see *fun*)  
 function type ( $\rightarrow$ ), 17, 24, 29  
 function type expression ( $\rightarrow$ ), 9, 29, 69  
 function-value binding (*fvalbind*), 30, 63, 65, 68  
 functor, 10, 14, 41, 42, 60  
 functor application, 12, 36, 57, 65  
 functor binding, 11, 14, 42, 59, 63, 65  
 functor closure, 55, 57, 59  
 functor declaration, 11, 14, 42, 60  
   as top-level declaration, 14, 43, 60  
 functor description, 11, 14, 41  
 functor environment ( $F$ ), 31, 42, 55, 59, 60  
 functor identifier (*funid*), 10, 12, 14  
 functor signature ( $\Phi$ ), 31, 42, 43  
 functor signature expression, 11, 14, 42, 65

functor signature matching, 11, 43  
 functor specification, 11, 14, 41  
 FunctorClosure (functor closures), 55  
*fundec* (functor declaration), 11, 14, 42, 60  
 FunDec (functor declarations), 11  
*fundesc* (functor description), 11, 14, 41  
 FunDesc (functor descriptions), 11  
 FunEnv (functor environments), 31, 55  
*funid* (functor identifier), 10, 12, 14  
 FunId (functor identifiers), 10  
*funsigexp* (functor signature expression), 11, 14, 42, 65  
 FunSigExp (functor signature expressions), 11  
*funspec* (functor specification), 11, 14, 41  
 FunSpec (functor specifications), 11  
 FunType (function types), 17  
*fvalbind* (function-value binding), 63, 65, 68  
   exhaustive, 30

## G

$G$  (signature environment), 31, 38, 55, 58  
 generalisation ( $\succ$ ), 19, 23, 28, 29, 34  
 generative signature expression, 12, 38, 58  
 generative structure expression, 12, 36, 57  
 grammar, 1  
   for the Core, 6, 66  
   for Modules, 10

## H

handle, 3, 8, 24, 50, 67

## I

$I$  (interface), 55, 58, 58–59

*IB* (interface basis), 55, 56, 58–59, 59  
 identifier (*id*), 4, 10  
     alphanumeric, 4  
     symbolic, 4  
*IE* (interface environment), 55, 59  
 if, 3, 64, 67  
 imperative attribute, 16, 19  
 imperative type, 19, 27, 28  
 imperative type variable (see type variable)  
 implementation, 1, 61  
 implode (a string list), 46, 71, 75  
 ImpTyVar (imperative type variables), 4  
 imptyvars (free imperative type variables), 17, 37  
 in (injection), 18  
 in, 3, 8, 12, 13, 64, 67, 68  
 include, 10, 13, 39, 59  
 inference, 2  
 inference rules  
     static semantics (Core), 23  
     static semantics (Modules), 36  
     dynamic semantics (Core), 47  
     dynamic semantics (Modules), 56  
*infixp* (infix expression), 66, 67  
 InfExp (infix expressions), 66, 67  
 infix, 3, 5, 6, 8, 68  
 infix expression, 6, 8, 66, 67  
 infix pattern, 6, 9, 69  
 infix identifiers, 5, 6, 8, 10, 67, 68, 69, 71  
*infixr*, 3, 5, 6, 8, 68  
 initial basis, 2, 70, 73  
 injection (in), 18  
 input, 46, 72, 76  
 input/output, 72, 75  
 instance ( $\geq$ )  
     of signature, 33, 34, 35, 38, 39  
     of functor signature, 33, 36  
     in matching, 34  
 instream, 70, 72, 75  
 int, 70, 72

Int (interfaces), 55  
 IntBasis (interface bases), 55  
 integer constant, 3, 72  
 IntEnv (interface environments), 55  
 Inter, 55, 58, 59  
 interaction, 1, 61  
 interface (*I*), 55, 58, 58–59  
 interface basis (*IB*), 55, 56, 58–59, 59  
 interface environment (*IE*), 55, 59  
 Interrupt, 46, 62  
 Io, 46, 76  
 irredundant patterns, 30–30, 46  
 it, 65

## L

L (left associative), 7  
*lab* (label), 4, 5  
 Lab (labels), 4, 5  
 let, 3  
     expression (Core), 8, 24, 49, 64, 67  
     expression (Modules), 12, 36, 57  
 letter in identifier, 4  
 lexical analysis, 5, 6  
 list, 70, 72  
 list reversal (*rev*), 71, 74  
 ln, 46, 71, 74  
 Ln, 46, 74  
 local, 3  
     declaration (Core), 8, 26, 51, 68  
     declaration (Modules), 12, 37, 57  
     specification (Modules), 13, 39, 59  
 long identifiers (e.g. *longexcon*), 4  
 lookahead, 46, 72, 76

## M

*m* (structure name), 16, 17, 18, 31, 32, 33, 34, 38, 41, 45  
     fresh, 36, 37  
*M* (structure name set), 31, 36  
 map, 71, 74  
 match (*match*), 7, 8, 25, 51

irredundant, 30, 46  
 exhaustive, 30, 46  
 in closure, 45, 47  
 Match, 7  
 Match (exception), 46, 50  
 match rule, 7, 8, 25, 51  
 matching  
   signatures (see signature matching)  
   functor signatures (see functor signature matching)  
*mem* (memory), 45, 49, 53  
 Mem (memories), 45  
 memory (*mem*), 45, 49, 53  
 mod, 46, 71, 73, 75  
 Mod, 46, 75  
 modification (+)  
   of finite maps, 17  
   of environments, 18, 48  
 module, 11  
 Modules, 1  
*mrule* (match rule), 7, 8, 25, 51  
 Mrule (match rules), 7  
 multiplication of numbers (\*), 46, 71, 73, 75

## N

*n* (name, see structure name, type name and exception name)  
*N* (name set), 31, 36  
*n*-tuple, 64, 67, 69  
 name  
   of structure (*m*), 16, 17, 18, 31, 32, 33, 34, 36, 37, 38, 41, 45  
 name set (*N*), 31, 36  
 names (free names), 31, 32, 36, 42  
 NameSet (name sets), 31  
 Natural Semantics, 2  
 negation of booleans (not), 71, 74  
 negation of numbers (~), 3, 46, 71, 74  
 nil, 64, 70, 71, 72  
 non-expansive expression, 20, 21

nonfix, 3, 6, 8, 10, 68, 71  
 nonfix identifiers, 6, 8, 10, 68, 71  
 not, 71, 74  
 num, 71

## O

o (function composition), 71, 73  
 occurrence  
   substructure, 31  
 of (projection), 18, 31  
 of, 3  
   in case expression, 64, 67  
   in constructor binding, 8  
   in exception binding, 8, 44  
   in exception description, 13, 55  
 op, 3, 6  
   on variable or constructor, 8, 9, 67, 68, 69  
   in constructor binding, 8, 68  
 open, 3, 4, 8, 13, 26, 51, 55, 59, 65, 68  
 open\_in, 46, 72, 75, 76  
 open\_out, 46, 72, 75, 76  
 opening structures in declarations, 8, 26, 51, 68  
 opening structures in specifications, 13, 14, 39, 59  
 options, 7  
   first (< >), 23, 38  
   second (<< >>), 23  
 ord (of string), 46, 71, 74  
 Ord, 46, 74  
 or\_else, 3, 64, 67  
 output, 46, 72, 76  
 "Output stream is closed", 76  
 outstream, 70, 72, 75

## P

*p* (see packet)  
 Pack (packets), 45  
 packet (*p*), 45, 48, 50, 56, 61–62  
 parsing, 1, 61

*pat* (pattern), 7, 9, 29, 53, 64, 69  
 Pat (patterns), 7  
*patrow* (pattern row), 7, 9, 28, 53, 64, 69  
 PatRow (pattern rows), 7  
 pattern, 7, 9, 29, 53, 64, 69  
   layered, 9, 29, 53, 69  
 pattern matching, 44, 46, 30–30, 53  
   with *ref*, 53  
 pattern row, 7, 9, 28, 53, 64, 69  
 polymorphic  
   functions, 23, 25, 28  
   references, 20, 21, 25, 37, 71  
   exceptions, 20, 27, 37, 40  
 precedence, 7, 66  
 principal  
   environment, 30, 37  
   signature, 35, 39, 42  
 Prod, 46, 75  
 product type (\*), 64, 69  
 program (*program*), 1, 61–62  
 Program (programs), 61  
 projection (of), 18, 31

## Q

Quot, 46, 75

## R

*r* (record), 45, 49, 52, 53  
 R (right associative), 7  
 raise, 3, 8, 24, 25, 48, 50, 61, 67  
 Ran (range), 17  
 real  
   the type, 70, 72  
   coersion, 46, 71, 74  
 real constant, 3, 72  
 realisation ( $\varphi$ ), 33, 34, 43  
 rec, 3, 8, 9, 47, 52, 68  
 Rec (recursion operator), 47, 50, 52  
 record  
   *r*, 45, 49, 52, 53

  as atomic expression, 8, 23, 49, 64, 67  
   as atomic pattern, 9, 28, 52, 64, 69  
   selector (*# lab*), 3, 64, 67  
   type expression, 9, 29, 69  
   type ( $\rho$ ), 17, 24, 28, 29  
 Record (records), 45  
 RecType (record types), 17  
 recursion (see *rec*, *Rec*, and *fun*)  
 ref  
   the type constructor, 70, 72  
   the type name, 19, 70, 71, 72  
   the value constructor, 44, 49, 53, 71, 72, 74  
 reserved words, 3, 10  
 restrictions  
   closure rules (see these)  
   syntactic (Core), 9, 30–30  
   syntactic (Modules), 12  
 rev, 71, 74

## S

*s* (state), 45, 47, 49, 53, 56, 61–62  
*S* (structure), 17, 31, 32, 34, 36, 38, 45  
 scope  
   of constructor, 5, 18  
   of value variable, 5, 18  
   of fixity directive, 6, 10  
   of explicit type variable, 19–20, 26  
*SE* (structure environment)  
   static, 17, 18, 31, 34, 38, 40, 70  
   dynamic, 45, 56, 58, 73  
 semantic object, 2  
   simple (Static), 16  
   simple (Dynamic), 44  
   compound (Core, Static), 16, 17  
   compound (Core, Dynamic), 45  
   compound (Modules, Static), 31  
   compound (Modules, Dynamic), 55



- sentence, 2, 23, 36, 47, 56, 61
- separate compilation, 11, 14–15, 43
- sequential
  - expression, 64, 67
  - declaration (Core), 8, 26, 51, 68
  - functor declarations, 14, 42, 60
  - functor specification, 14, 41
  - signature declaration, 12, 38, 58
  - specification, 13, 39, 59
  - structure-level declaration, 12, 37, 57
- shareq* (sharing equation), 11, 13, 41, 55
- SharEq (sharing equations), 11
- sharing, 14–15, 37, 38, 40, 41, 43
  - equations, 11, 13, 41, 55
  - specification, 13, 39
  - of structures, 13, 41
  - of types, 13, 41
  - multiple, 13, 41
- sharing, 10, 13, 39
- side-condition, 47, 56
- side-effect, 56, 62
- sig, 10, 12, 38, 58
- Sig (signatures), 31
- sigbind* (signature binding), 11, 12, 39, 58
- SigBind (signature bindings), 11
- sigdec* (signature declaration), 11, 12, 38, 58
- SigDec (signature declarations), 11
- SigEnv (signature environments), 31, 55
- sigexp* (signature expression), 11, 12, 38, 58
- SigExp (signature expressions), 11
- sigid* (signature identifier), 10, 12, 38, 58
- SigId (signature identifiers), 10
- signature ( $\Sigma$ ), 31, 32, 33, 34, 35, 38, 39, 42, 43, 56
- signature, 10, 12, 38, 58
- signature binding, 11, 12, 39, 58
- signature declaration, 11, 12, 38, 58
  - in top-level declaration, 14, 43, 60
- signature environment ( $G$ )
  - static, 31, 38, 39, 43
  - dynamic, 55, 56, 58, 60
- signature expression, 11, 12, 38, 58
- signature identifier, 10, 12, 38, 58
- signature instantiation (see instance)
- signature matching, 34, 36–37, 38, 42
- sin, 46, 71, 74
- size (of strings), 46, 71, 74
- spec* (specification), 11, 13, 39, 58
- Spec (specifications), 11
- specification, 11, 13, 39, 58
- sqrt (square root), 46, 71, 74
- Sqrt, 46, 74
- state ( $s$ ), 45, 47, 49, 53, 56, 61–62
- State, 45
- state convention, 48, 49
- static
  - basis, 1, 23, 31, 36, 61, 70
  - semantics (Core), 16
  - semantics (Modules), 31
- std\_in*, 46, 72, 76
- std\_out*, 46, 72, 76
- Str (structures), 17
- strbind* (structure binding), 11, 12, 38, 58
- StrBind (structure bindings), 11
- strdec* (structure-level declaration), 11, 12, 37, 57
- StrDec (structure-level declarations), 11
- strdesc* (structure description), 11, 13, 40, 59
- StrDesc (structure descriptions), 11
- stream (input/output), 75
- StrEnv (structure environments), 17, 45
- strexpr* (structure expression), 11, 12, 36, 57, 65
- StrExp (structure expressions), 11
- strid* (structure identifier), 4

as structure expression, 12, 36, 57  
 StrId (structure identifiers), 4  
 string, 70, 72  
 string constant, 3, 72  
 StrName (structure names), 16  
 strnames (free structure names), 31  
 StrNameSet (structure name sets), 31  
 struct, 10, 12, 36, 57, 65  
 structure ( $S$  or  $(m, E)$ ), 17, 31, 32, 34, 36, 38, 45  
 structure, 10, 12, 13, 37, 39, 57, 59  
 structure binding (*strbind*), 11, 12, 38, 58  
 structure declaration, 12, 37, 57  
 structure description (*strdesc*), 11, 13, 40, 59  
 structure environment (*SE*)  
   static, 17, 18, 31, 34, 38, 40, 70  
   dynamic, 45, 56, 58, 73  
 structure expression (*strexpr*), 11, 12, 36, 57, 65  
 structure identifier (*strid*), 4  
   as structure expression, 12, 36, 57  
 structure-level declaration (*strdec*), 11, 12, 37, 57  
   in top-level declaration, 14, 42, 60  
 structure name ( $m$ , see name)  
 structure name set ( $M$ ), 31, 36  
 structure realisation ( $\varphi_{\text{Str}}$ ), 33  
 structure specification, 13, 39, 59  
 substructure, 31  
   proper, 31, 32  
 subtraction of numbers ( $-$ ), 46, 71, 73, 75  
 Sum, 46, 75  
 Supp (support), 33  
 symbol, 4  
 syntax, 3, 10, 44, 55, 66

## T

$t$  (type name), 16, 19, 21–22, 25, 27, 30, 31, 32, 33, 34, 40, 72  
 $T$  (type name set), 17, 31  
 $TE$  (type environment), 17, 21–22, 27, 34, 40, 56  
 then, 3, 64, 67  
*topdec* (top-level declaration), 11, 14, 42, 60  
   in program, 61–62  
 TopDec (top-level declarations), 11  
 top-level declaration, 1, 11, 14, 42, 60  
 true, 70, 71, 72  
 truncation of reals (*floor*), 46, 71, 74  
 tuple, 64, 67, 69  
 tuple type, 64, 69  
*ty* (type expression), 7, 9, 29, 44, 64, 69  
*Ty* (type expressions), 7, 9  
*tycon* (type constructor), 4, 8, 9, 13, 17, 21–22, 27, 29, 32, 34, 40, 41, 72  
 TyCon (type constructors), 4  
 TyEnv (type environments), 17  
 TyName (type names), 16  
 tynames (free type names), 17, 36  
 TyNameSet (type name sets), 17  
*typbind* (type binding), 7, 8, 27, 44, 68  
*TypBind* (type bindings), 7  
*typdesc* (type description), 11, 13, 40, 55  
*TypDesc* (type descriptions), 11  
 type ( $\tau$ ), 17, 18, 19, 20, 23–25, 28, 29  
 Type (types), 17  
 type, 3, 8, 13, 25, 39, 41, 44, 55, 68  
 type binding, 7, 8, 27, 44, 68  
 type constraint ( $:$ )  
   in expression, 8, 24, 44, 67  
   in pattern, 9, 29, 44, 69  
 type construction, 9, 29  
 type constructor (*tycon*), 4, 8, 9, 13, 17, 21–22, 27, 29, 32, 34, 40, 41, 72  
 type constructor name (see type name)  
 type declaration, 8, 25, 44, 68

type description (*tydesc*), 11, 13, 40, 55  
 type environment (*TE*), 17, 21–22, 27, 34, 40, 56  
 type expression, 7, 9, 29, 44, 64, 69  
 type-expression row (*tyrow*), 7, 9, 29, 44, 69  
 type function ( $\theta$ ), 17, 18–19, 21–22, 27, 32, 33, 34, 40, 41, 72  
 type name (*t*), 16, 19, 21–22, 25, 27, 30, 31, 32, 33, 34, 40, 72  
 type name set, 17, 31  
 type realisation ( $\varphi_{\text{Ty}}$ ), 33  
 type scheme ( $\sigma$ ), 17, 19, 20–21, 23, 28, 34, 40, 71–72  
 type specification, 13, 39, 55  
 type structure ( $\theta$ , *CE*), 17, 21–22, 25, 27, 29, 32, 34, 39, 40, 41, 71–72  
 type variable (*tyvar*,  $\alpha$ ), 4, 9, 16  
   in type expression, 9, 29, 69  
   equality, 4, 16, 18, 19  
   imperative, 4, 16, 17, 19, 21, 25, 27, 28, 30, 37  
   applicative, 5, 16, 17, 19, 21, 25, 27, 28  
   explicit, 19–20, 25, 26  
 type vector ( $\tau^{(k)}$ ), 17, 18, 19  
 TypeFcn (type functions), 17  
 TypeScheme (type schemes), 17  
*tyrow* (type-expression row), 7, 9, 29, 44, 69  
 TyRow (type-expression rows), 7, 9  
 TyStr (type structures), 17  
*tyvar* (see type variable)  
 TyVar (type variables), 4, 16  
 tyvars (free type variables), 17  
*tyvarseq* (type variable sequence), 7  
 TyVarSet, 17

## U

*U* (explicit type variables), 17, 20, 25, 26

unit, 72  
 unguarded type variable, 20

## V

*v* (value), 45, 48–51  
 Val (values), 45  
 val, 3, 8, 13, 25, 39, 51, 58, 68  
*valbind* (value binding), 7, 8, 20, 21, 25, 26, 52, 68  
   simple, 8, 26, 52, 68  
   recursive, 8, 26, 27, 52, 68  
 Valbind (value bindings), 7  
*valdesc* (value description), 11, 13, 40, 59  
 ValDesc (value descriptions), 11  
 value binding (*valbind*), 7, 8, 20, 21, 25, 26, 52, 68  
   simple, 8, 26, 52, 68  
   recursive, 8, 26, 27, 52, 68  
 value constant (*con*)  
   in pattern, 9, 28, 52, 69  
 value constructor (*con*), 4  
   as atomic expression, 8, 23, 49, 67  
   scope, 5, 18  
 value construction  
   in pattern, 9, 29, 53, 69  
   infix, in pattern, 9, 69  
 value declaration, 8, 20, 25, 51, 68  
 value description (*valdesc*), 11, 13, 40, 59  
 value variable (*var*), 4  
   as atomic expression, 8, 23, 48, 67  
   in pattern, 9, 28, 52, 69  
 value specification, 13, 39, 58  
*var* (see value variable)  
 Var (value variables), 4  
 VarEnv (variable environments), 17, 45  
 variable (see value variable)  
 variable environment (*VE*)  
   static, 17, 18, 20–21, 25, 26, 27, 28, 29, 34, 40, 56, 71–72

dynamic, 45, 47, 52, 53, 56, 73  
*vars* (set of value variables), 55, 59  
*VE* (see variable environment)  
via  $\varphi$ , 34, 43  
view of a structure, 38, 41, 55, 57, 58

## W

well-formed  
  type environment, 21  
  signature, 32  
  functor signature, 32  
  assembly, 32, 33  
while, 3, 64, 67  
wildcard pattern ( $\_$ ), 9, 28, 52, 69  
wildcard pattern row ( $\dots$ ), 3, 9, 28,  
  30, 53, 69  
with, 3, 8, 68  
withtype, 3, 63, 65, 68

## Y

Yield, 33

**Copyright © 1988, Laboratory for Foundations of Computer Science,  
University of Edinburgh. All rights reserved.**

**Reproduction of all or part of this work  
is permitted for educational or research use  
on condition that this copyright notice is  
included in any copy.**